

# Anchors

**Anchor Straps** 

Fall Safe

Cable Cross-Arm Strap

Part #	Length	Weight Cap.	Attachment Point(s)
FS830-12	12'	310 lbs	2 Pass-through D-Rings
FS830-C6	6'	310 lbs	2 Pass-through D-Rings

#### Cross-Arm Strap



Part #	
C88811_H\M	

# Heavy Duty Cross-Arm Strap

- Heavy-duty
- 1-3/4" and 3' webbing
- 6' length

Part #	Length	Weight Cap.	Attachment Point(s)
FS810	6'	310 lbs	2 Pass-through D-Rings

## Medium Duty Cross-Arm Strap

- Medium-duty 6'; 1-3/4" webbing
- Forged steel pass-through D-rings

Part #	Length	Weight Cap.	Attachment Point(s)
FS811	6'	310 lbs	2 Pass-through D-Rings
FS811-12	12'	310 lbs	2 Pass-through D-Rings
FS811-16	16'	310 lbs	2 Pass-through D-Rings
FS811-3	3'	310 lbs	2 Pass-through D-Rings



# **Anchors**

**Beam Anchors** 

Fall Safe

## Affordable Quality Anchor

- Patented one-handed double-action quick-release latch
- Centered D-ring prevents jamming on beam flange for smoother sliding
- Patented double-toothed latch

Part #	Length	Fits Beam Flange Width
FS861	18.5"	3.5" - 14"

#### Girder Grip



- Mobile anchorage point for metal/steel structures
- Can be used vertically or horizontally
- Fits 3/4" diameter hole

Part #	Length	Dia.	Weigth Cap.
FS885	9.5"	1.38"	310

## Premier Beam Anchor

- Reduced friction nylon rollers
- Center positioning retainer prevents jamming on beam
- Double-toothed pawl

Part #	Overall Length	Fits Beam Flange Width
FS860	19"	3.5" - 14"

#### Stationary Beam Clamp

- Fits vertical and horizontal positions
- 2 Handled locking wing nuts
- 2 Attachment points (snap hook, carabiners, lifelines)
- Fits up to 12" wide and 1" thickness

Part #	Length	Fits Beam Flange Width
FS865	19"	up to 12"



# Anchors

**Removable Anchors** 

Fall Safe

## Removable Concrete Hole Anchor



- Exclusive "Easy Button" feature boosts productivity by providing immediate anchor removal
- Virtually eliminates the need for tools to remove a stuck anchor from a hole giving the user instant mobility
- The anchor can be set as hard as desired, without fear of getting the anchor stuck in a hole

Part #	Length	Dia.
FS876	used with 5/8 in (15.88 mm) to 3/4 in	3"
	(19.05 mm) rope only	

#### **Roof Anchors**

#### **Fall Safe**

## Non-Swivel Roof Anchor

- Reusable
- Steel construction
- Powder-coated

Part #	Overall Length	Width of Plate	# of Holes
FS870	11"	3"	16



## **Anchors**

#### **Roof Anchors**

#### Fall Safe

#### Roof Ring Anchor



**Description** Reusable roof anchor for wood or metal. Installs with 3 threaded fastners or 6 nails.

Used for fall protection-anchor point.

**Length** 9 in (228.6 mm)

**Width** 3 in (76.2 mm)

Weight 1.75 lbs (0.79 kg)

**Thickness** 0.25 in (6.35 mm)

Ring 3 in (76.2 mm) with opening diameter of 2.25 in (57.15 mm)

**Max. Cap.** Single person - 310 lbs (140.61 kg) including person, tools, and materials

Materials Forged steel

Min Tensile Strength 5000 lbs (2267.96 kg)

Applicable Standards Meets OSHA 1926-502 - ANSI Z359.1-2007 - ANSI A10.32 2004

Part #	Description
FS-EX310	Reusable roof anchor for wood or metal.

#### Standing Seam Clamp Anchor



- Deluxe standing seam anchor
- Includes D-ring and slot for retractable device
- Swivels a full 360 degrees
- Powder-coated

Part #	Adj Length	Working Load
FS874	24"	400 lbs



## **Anchors**

**Roof Anchors** 

**Fall Safe** 

Standing Seam Roof Anchor



**Description** The FallSafe metal standing seam roof clamp is a rated roof anchor point designed for

sloped or flat roofs. Must be rated to meet OSHA, federal, state and local government regulations for fall protection anchor points. MINIMUM required substrate thickness: 24

gauge

VISUALLY INSPECT UNIT BEFORE INSTALLATION

**Length** 6 in (152.5 mm)

**Height** 4 in (101.6 mm)

**Width** 2"+ (Expands based on seam width)

Material Carbon steel

Working Load 310 lbs (140.61 kg) - Designed for single person use

Min Tensile Strength 5,000 lbs (2267.96 kg)

**Weight** 7 lbs (3.18 kg)

**Installation Instructions** 

- 1. Adjust leg of anchor to align with the spacing of the roof seam -
- minimum 4 ft (1.22 m) from edge
- 2. Bent sides of clamps must be hooked underneath lip of seam. Flat
- sides must be flush with flat side of seam before tightening.
- 3. Tighten clamps to secure assembly to metal deck seam. Torque each bolt to 50' pounds. Top 2 bolts first, then bottom 2 bolts.

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.1-2007 - ANSI A10.32 2004

Part #	Description
FS-EX311	Non-Penetrating Standing Seam Roof Anchor



# Connectors

Carabiners

Fall Safe

#### Carabiner



Part #	Description
FS1015	Steel Carabiner
FS1017	Large Steel Carabiner

## **Extreme Lanyards**

#### Fall Safe

#### Adjustable Shock Lanyard



- Energy-absorbing lanyards with double-locking snap hooks
  - 1" Polyester webbing
  - 3,600 lbs gate-rated snap hooks
  - Adjustable range 4'-6'

Part #	Length	Weight Cap.	Attachment Point(s)
FS560-AJ	6'	310 lbs	2 Snap hooks

## Dual Leg Heavyweight Shock Lanyard

Part #	Length	Weight Cap.	Attachment Point(s)
FS88661-HW	6'	400 lbs	3 Snap hooks

## Dual Leg Shock Lanyard

Part #	Length	Weight Cap.	Attachment Point(s)
FS561	6'	310 lbs	3 Snap hooks

#### Dual Leg Shock Lanyard with Rebar Hook

Part #	Length	Weight Cap.	Attachment Point(s)
FS566	6'	310 lbs	2 Snap hooks

## Dual Leg Stretch Shock Lanyard

Part #	Length	Weight Cap.	Attachment Point(s)
FS591	4'	310 lbs	3 double action snap hooks



## Connectors

**Extreme Lanyards** 

**Fall Safe** 

Dual Leg Stretch Shock Lanyard with Rebar Hooks



Part #	Length	Weight Cap.	Attachment Point(s)
FS596	4'	310 lbs	1 Snap hook 2 Rebar hook

#### Dual Leg Tie Back Lanyard

Fall arrest lanyard with three snap hooks. Hook with shock pack attaches to harness D-ring. Other two ends wrap around anchor points and attach back to lanyard via tie-back rings.

Part #	Length	Weight Cap.	Attachment Point(s)
FS456	6'	310 lbs	3 double action snap hooks

#### Heavyweight Lanyards



- 1" Polyester webbing with tensile strength > 5,000 lbs
  - Rated up to 400 lbs.
  - Double-locking snap hooks

Part #	Length	Weight Cap.	Attachment Point(s)
FS88660-HW	6'	400 lbs	2 Snap hooks

#### Shock Lanyard



- Energy-absorbing lanyard with double-locking snap hooks
  - 1" Polyester webbing
  - 3,600 lbs gate-rated snap hooks

Part #	Length	Weight Cap.	Attachment Point(s)
FS560	6'	310 lbs	2 Snap hooks
FS560-4	4'	310 lbs	2 Snap hooks



# Connectors

**Extreme Lanyards** 

Fall Safe

## Shock Lanyard with Rebar Hook



- 1" Polyester webbing
  - Rebar hook designed to fit Symons Form
  - 3,600 lbs gate-rated hooks

Other Options: FS566 Dual-leg lanyard for 100% tie-off

Part #	Length	Weight Cap.	Attachment Point(s)
FS565	6'	310 lbs	1 Rebar hook

## Steamline Shock Lanyard with Rebar Hook



- Double-locking rebar hook designed to fit Symons Form
- 3,600 lbs gate-rated snap hook and rebar hook

Part #	Length	Weight Cap.	Attachment Point(s)
FS585	6'	310 lbs	1 Snap hook 1 Rebar hook



# Connectors

## **Extreme Lanyards**

## Fall Safe

#### Streamline Shock Lanyard



- Double-locking snap hooks
- Tubular webbing
- 3,600 lbs gate-rated

Part #	Length	Weight Cap.	Attachment Point(s)
FS580	6'	310 lbs	2 Snap hooks

#### Stretch Shock Lanyard



- Double-locking snap hook
  - Stretch tubular webbing
  - 4'-6' Maneuverability
  - 3,600 lbs gate-rated snap hooks

Part #	Length	Weight Cap.	Attachment Point(s)
FS590	4'	310 lbs	2 Snap hooks

## Stretch Shock Lanyard with Rebar Hook



- Rebar hook designed to fit Symons Form
- Stretch tubular webbing
- 4'-6' Maneuverability
- 3,600 lbs gate-rated snap hook and rebar hook

Part #	Length	Weight Cap.	Attachment Point(s)
FS595	4'	310 lbs	1 Snap hook 1 Rebar hook



## Connectors

## **Extreme Lanyards**

## Fall Safe

#### Tie Back Lanyard



- 1" Polyester webbing with tensile strength > 5,000 lbs
  - Double-locking tie-back hook and snap hook
  - 6' Length
  - Clear shock pack for easy inspection

Other Options: FS451 Dual-leg lanyard for 100% tie-off

Part #	Length	Weight Cap.	Attachment Point(s)
FS450	6'	310 lbs	1 Snap Hook 1 tie back hook

## **FSP Lanyard**

#### **Fall Safe**

#### Welding and Fire Rated Lanyards

- Nomex® cover/polyester core
- Prevents welding burn slag
- Surface at 700° F
- Designed specifically for welders

Part #	Length	Weight Cap.	Attachment Point(s)
FS77430-WE	6'	310 lbs	2 Snap hooks

# Positioning Assemblies Fall Safe Positioning Device Part # Description FS060 13" Rebar chain assembly

# Rope & Rope Lifelines Fall Safe

#### \_ .. \_

## Bulk Rope

Part #	Dia	Length	Material
FS700-581200	5/8"	1200'	Polyester-dacron Blend
FS700-58600	5/8"	600'	Polyester-dacron Blend



# Connectors

Rope & Rope Lifelines

Fall Safe

Rope Lifelines

Part #	Dia	Length	Material
FS700-100	5/8"	100'	Polyester-dacron Blend
FS700-25	5/8"	25'	Polyester-dacron Blend
FS700-50	5/8"	50'	Polyester-dacron Blend

## Rope Termination Plate

- Rope anchor replaces splicing in synthetic rope
- Use with 5/8" and 3/4" rope
- Carabiner and rope sold separately

Part #	Description	
FS875	Rope termination plate replaces splicing in synthetic ropes. To	
	be used with 5/8 in (15.88 mm) to 3/4 in (19.05 mm) rope only.	

## **Rope Grabs**

#### **Fall Safe**

#### Removable Trailing Rope Grab

- For 5/8" rope
- Stainless steel
- Meets OSHA 1926-502, ANSI Z359.1-2007 and A10.32 2004

Part #	Length of Body	Length of Actuator	Eye Dia.	Rope Size
FS1118	4.05"	3.18"	2.16"	5/8"

## Removable Trailing Rope Grab with 3 FtShock Absorber

- For 5/8" rope
- Stainless steel
- Meets OSHA 1926-502, ANSI Z359.1-2007 and A10.32 2004

Part #	Length of Body	Length of Actuator	Eye Dia.	Rope Size
FS1118-3	4.05"	3.18"	2.16"	5/8"



# Connectors

**Rope Grabs** 

Fall Safe

Stationary Manual Rope Grab with 3 Ft Shock Absorber

- For 5/8" rope
- Dual-cam
- Non-removable
- Nickel-plated steel
- Meets OSHA 1926-502, ANSI Z359.1-2007 and A10.32 2004

Part #	Length of Body	Length of Actuator	Eye Dia.	Rope Size
FS1117-3	3.86"	3.07"	.78"	5/8"

## Harnesses

**Exteme Harnesses** 

Fall Safe

Heavyweight 3 D-Ring Harness

Part #	Size
FS99281-HW3X/4X	3X/4X

## Heavyweight Single D-Ring Harness

- Single back D-ring
- Multiple adjustment points
- Universal sizing

Part #	Size
FS99280-E	Universal
FS99280-HW3X/4X	3X/4X



## Harnesses

#### **Extreme Harnesses**

#### Fall Safe

## No-Tangle 3 D-Ring Harness

- No-tangle D-ring pad reduces web knotting and relieves D-ring back pressure
- Back D-ring
- Convenient lanyard keepers
- Fall arrest indicators
- · Pass-through chest buckles
- Grommet leg straps

Part #	Size
FS285LXL	L/XL
FS285S/M	S/M
FS285XXL	L/XL

#### No-Tangle Construction Harness

- No-tangle D-ring pad reduces web knotting and relieves D-ring back pressure
- Premium internal foam back support.
- Removable comfort shoulder pads
- · Back D-ring
- Fall arrest indicators
- Convenient lanyard keepers
- · Pass-through chest buckles
- Free-floating comfort back pad
- Grommet leg straps

Part #	Size
FS160-2XL	2X-Large
FS160-L	Large
FS160-M	Medium
FS160-S	Small
FS160-XL	X-Large



# Harnesses

## **Extreme Harnesses**

#### Fall Safe

## No-Tangle Construction Harness with Built in Tool Pouch



The popular FS170 with permanently attached tool pouches.

- Removable comfort shoulder pads
- Back D-ring
- No-tangle back pad
- Fall arrest indicators
- Convenient lanyard keepers
- Fixed tool pouch
- Pass-through chest buckles
- Fixed back pad
- Grommet leg straps

Part #	Size
FS175-L	Large
FS175-M	Medium
FS175-XL	X-Large



# Harnesses

**Extreme Harnesses** 

Fall Safe

## No-Tangle Single D-Ring Grommet Harness



- No-tangle D-ring pad reduces web knotting and relieves D-ring back pressure
- Back D-ring
- Convenient lanyard keepers
- Fall arrest indicators
- Pass-through chest buckles
- Grommet leg straps

Part #	Size
FS185-2XL-PL	2X-Large
FS185LXL	L/XL
FS185-LXL	L/XL
FS185LXL-BLACK	L/XL
FS185SM	S/M
FS185SM-BLACK	S/M
FS185-SM-PL	S/M
FS185XXL	X-Large



# Harnesses

Flex Harness

Fall Safe

#### Flex253 Premium Construction Harness



Developed by FallSafe USA in cooperation with ergonomics experts and university professors, using wearability/ergonomic principles for premium comfort.

Internal memory foam cells for optimal fit and impact absorption. External foam with high hardness stability. Incorporates all aluminum D-rings.

- · 2nd skin shoulder pad
- Back D-ring
- Quick-release leg buckles
- Side positioning D-rings
- · Convenient lanyard keepers
- Fall arrest indicators
- Free-floating comfort back pad
- Removable grommet belt
- Cool-air leg pads

Part #	Size
FS-FLEX253-M	Medium



# Harnesses

**Flex Harness** 

Fall Safe

## Flex280 Comfort Harness



Designed for ultimate comfort, the FS-FLEX280 incorporates high-tech components for optimum service and wear.

- 2nd skin shoulder pad
- · Back D-ring
- Convenient lanyard keepers
- Fall arrest indicators
- Quick-release chest and leg buckles

Part #	Size
FS-FLEX280-L/XL	L/XL
FS-FLEX280-S/M	S/M
FS-FLEX280-XXL	XXL

## Harnesses

Flex Harness

Fall Safe

## Flex360 Premium Construction Harness



Developed by FallSafe USA in cooperation with ergonomics experts and university professors, using wearability and ergonomic principles for premium comfort.

Internal memory foam cells for optimal fit and impact absorption. External foam with high-hardness stability.

- 2nd skin shoulder pad
- · Back D-ring
- Quick-release chest buckle
- Side positioning D-rings
- · Convenient lanyard keepers
- Fall arrest indicators
- Free-floating comfort back pad
- Grommet leg straps

Part #	Size
FS-FLEX360-2XL	2X-Large
FS-FLEX360-L	Large
FS-FLEX360-M	Medium
FS-FLEX360-XL	X-Large



## Harnesses

## **FSP Harnesses**

#### Fall Safe

#### **Derrick Harness**



- No-tangle D-ring pad reduces web knotting and relieves D-ring back pressure
- Removable comfort shoulder pads and no tangle pad
- Double-slot D-ring
- Fall arrest indicators
- Convenient lanyard keepers
- Firm back support
- Seat sling attached
- Grommet leg straps

Part #	Size
FS-OD1115/L	Large
FS-OD1115/M	Medium
FS-OD1115/XL	X-Large
FS-OD1115/XXL	2X-Large

## Welding Harness



- Nomex® cover/polyester cone
- Prevents welding burn slag
- Surface at 700° F
- Designed specifically for welders

Part #	Size
FS77425-WE-LXL	L/XL
FS77425-WE-XXL	2X-Large

#### **V-Line Harnesses**

#### Fall Safe

## Value Harness with Pass Through Leg Straps

- Single back D-ring
- Multiple adjustment points
- Universal sizing

Part #	Size
FS99185-E	Universal



# Horizontal Lifelines

**Pre Engineered Lifelines** 

Fall Safe

5/16" Portable Horizontal Cable Lifeline Kit



- 60' Cable
- Turnbuckle
- 2 Carabiners
- 2 Connector rings
- 2 Shackles
- 2 Cross arm-straps
- Energy absorber
- Transport bag

Part #	Length
FS806	60'
FS806-100	100'



# **Horizontal Lifelines**

## **Pre Engineered Lifelines**

Fall Safe

## 60 Ft Portable Horizontal Rope Lifeline Kit



- 2 Carabiners
  - 2 Cross-arm straps
  - 2 Connector rings
  - 60' Rope
  - Energy absorber
  - Transport bag

Part #	Length
FS805	60'

#### 60 Ft Portable Horizontal Web Lifeline Kit



- 2 Carabiners
- 2 Connector rings
- 60' Web line
- 2 Cross-arm straps
- Web ratchet
- Energy absorber
- Transport bag

Part #	Length
FS804	60'

## Retractables

#### **Extreme Retractables**

**Fall Safe** 

#### Retractable Lifelines (Web)

- · Heavy-duty housing
- Includes carabiner
- 3,600 lbs gate-rated hook
- Meets OSHA 1926-502 and ANSI Z359.1-2007

Part #	Length
FS-EX1520W	20 Ft



## Retractables

#### **FSP Retractables**

#### Fall Safe

#### Class A Cable Retractable Lifelines

- First retractable to meet rigorous ANSI Z359.14-2012 Class A Standards
- 11' 3/16" Cable
- Includes carabiner
- 3,600 lbs gate-rated snap hook
- Tie-back & dual-leg options available
- Engraved housing

Part #	Cable Length	Cable Dia.
FS-FSP1215-G	15'	3/16"
FS-FSP1220-G	20'	3/16"

#### Class A Web Retractable Series



- First retractable to meet rigorous ANSI Z359.14-2012 Class A Standards
- 11' Dynema Webbing
- Includes carabiner
- 3,600 lbs gate-rated snap hook
- Tie-back and dual-leg options available
- Engraved housing

Part #	Dynema webbing
FS-FSP1407-W	7'
FS-FSP1411-W	11'

## Class A Web Retractable Series Dual-Leg



- First retractable to meet rigorous ANSI Z359.14-2012 Class A Standards
- 7' Dynema Webbing
- Includes carabiner
- 3,600 lbs gate-rated snap hook
- Tie-back & dual retractable options available
- Engraved housing

Part #	Dynema webbing
FS-FSP14075-W	7'



# Retractables

**FSP Retractables** 

Fall Safe

## Class B Cable Retractable Lifelines



- Meets ANSIZ359.14-2012 Class B Standards
- LEADING EDGE and multiple length options available
- 30' 3/16" Galvanized cable
- Includes carabiner
- 3,600 lbs gate-rated indicator snap hook
- Swivel top
- Engraved housing

Part #	Cable Length	Cable Dia.
FS-FSP1230-G	30'	3/16"
FS-FSP1250-G	50'	3/16"

## **Table of Contents**

#### **Categorized Listing**

	itegorize	a Listing	
Safety	1	Harnesses	12
Anchors	1	Exteme Harnesses	12
Anchor Straps	1	Fall Safe	12
Fall Safe	1	Heavyweight 3 D-Ring Harness	12
Cable Cross-Arm Strap	1	Heavyweight Single D-Ring Harness	12
Cross-Arm Strap	1	Extreme Harnesses	13
Heavy Duty Cross-Arm Strap	1	Fall Safe	13
Medium Duty Cross-Arm Strap	1	No-Tangle 3 D-Ring Harness	13
Beam Anchors	2	No-Tangle Construction Harness	13
Fall Safe	2	No-Tangle Construction Harness with Built in Tool Pouch	14
Affordable Quality Anchor	2	No-Tangle Single D-Ring Grommet Harness	15
Girder Grip	2	Flex Harness	16
Premier Beam Anchor	2	Fall Safe	16
Stationary Beam Clamp	2	Flex253 Premium Construction Harness	16
Removable Anchors	3	Flex280 Comfort Harness	17
Fall Safe	3	Flex360 Premium Construction Harness	18
Removable Concrete Hole Anchor	3	FSP Harnesses	19
Roof Anchors	3	Fall Safe	19
Fall Safe	3	Derrick Harness	19
Non-Swivel Roof Anchor	3	Welding Harness	19
Roof Ring Anchor	4	V-Line Harnesses	19
Standing Seam Clamp Anchor	4	Fall Safe	19
Standing Seam Roof Anchor	5	Value Harness with Pass Through Leg Straps	19
Connectors	6	Horizontal Lifelines	20
		Pre Engineered Lifelines	20
Carabiners	6	Fall Safe	20
Fall Safe	6	5/16" Portable Horizontal Cable Lifeline Kit	20
Carabiner	6	60 Ft Portable Horizontal Rope Lifeline Kit	21
Extreme Lanyards	6	60 Ft Portable Horizontal Web Lifeline Kit	21
Fall Safe	6	Retractables	21
Adjustable Shock Lanyard	6		
Dual Leg Heavyweight Shock Lanyard	6	Extreme Retractables	21
Dual Leg Shock Lanyard	6	Fall Safe	21
Dual Leg Shock Lanyard with Rebar Hook	6	Retractable Lifelines (Web)	21
Dual Leg Stretch Shock Lanyard with Behar Hooks	6 7	FSP Retractables	22
Dual Leg Stretch Shock Lanyard with Rebar Hooks	7	Fall Safe	22
Dual Leg Tie Back Lanyard Heavyweight Lanyards	7	Class A Wah Betractable Lifelines	22
Shock Lanyard	7	Class A Web Retractable Series	22
Shock Lanyard with Rebar Hook	8	Class A Web Retractable Series Dual-Leg	22 23
Steamline Shock Lanyard with Rebar Hook	8	Class B Cable Retractable Lifelines	
Streamline Shock Lanyard	9		
Stretch Shock Lanyard	9		
Stretch Shock Lanyard with Rebar Hook	9		
Tie Back Lanyard	10		
FSP Lanyard	10		
Fall Safe	10		
Welding and Fire Rated Lanyards	10		
Positioning Assemblies	10		
Fall Safe	10		
Positioning Device	10		
Rope & Rope Lifelines	10		

10

10

11

11

11

11

11

11

12

Fall Safe

Rope Grabs

Fall Safe

Bulk Rope

Rope Lifelines

Rope Termination Plate

Removable Trailing Rope Grab

Removable Trailing Rope Grab with 3 FtShock Absorber

Stationary Manual Rope Grab with 3 Ft Shock Absorber

# **Table of Contents**

# **Alphabetized Listing**

5	
5/16" Portable Horizontal Cable Lifeline Kit	20
6	
60 Ft Portable Horizontal Rope Lifeline Kit	21
60 Ft Portable Horizontal Web Lifeline Kit	21
Α	
Adjustable Shock Lanyard	6
Affordable Quality Anchor	2
Anchor Straps	1 1-5
Anchors  B	1-5
=	2
Beam Anchors Bulk Rope	10
C	10
Cable Cross-Arm Strap	1
Carabiner	6
Carabiners	6
Class A Cable Retractable Lifelines	22
Class A Web Retractable Series	22
Class A Web Retractable Series Dual-Leg	22
Class B Cable Retractable Lifelines	23
Connectors	6-12
Cross-Arm Strap	1
D	
Derrick Harness	19
Dual Leg Heavyweight Shock Lanyard Dual Leg Shock Lanyard	6
Dual Leg Shock Lanyard with Rebar Hook	6
Dual Leg Stretch Shock Lanyard	6
Dual Leg Stretch Shock Lanyard with Rebar Hooks	7
Dual Leg Tie Back Lanyard	7
E	
Exteme Harnesses	12
Extreme Harnesses	13-15
Extreme Lanyards	6-10
Extreme Retractables	21
F	
Fall Safe	1-23
Flex Harness	16-18
Flex253 Premium Construction Harness Flex280 Comfort Harness	16 17
Flex360 Premium Construction Harness	17
FSP Harnesses	19
FSP Lanyard	10
FSP Retractables	22-23
G	
Girder Grip	2
Н	
Harnesses	12-19
Heavy Duty Cross-Arm Strap	1
Heavyweight 3 D-Ring Harness	12
Heavyweight Lanyards	7
Heavyweight Single D-Ring Harness	12
Horizontal Lifelines	20-21
M	
Medium Duty Cross-Arm Strap	1
N	
Non-Swivel Roof Anchor	3
No-Tangle 3 D-Ring Harness	13

	No-Tangle Construction Harness	13
	No-Tangle Construction Harness with Built in Tool Pouch	14
	No-Tangle Single D-Ring Grommet Harness	15
P		
	Positioning Assemblies	10
	Positioning Device	10
	Pre Engineered Lifelines	20-21
	Premier Beam Anchor	2
F		
	Removable Anchors	3
	Removable Concrete Hole Anchor	3
	Removable Trailing Rope Grab	11
	Removable Trailing Rope Grab with 3 FtShock Absorber	11
	Retractable Lifelines (Web)	21
	Retractables	21-23
	Roof Anchors	3-5
	Roof Ring Anchor	4
	Rope & Rope Lifelines	10-11
	Rope Grabs	11-12
	Rope Lifelines	11
	Rope Termination Plate	11
S		
	Safety	1-23
	Shock Lanyard	7
	Shock Lanyard with Rebar Hook	8
	Standing Seam Clamp Anchor	4
	Standing Seam Roof Anchor	5
	Stationary Beam Clamp	2
	Stationary Manual Rope Grab with 3 Ft Shock Absorber	12
	Steamline Shock Lanyard with Rebar Hook	8
	Streamline Shock Lanyard	9
	Stretch Shock Lanyard	9
	Stretch Shock Lanyard with Rebar Hook	9
I		
	Tie Back Lanyard	10
V	,	
	Value Harness with Pass Through Leg Straps	19
	V-Line Harnesses	19
V	V	
-	Welding and Fire Rated Lanyards	10
	Welding Harness	19
	Troiding Harrison	10