



DTEN GO with DTEN Mate

SPECIFICATIONS

All-in-One Video Conferencing Solution for Unparalleled Collaborations



Technology Partner



DTEN GO

DTEN Mate

PRODUCT	DTEN GO
SOFTWARE	DTEN OS
ALL-IN-ONE	Your Display
CAMERA SYSTEM	1080p x 2 Side Cameras 4k x 2 Center Cameras Horizontal Field of View (FOV): 160 Degrees
AUDIO SYSTEM	12 Elements Microphone Array Microphone Pickup Range 0-50 ft Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
NETWORK	Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support

INPUTS AND OUTPUTS	HDMI out x 1 Ethernet LAN (RJ45) x 1 3.5mm Audio Jack x 1
POWER	100 to 240 VAC, 50 to 60 Hz
OPERATING TEMPERATURE AND HUMIDITY	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
LANGUAGE SUPPORT	English * Additional languages to be supported in future software release

PRODUCT	DTEN Mate
PRODUCT SIZE	10"

*Image is not in 1:1 ratio
**Specifications are subject to change without prior notice

Zoom Rooms Simplified