

## Pneumatic ST-315 Fencing Stapler

### Features

#### Proven Pneumatic Technology

- Adjustable power for high density timber
- Reliability for high volume fence construction

#### Aluminium Alloy Housing

- Lightweight and corrosion resistant for extreme durability

#### Rugged Driver Blade

- Engineered specifically for driving heavy-duty fencing staples
- Manufactured from high impact resistant steel for long life

#### Suitable for 1¼" to 1½" Length Fence Batten Staples

- Ideal for rural wire and batten fencing applications

#### Suitable for 10½ Gauge Fence Batten Staples

#### Staple Wire Angle Guide

- Custom nose locates the wire for speed and reliability

#### Adjustable Depth of Drive

- Precision placement to prevent damage to fence wire

#### Top Load Magazine

- Fast reloading to minimize down-time

#### Adjustable Air Deflector

- Deflects discharged air away from operator for improved comfort

#### Sequential Trigger System

- Superior operator safety

#### Swivel coupling

- Greater flexibility for added convenience



| Product Code | Description                                       | Barcode       |
|--------------|---|---------------|
| A12505       | STOCKade Pneumatic 10½ Gauge Fence Batten Stapler | 9315104016132 |

## Pneumatic ST-315 Fencing Stapler

| Specifications                        | A12505  |
|---------------------------------------|---|
| Product Size (WxHxD)                  | 14.8" x 12.2" x 3.6"                            |
| Packaged Size (WxHxD)                 | 17.5" x 15" x 4.3"                              |
| Tool Weight                           | 6.4lb   |
| Packaged Weight                       | 10.8lb  |
| Quantity Per Pack                     | 1   |
| Cycle Rate                            | 3 staples per second                            |
| Magazine Capacity                     | 80 staples (3 strips)                           |
| Staple Range Length                   | 1¼" and 1½"                                     |
| Staple Range Gauge                    | 10½ gauge                                       |
| Staple Type                           | Hot dipped galvanised<br>Divergent point staple |
| Collation Type                        | Paper collated                                  |
| Operating Pressure                    | 6.2 to 8.3bar (90 to 120psi)                    |
| Optimum Operating Pressure            | 6.75 to 7.24bar (98 to 105psi)                  |
| Noise Level                           | 89 to 94dB                                      |
| Air Consumption at 7bar               | 1.1 Litres / cycle                              |
| Recommended Air Hose Fitting Diameter | ⅜" to ½"  |
| Vibration Value                       | 3.2m/s²   |

| Applications                                     |
|--|
| Rural livestock fencing                          |
| Horticulture                                     |
| Rural light mesh and light woven fencing         |
| Predator control fencing                         |
| Plastic mesh, pet enclosures and poultry fencing |
| Rural utilities applications                     |
| Cladding   |

The information presented in this product information sheet is correct as at the date of publication. STOCKade reserves the right to change performance, product or content information without notice.

READ ALL SAFETY INSTRUCTIONS

