

Impulse® ST-315i Fencing Stapler

Features

Impulse Technology

Portable, no need for compressors or air lines
Fast, high output design
Drives up to 2 staples per second

Lightweight Design

Comfort for periods of high use
Hose free for work in remote situations

Adjustable Depth of Drive

Greater flexibility for staple placement and a superior finish
Prevents damage to wire

Suitable for 1¼" and 1½" Length Staples

Ideal for rural wire and batten fencing applications

Suitable for 10½ga Staples

Quick Clear Nose

Less downtime if fastener jams occur

Top Load Magazine

Easy and fast re-loading
Rail protection bars

Sequential Trigger System

Improved operator safety

V Notch Guide

Ensures correct staple placement for
improved holding power



Product Code	Description	Barcode
A12315	STOCKade Impulse ST-315i 10½ga Stapler	9315104016767

Impulse® ST-315i Fencing Stapler

Specifications	A12315
Product Size (WxHxD)	4.3 x 15.6 x 14.9"
Packaged Size (WxHxD)	20.1 x 17.9 x 5.9"
Tool Weight (with battery)	8.4lbs
Packaged Weight	14.6lbs
Quantity Per Pack	1
Cycle Rate Per Second	2 staples per second
Magazine Capacity (Short)	80 staples (approx 3 strips)
Battery Capacity (Maximum)	Up to 3,000 staples per charge
Fuel Cell Capacity	Up to 1,000 staples per cell
Staple Range Length	1¼" and 1½"
Staple Diameter	10½ga
Staple Type	Divergent point (hot dipped galvanised)
Battery	6 Volt DC
Battery Recharge	2 hours
Fuel Cell	STOCK-ade Impulse Fuel Cell
Propellant	Liquid Hydrocarbon
Fuel Cell & Battery Storage Temperature	118.4°F
Rated Input Voltage Battery Charger Base	12 Volts DC 800mA
Rated Output Voltage Battery Charger Base	6 Volts DC 700mA
Rated Input Voltage Power Adaptor / Transformer	110 Volt AC 60Hz
Rated Output Voltage Power Adaptor / Transformer	12 Volt DC 800mA

Applications

	Rural livestock fencing, rural light mesh, light woven fencing
	Predator control fencing, plastic mesh, pet enclosures, poultry fencing
	Horticulture, cladding
	Rural utilities applications

The information presented in this product information sheet is correct as at the date of publication. STOCK-ade reserves the right to change performance, product or content information without notice.

READ ALL SAFETY INSTRUCTIONS

ST-315i™