

# Low-Pro Flatdeck with Singles







#### Standard Features

- 15,680 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- 2 5/16" Gooseneck Ball Coupler (25,000 lb.)
- Safety Chains
- 2 Drop Leg Jacks (10,000 lb.)
- 2 Dexter E-Z Lube Brake Axles (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 16" White Spoke Wheels
- 4 235/80R16 Radial Tires (3,520 lb.)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Side Steps on Both Sides
- Front Toolbox
- 8' Ramps w/ Holders

- 12" x 14 lb. I-Beam Main Frame, Riser & Neck
- Frame Bridge Standard on 30' and up.
- 3" Channel Crossmembers 16" on Center
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- 2" Treated Pine Lumber Deck
- 102" Wide Deck
- DOT Approved Flushmount Lifetime LED Lights
- Amber Side Turn Flashers
- Sealed Wire Harness w/ 7-Way RV Plug
- · Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams  $^{\text{TM}}$  Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.



#### AIR RIDE SUSPENSION AVAILABLE



Also Available with a Bumper Pull or Pintle Coupler.

### **Coupler Options**

GN 2 5/16" Round (25,000 lb.) w/Toolbox \* BP 2 5/16" Adjustable Rigid Mount (25,000 lb.) GN 2 5/16" Round (30,000 lb.) w/Toolbox GN Load-Leveling 2 5/16" Square (30,000 lb.) & Tbx 3" Pintle Eye - Face-mount (36,000 lb.) GN 2 5/16" Square (30,000 lb.) w/Toolbox GN 2 5/16" Square (25,000 lb.) w/Toolbox

## Axle Options

- (2) 7,000# Electric / Spring \*
- (2) 7,000# Electric / Torsion
- (2) 7,000# Elec/Hyd Disk / Spring
- (2) 7,000# Elec/Hyd Disk / Torsion
- (3) 7,000# Electric / Spring
- (3) 7,000# Electric / Torsion
- (2) 7,000# Load Range G I 4ply Tires Electric / Spring
- (2) 7,000# Load Range G 14ply Tires Electric / Torsion
- (2) 7,000# Load Range G 14ply Tires Elec/Hyd Disk / Spring (2) 7,000# Load Range G 14ply Tires Elec/Hyd Disk / Torsion
- (3) 7,000# Load Range G 14ply Tires Electric / Spring
- (3) 7,000# Load Range G 14ply Tires Electric / Torsion
- Consult Your Sales Rep. for Additional Available Axles

### Tail Options

Straight Deck w/ 8' Slide-in Ramps \*

- 5' Dovetail w/ 5' Slide-in Ramps
- 5' Dovetail w/ 2 Flip-over Ramps
- 5' Center Pop-up Dove w/ 2 Flip-over Ramps
- 5' Adjustable Dovetail w/ Slide in Ramps
- 5' Adjustable Dovetail w/ Stand Up Ramps
- 5' Dovetail w/ 3 Flip-over Ramps
- 5' Dovetail w/ 2 F/O Monster Ramps w/HD Gussets
- 5' Dovetail w/ 2 Flip-over Monster Ramps
- 5' Dovetail w/ Power Tail (Patent Pending)

#### Other Options

2 Hydraulic Jacks

GN Light Bar w/4 Lights (GN Only)

Mud Flaps Single Wheel Deckover

Rear Support Stands

Under Frame Spare Tire and Mount

Top Riser Toolbox

Cold Weather Wiring Harness (7-Way RV)

Plate for Winch

6" Taller GN Riser

Douglas Fir Lumber

Under Frame Tie Down Flat 19 lb. l-Beam Main Frame, Riser & Neck

22 lb. I-Beam Main Frame, Riser & Neck <sup>2</sup>

12"oc Crossmembers

I Pair D-Rings

Rough Oak Floor

Weld-On Strap Ratchets (2)

Receiver Hitch

4" Ratchets every 4ft w/ Slide Track

Side Mount Wood Rack

I Iga (1/8") Diamond Plate Steel Floor w/ 4 D-Rings

Frame Bridging

Diamond Plate Ramp Bottoms

Torque Tube

Deck on the Neck 8x8 ft

Side-mount Toolbox

Warn M I 2000 Winch w/ Plate, Batt, & Frt Toolbox

2-speed Jacks (12,000 lb.)

HD Semi Trailer 2x Jacks (25,000 lb.)

Ramp Support Arms

<sup>\*</sup> Standard Feature

<sup>&</sup>lt;sup>2</sup> Special Order Option: Requires additional lead-time