



60" Utility Dump (D5)

D5



Lengths
8' & 10'



Standard Features

- 5,200 lb. G.V.W.R.
- 5,200 lb. x 1 G.A.W.R.
- 2" Ball Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 1 - Dexter E-Z lube Brake Axle (5,200 lb.)
- 6 Leaf Double-eye Spring Suspension
- 2 - 15" White Spoke Wheels
- 2 - ST225/75B15 (2540 lb.)
- Electric Breakaway Kit w/ Charger
- 1/8" Treadplate Steel Fenders
- Toolbox
- Barn Door Gate w/ Camlatch
- 4 - D-Rings
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 3" x 30" Hydraulic Cylinder
- 12' Control Cable
- 4" Channel Main Frame & Tongue
- 2" x 4" x 11ga. Tubing Bed Frame
- 3" Channel Crossmembers 16" oc
- 10ga. Steel Bed
- 5' Wide Bed
- 10ga. Steel Sides
- 18" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness w/ 7-Way RV Plug
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- Integrated 12V Trickle Charger

POWDER  COATED

At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Coupler Options

- 2" A-Frame (7,000 lb.) *
- BP 2 5/16" Adjustable (14,000 lb.)
- BP 2" Atwood Style A-Frame Coupler (5,000 lb.)
- 3" Pintle Eye - Channel-mount (21,000 lb.)

Axle Options

- (2) 3,500# Electric / Drop Axle
- (2) 3,500# Electric / Spring
- (2) 3,500# Surge/Hyd Drum w/ Surge Cplr/Spring
- (1) 5,200# Electric / Air Ride
- (1) 5,200# Electric / Spring *
- (1) 5,200# Elec/Hyd Drum (1,000 PSI)/Spring
- (1) 5,200# Surge/Hyd Drum w/ Surge Cplr/Spring
- (2) 5,200# Electric / Air Ride
- (2) 5,200# Electric / Spring
- (2) 5,200# Elec/Hyd Drum (1,000 PSI)/Spring
- (2) 5,200# Elec/Hyd Disk (1,600 PSI)/Air Ride
- (2) 5,200# Surge/ Hyd Drum w/ Surge Cplr/Spring

Tail Options

- Split Gate *
- Split / Spreader Gate

Other Options

- Rate at 9900 GVWR
- Cold Weather Wiring Harness (7-Way RV)
- Solar Battery Charger
- Upgrade to 235/80 R16 on 52k Axles
- Battery Charger 12V
- Tarp Mounting Brackets
- 12" oc Crossmembers
- 1 Extra Pair of D-Rings
- Mount Only for Spare Tire
- Tarp kit (Pull Bar)
- Ramps
- Spare Tire and Mount
- 18" Side Extensions (Expanded Metal)
- 18" Side Extensions

Notes:

- 8' 2.22 cu yds
- 10' 2.77 cu yds
- MAX GVWR 10,400 with Correct Options

Weights

Length	Axles	Est. Base Weight†
8'	1 - 5,200	1800 lbs / 816 kg
10'	1 - 5,200	2020 lbs / 916 kg
10'	2 - 3,500	2200 lbs / 998 kg

† Weights are estimated for base trailer only, PJ Trailers makes no guarantee regarding the accuracy of estimated weights

NOW EQUIPPED WITH

