



DECLARATION OF PERFORMANCE

Pursuant to the Construction Products Regulation n° 305/2011

n° **DOP-IT- 246**

1. Unique identification code of the product-type: **INTOCOL P (EN 12004)**
2. Type number: **ADHESIVE IN NORMAL DISPERSION.**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **for tiling internal walls.**
4. Name, registered name or registered trade mark and contact address of the manufacturer as required pursuant to 11, (5): **MALVIN SRL– industrial area ASI state road 7 bis km 15,400 - 81030 Gricignano D’Aversa (CE) - www.malvinsrl.com**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2): **not applicable.**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **system 3.**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard: **TECNOPROVE SRL, as notified testing laboratory n. 0925, performed the determination of the product type on the basis of the type testing on samples taken by the manufacturer, under system 3, and issued the test report n. ____.**
8. In case of a declaration of performance concerning a construction product for which has been issued an European technical assessment: **not applicable.**
9. Declared performance

Main characteristics	Performance	Harmonized technical norm
Fire reaction	Class E	EN 12004:2012
Initial tensile adhesion	$\geq 1,0 \text{ N/mm}^2$	
Shear strenght after heat ageing	$\geq 1,0 \text{ N/mm}^2$	
Dangerous substances	See SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer, by: **Giovanni Vittorioso - Sole Administrator**

Gricignano D’Aversa, 30/06/2013





 0925 EN 12004:2012	<p align="center">MALVIN SRL <i>Registered office and Factory:</i> Zona ASI, S. S. 7 bis Km 15,400 81030 Gricignano Di Aversa (CE) www.malvinsrl.com</p>	
<p align="center">10 INTOCOL P (EN 12004) n° DoP-IT - 246</p> <p align="center">Adhesive in normal dispersion to lay internal ceramic tiles</p>		
Fire reaction	Class E	
Initial tensile adhesion	≥ 1,0 N/mm²	
Shear strenght after heat ageing	≥ 1,0 N/mm²	
Dangerous substances	See SDS	

MALVIN

The performance characteristics refer to laboratory tests, values depend on the weather conditions and on the methods of implementations. The operator must verify the suitability of the product depending on the use planned.



MALVIN

