DECLARATION OF PERFORMANCE



Pursuant to the Construction Products Regulation n° 305/2011 n° **DOP-IT- 292**

- 1. Unique identification code of the product-type: INTOCOL PP L (EN 998-1)
- 2. Type number: LIGHT MORTAR FOR INTERNAL AND EXTERNAL PLASTERS (LW)
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **for internal/external plasters.**
- 4. Name, registered name or registered trade mark and contact address of the manufacturer as required pursuant to 11, (5): MALVIN SRL- industrial area ASI state road 7 bis km 15,400 81030 Gricignano D'Aversa (CE) www.malvinsrl.com
- 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12 (2): **not applicable.**
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: system 4.
- 7. In case of declaration of performance concerning a construction product covered by a harmonized standard: **The notified body has no tasks to be carried out.**
- 8. In case of a declaration of performance concerning a construction product for which has been issued an European technical assessment: **not applicable.**
- 9. Declared performance

Main characteristics	Perf <mark>ormance</mark>	Norm
Fire reaction	class A1	
Water absorption "c"	W1	
Water vapor diff. Coeff. "µ"	10	
Adhesion	1,20 N/mm ²	EN 998-1:2010
Thermal conductivity (tabulated value) "λ"	0,35 W/mK	
Durability	NPD	
Dangerous substances	See SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer, by: **Giovanni Vittorioso - Sole Administrator** (name and function)

Gricignano D'Aversa, 30/06/2017

(place and date of issue)

signature

DECLARATION OF PERFORMANCE

Pursuant to the Construction Products Regulation n° 305/2011 n° **DOP-IT-292**





MALVIN SRL

Registered office and Factory: Zona ASI, S. S. 7 bis Km 15,400 81030 Gricignano Di Aversa (CE) www.malvinsrl.com



10 INTOCOL PP L (EN 998-1) n° DoP-IT - 292

Light mortar for internal and external plasters (LW)

Fire reaction	class A1
Water absorption "c"	W1
Water vapor diff. coefficient "µ"	10
Adhesion	1,20 N/mm ²
Thermal conductivity (tabulated value) "λ"	0,22 W/mK
Durability	NPD
Dangerous substances	see SDS



The performance characteristics refer to laboratory tests, values depend on the weather conditions and on the methods of implementations. The operator must verify the suitability of the product depending on the use planned.















