Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

1. Identification of the product and of the company

Product identifier Trade name: INTOBIO MAS

首目

101 101

Product name: screed mortar

Chemical name: not applicable because it is multi-constituent substances of inorganic origin

Identified uses and uses advised against

Mortar for insulating base coat screeds No use advised against

Details of the supplier of the safety data sheet

Producer/Supplier: MALVIN s.r.l. Zona ASI S.S. 7 bis km 15,400 81030 – Gricignano D'Aversa (CE) Tel. + 39 081 813 27 80 /+ 39 081 502 97 13 Fax + 39 081 502 97 48 www.malvinsrl.com Email of the supplier of the safety data sheet: ufficiotecnico@malvinsrl.com

Emergency telephone number

Emergency telephone number of the company: MALVIN s.r.l. Zona ASI S.S. 7 bis km 15,400 81030 – Gricignano D'Aversa (CE) Tel. + 39 081 813 27 80 /+ 39 081 502 97 13 AVIABILITY: 8.00 – 12.30 // 13.30 – 17.00

Official advisory body:


HOSPITAL "A. CARDARELLI" Via Cardarelli, 9 - 80131 NAPOLI Telephone: 081-7472870 081-5453333 AVIABILITY: H 24

2. Hazard identification

10.00

10.00

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015



Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

3. Composition/information on ingredients

Chemical identity: Mixes

盲菌

100 100

Description: Premixed mortars with cement type Portland.

Dangerous substances:


Chemical characteristics: Mixes

Description: Mixture consisting of the following components with harmless additives.

Sostanze pericolose:

CAS: 85117-09-5, EC: 285-561-1 NATURAL HYDRAULIC LIME NHL R37/38-41 Percentage : >10 %





3.8/3 STOT SE 3 H335

4. First aid measures

Eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Protect unharmed eye.

Skin contact

Remove contaminated clothes. Wash immediately with abundant water and soap the body parts that have come in contact with the product, even if only suspected. Wash the body completely (bath or shower). Remove contaminated clothing immediately.

Ingestion

Do not induce vomiting: SEEK MEDICAL ADVICE IMMEDIATELY

Inhalation

Remove to fresh air and keep at warm and at rest.

Most important symptoms and effects, both acute and delayed

Not expected.

Indication of any immediate medical attention and special treatment needed

In case of accident, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: None.

5. Firefighting measures

10.00

10 10

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

The product is not flammable so no substantial provision is expected for the fire protection.

6 Accidental release measures

Personal precautions: Avoid formation of dust.

Environmental protection measures: No special measures required.

Measures for cleaning/collecting : Collect mechanically, using adequate ppe.

7 Handling and storage

Handling:

Information for safe handling:

Do not use sweeping or compressed air. Use dry cleaning (as for example aspirators and vacuum extractor), that does not cause dust dispersion on air.

Information about fire - and explosion protection: No special measures required.

Storage:

Requirements to be met by storerooms and container: Keep in closed containers.

Information for storing in one common facility: Keep away from acids, ammonium salts, aluminum and other metals non noble metals.

Further information about storage conditions:

Store in a dry place. Prevent dust dispersion. Keep receptacle tightly sealed. The total integrity of the package and the respect of the storage conditions are fundamental for the effectiveness of the reducing agent during the conservation period specified on the sack or on the transport document.

8 Exposure controls/personal protection.

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

Threshold Limit Value – Time-Weighted Average (TLV-TWA) applied on working environments of Association of Industrial American hygienists (ACGIH) for Portland cement is equal to 10 mg/m^3 for the unbreathable fraction and 3 mg/m^3 for the breathable fraction.

Personal protection measures

General protective and hygienic measures:

Do not eat, drink or smoke while you are working with the mix to avoid the skin contact or respiratory system Keep away from foodstuffs, beverages and feed.

Take off contaminated clothing immediately.

Wash your hand, with a neutral soap or appropriate light detergent, before breaks and at the end of work. Avoid contact with eyes and skin.

Respiratory protection:

Not necessary for the normal use.

In case of dust over the exposure limits, during refilling, use adequate protections to the respiratory tract, commensurate to the dust level and conform to the relevant standard EN (facial filter certified in accordance with UNI EN 149 or dust mask certified in accordance with UNI EN 140).

Hand protection:

篇 篇

100 100

Use protective gloves that ensure a total protection, for example in PVC, neoprene or rubber. Is recommended neoprene (0,5 mm). Not recommended gloves: not waterproof gloves.

Eye protection:

Safety goggles with side protection.

Skin protection:

Wear clothes that ensure a total protection for skin, for example in cotton, rubber, PVC or viton. Safety boots or shoes, such as produced (including moisturizing creams) to ensure the maximal protection of the skin from the prolonged contact with the wet cement.

All the Personal Protective Equipment must follow the related EC standard (as EN 374 for gloves and EN 166 for goggles), kept efficient and stored appropriately.

The duration of use of devices for protection against chemical agents depends on several factors (type of use, climatic conditions and method of preservation), which can considerably reduce the time required by the EC standards of usability. Always consult the supplier of the protection equipment.

To instruct personnel on the use of the supplied equipment.

Check the concentration of substances with exposure limits assigned, on the workplace

in accordance with the time and mode limits set out by local dispositions.

9 Physical and chemical properties

10.00

10 10

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

General indications Appearance: light powder Odor: lime Change of state Melting point/Melting range: > 700 °C Boiling point/range: not applicable Self-inflammability : not applicable Auto ignition: Product is not self igniting. Explosion hazard: The product is not explosive. Apparent density at 20°C: 1000 - 2400 kg/m³ Solubility: dispersible in water Values of pH at 20°C: ca. 11 – 13 in aqueous solution

10 Stability and reactivity

Stability:

The total integrity of the package and the respect of the storage conditions are fundamental for the effectiveness of the reducing agent during the conservation period specified on the sack or on the transport document.

Conditions to avoid:

Avoid high temperatures, and storage in damp and/or ventilated environments.

Incompatible materials:

Reacts with acids, ammonium salts, aluminum or other non noble metals provoking violent reactions.

11 Toxicological informations

Information on toxicological effects:

Are not available toxicological data of the product because isn't toxic.

Tests on the substances contained on the product show that, with a proper handling and the respect of the usual hygienic measures, the product can be used without endangering human health.

On skin: Into contact with moist skin can cause irritations, repeated contacts can cause dermatosis or eczemas. Meroevor the prolungated contact together with existing abrasions can cause severe burns.

On eyes: Direct contact causes eyelids and cornea irritations and damages to the eye balls.

Inhalation: May cause irritation of the mucous membranes and respiratory tract.

12 Ecological informations

Further informations:

There is no evidence of toxicity during the sedimentary phase.

The addition of large quantity of product to water can, however, cause an increase in the pH level and can be toxic for aquatic life under certain circumstances.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

13 Disposal considerations

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

Waste code:

窗 協

10 III

Recover if possible. Operate according to local and national dispositions in force. Where applicable, refer to the following regulatory provisions: 91/156/CEE, 91/689/CEE, 94/62/CE and following adjustments. Disposal hardened product (CER code): 170101 Disposal empty paper packaging (CER code):15.01.01 Disposal empty plastic packaging (CER code):15.01.02

The european code of the refusal here suggested is based on the composition of the product. According to the specific field of use can be necessary to give to the refusal a different code. Uncleaned packaging:

Advices:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport informations

The preparation is not classified for any hazard class for the transportation of hazardous goods, so it isn't subjected to the related modal regulation: IMDG (by sea), ADR (on the road), RID (by railway), IACO/IATA (air). During transport, avoid wind dispersion using closed containers.

15 Regulatory informations

10.00

田田

Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015



Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

Text of phrases referred to under heading 3:

R37/38: Irritating to respiratory system and skin. R41: Risk of serious damage to eyes.

H315: Causes skin irritation.

窗 協

100 100

H318: Can cause serious damage to eyes.

H335: May cause respiratory irritation.

These information are based on the best our knowledge at the indicated date and relates. Data were taken from the supplier of the single raw materials insert into our preparations. The Company shall accept no liability for damage to people or things that may result from improper use of informations presented in this document. Data sheet is an addition to not a substitute for rules and texts that regulates the activity of the user. User have to make sure that these informations are appropriate and complete with the respect to the specific use intended. Data sheet compliant with the dispositions of following regulatory: D.M. 4 april 1997 "Execution of art.25 comm.1 and 2, of D.Lgs 3 february1997 n.52, concerning the classification, packaging and labeling of dangerous

substances about the safety data sheet.

D.M. 07.09.2002. DD.L. 52/97; 285/98 and 65/2003.

Department issuing MSDS : QSU

Contact:

Quality Assurance Manager Vittorioso Antonio This sheet cancels and replaces any preceding release.



Data Compilazione: 01.03.2010 --- Revisione: 04.05.2015

PRODUCT LABEL:

	INTOBIO MAS	
Contains: Natural hydraulic lime	e	
Hazard statements:		
H315 H318 H335	Causes skin irritation. Can cause serious damage to eyes. May cause respiratory irritation.	Hazard
Precautionary state	ments:	
P261 P264 P271 P272	Avoid breathing dust. After use, wash hands and face. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.	MALVIN s.r.I. Via Zona ASI S.S. 7 bis km 15.400
P280	Wear suitable protective clothing and gloves/Protect eyes/face.	81030 – Gricignano D'Aversa (CE) Tel. + 39 081 813 27 80
P302 + P352	IN CASE OF SKIN CONTACT: flush with soap and water.	+ 39 081 502 97 13 www.malvinsrl.com
P304+P340	IN CASE OF INHALATION: remove victim to fresh air and keep at rest in a position comfortable for breathing.	ufficiotecnico@malvinsrl.com
P305 + P351 + P338 P310	IN CASE OF EYE CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call immediately a POISON CENTER or a doctor.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P321	Specific treatment (see on this label).	
P332+P313 P333 + P313	If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice.	
P362	Take off contaminated clothing and wash before reuse.	
P403+P233	Keep container tightly closed and in a well-ventilated place.	
P405 P501	Keep locked up. Dispose of contents/container to landfill.	

The performance characteristics refer to laboratory tests, values depend on the weather conditions and on the methods of implementations. The operator must verify the suitability of the product depending on the use planned.





P405	Keep locked up.
P501	Dispose of contents/container to landfill.