

Certificate of Accreditation Sewage Management Facility Sewage Ejection Pump Station

This Certificate of Accreditation is issued by the Secretary of the NSW Ministry of Health pursuant to Clause 41(1) of the Local Government (General) Regulation 2005.

System: Es 900 Litre Model SEPS and

Es 2000 Litre Model SEPS

Manufacturer: Rivatec Environmental Pty Ltd

(Central Coast Septics Pty Ltd)

Of: 6 Marklea Close, Tuggerah, NSW, 2259

The Es600 litre and Es2000 litre SEPS as described in the attached Schedule have been accredited as a sewage management facilities for use in single domestic premises in NSW. The pump well is manufactured to the Australian / New Zealand Standard AS/NZS 1546.1:2008 On-site domestic wastewater treatment units - septic tanks.

Director, Environmental Health

for Secretary (delegation PH335)

Issued: 9 July 2019

Certificate No: SEPS014 Expires: 31 December 2020



Accreditation Schedule

The Certificate of Accreditation applies to the Es600 litre and Es2000 litre sewage ejection pump stations in accordance with the attached plans.

The sewage ejection pump stations consist of:

- A vertical axis type cylindrical precast concrete pump well and lid, manufactured by Central Coast Septics Pty Ltd, with capacities of 900 and 2000 litres;
- A Keener model HGP2 grinder pump (or equivalent) fitted with a start, stop and high level flow switches;
- A PVC 32 mm diameter pressure discharge pipe fitted with a gate valve and check valve on the outlet of the grinder pump;
- An audible and visible alarm system.



Precast Concrete Pump Station

ABN; 19 099 003 737

PO Box 605 Wyong 2259 Ph; 1300 327 847 F; 02 43534113

Lic; 188794C

6 Marlea Close Tuggerah 2259 NSW

D

C1

SITE;

Designed;SF

Date: 05/2010

Rivatec Environmental make a range of single pump and double pump stations for the use on single to multi-dwelling residentional installations.

The pump stations can be used in a wide range of applications from Effluent, Sewage and Stormwater.

Pump stations come with 1 \times 600mm access covers, the standard cover is a compressed fibre glass lid for trafficable areas.

Controllers

Fitted with high level visual and audible alarms, hour run meter and timer, single or double controller fixed on the tank or remote on the building.

Guide Rails

Some pump stations come with pump guide rails or stand

Float Switch

Each pump station comes with separate high float and pump start/stop float

Collect Well

The Collection Wells are made to AS/NZ 1546-1

Pipe Work

Pump line is 32mm or 50mm Pn12 PVC pressure pipe with Gate valve and check valve

Pumps

Single or dual pumps are fitted fixed or on guide rails and changes for easy maintenance Grinder pumps for sewage and Vortex pumps for clean water.

935mm

В

2065mm


ACCREDITED

-9 JUL 2019

NSW MINISTRY OF HEALTH

65

60



Note;

Es 900

CAPACITY

Hole excavation 1.5m squ by the depth 2.1m

C1

575

C2

995

D

120



ABN;19 099 003 737 PO Box 605 Wyong 2259 Ph; 1300 327 847 F; 02 43534113 6 Marklea Close Tuggerah

2259

Designed:SF

Date:05/2010

Lic: 188794C

SITE;

Precast Concrete Pump Station

Rivatec Environmental make a range of single pump and double pump stations for the use on single to multi-dwelling residentional installations.

The pump stations can be used in a wide range of applications from Effluent, Sewage and Stormwater. Pump stations come with 1 x 600mm access covers, the standard cover is a compressed fibre glass Ii d for trafficable areas.

Controllers

Fitted with high level visual and audible alarms, hour run meter and ti mer, single or double control I er fixed on the tank or remote on the building.

Guide Rails

Some pump stations come with pump guide rails or stand

Float Switch

Each pump station comes with separate high float and pump start/stop float

Collect Well

The Collection Wells are made to AS/NZ 1546-1

Pipe Work

Pump line is 32mm or 50mm Pn12 PVC pressure pipe with Gate valve and check valve

Pumps

Single or dual pumps are fitted fixed or on guide rails and changes for easy maintenance Grinder pumps for sewage and Vortex pumps for clean water.

Concrete bench

poured after tank is made

CAPACITY

Es2000

B

1605mm

1750mm

C

755


D

120

Ë

80

50



ACCREDITED

- 8 JUL 2019

H. ** BO ANISIN WINSN