



SEE MORE. DO MORE.

Zebra® 105SL Plus™



Call Today!
(800) 643-2664

Zebra's 105SL Plus provides economical, dependable, high-performance printing. This rugged printer is built for continuous operation, with exactly the features needed for fast, reliable and cost-effective printing in your manufacturing and warehousing environments.

Zebra created the 105SL Plus with ease of use in mind. The icon-based, multilingual graphical LCD user interface is intuitive to operate, minimizing user training and making the printer ideal for a multitude of languages and global applications. The simplified ribbon loading process minimizes downtime.

The 105SL Plus offers durable all-metal construction and a robust

print mechanism to withstand the toughest environments. The 105SL Plus leverages Zebra's proven electronics platform to offer increased speed for high-volume applications—and increased storage of formats, fonts and graphics. Element Energy Equalizer™ (E³™) technology extends the life of the printhead and provides outstanding print quality.

The 105SL Plus is designed to easily fit into existing operations. Multiple standard connectivity options including parallel, serial, USB and Ethernet coupled with full backward compatibility makes integration fast and simple. For added connectivity, choose the optional ZebraNet® b/g Print Server for wireless support.

Ideal for These Applications

Manufacturing / Product identification labels, Packaging labels, Receiving/Put-away labeling, Work-in-process

Transportation & Logistics / Order picking/packing, Shipping/Receiving, Cross-docking, Compliance labeling

Retail / Shipping, Returns

Government / Asset tracking, Compliance labeling, Inventory labeling

SPECIFICATIONS AT A GLANCE *

Printer Name	Operating Characteristics	Fonts/Graphics/Symbologies
105SL Plus		
Standard Features	Environmental	Fonts and Character Sets
<ul style="list-style-type: none"> Full-function front panel and large multilingual back-lit LCD display—with user-programmable password protection Thin film printhead with Element Energy Equalizer™ (E^{3™}) for superior print quality 8 MB Flash memory—including 2 MB user-available non-volatile memory storage for downloadable objects Serial RS-232 and bi-directional parallel ports—with auto detect USB 2.0 Dual media sensors—transmissive and reflective, selectable through software or front panel Internal ZebraNet® 10/100 Print Server—supports 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks. 	<ul style="list-style-type: none"> Operating environment: <ul style="list-style-type: none"> Thermal transfer = 40° F/5° C to 105° F/40° C Direct thermal = 32° F/0° C to 105° F/40° C Operating Humidity: 20% to 85% non-condensing Storage/Transportation environment: -40° F/-40° C to 140° F/60° C Storage Humidity: 5% to 85% non-condensing 	<ul style="list-style-type: none"> Zebra Global printing solution including Unicode™ Swiss 721 font standard Bitmap fonts A to H and GS symbols are expandable up to 10 times, height- and width-independent Smooth-scalable font Ø (CG Triumvirate™ Bold Condensed) is expandable dot-by-dot, height- and width-independent IBM® Code Page 850 International Characters Contains UFST® from Agfa Monotype Corporation Firmware support for downloadable TrueType™ fonts Additional fonts available
Printer Specifications	Electrical	Graphics Features
Resolution	<ul style="list-style-type: none"> Universal power supply with power-factor correction 100-240 VAC, 47-63 Hz 	<ul style="list-style-type: none"> Supports user-defined fonts and graphics, including custom logos
<ul style="list-style-type: none"> 203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional) 	Agency Approvals	Barcode Symbologies
Memory	<ul style="list-style-type: none"> IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3 Product Markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark(Arg), CCC, GOST-R, BSMI, KCC, and UkrSEPRO 	<ul style="list-style-type: none"> All standard linear and 2D barcodes supported
Standard: 16 MB SDRAM; 8 MB Flash	Physical Characteristics	For optimum print quality and printer performance, use genuine Zebra™ supplies.
Print width	<ul style="list-style-type: none"> Height: 15.5"/393.7 mm Width: 10.31"/261.9 mm Depth: 20.38"/517.5 mm Weight: 50 lbs/22.7 kg 	
4.0"/102 mm	Options and Accessories	
Print length	<ul style="list-style-type: none"> 300 dpi Cutter and catch tray Media rewind spindle—internal finished roll rewind or passive-peel with liner take-up spindle 64 MB On-Board Linear Flash Memory (factory installed only) Scalable and international fonts 	
<ul style="list-style-type: none"> 203 dpi: 150"/3810 mm (with standard memory) 300 dpi (optional): 100"/2540 mm (with standard memory) 	ZebraLink™ Solutions	
Print speed	Software	
<ul style="list-style-type: none"> 203 dpi: 12"/305 mm per second 300 dpi: 10"/254 mm per second 	<ul style="list-style-type: none"> ZebraDesigner™ Pro ZebraDesigner for XML ZebraNet™ Bridge Enterprise ZebraNet™ Utilities v 7.0 	
Media Specifications	Optional Connectivity	
<ul style="list-style-type: none"> Media types: continuous, die-cut, or black mark, notch Media thickness (label and liner): 0.003"/0.076 mm to 0.012"/0.305 mm Maximum media roll size: 8.0"/203 mm O.D. on a 3"/76 mm I.D. core Media width (label and liner): 0.79"/20 mm to 4.5"/114 mm Maximum non-continuous label length: 39"/991 mm 	Firmware	
	<ul style="list-style-type: none"> ZPL II® Zebra Global Printing Solution Web View & Alert ZBI 2.0™ (optional) 	
Ribbon Characteristics		
<ul style="list-style-type: none"> Standard Lengths: 1476'/450 m or 984'/300 m Provides 2:1 and 3:1 media roll to ribbon ratios Maximum ribbon roll size: 3.2"/81.3 mm O.D. on a 1.0"/25.4 mm I.D. core Ribbon wound coated-side out Ribbon width: 0.79"/20 mm to 4.33"/110 mm 		



MIDCOM Data Technologies®, Inc.
"Your Business. The Right Solution."

MIDCOM Data Technologies, Inc.
 phone: (800) 643-2664
 website: www.midcomdata.com
 email: info@midcomdata.com

*Specifications subject to change without notice.

©2013 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All rights reserved. All other trademarks are the property of their respective owners.

P1058645 (02/13)