



ALL ACCESS OPENING ARE 24" I.D.

ALL BAFFLES HAVE A MINIMUM 1" AIR SPACE BETWEEN COVER AND TOP OF BAFFLE

# **TANK SPECIFICATIONS**

## **CAPACITY:**

2250 GALLONS = 1150 & 1100

### **DIMENSIONS:**

LENGTH = 175" AT TOP, 169" AT BOTTOM

WIDTH = 84" AT TOP,

78" AT BOTTOM

OVERALL HEIGHT = 65"

**DEPTH BELOW INLET = 48"** 

**DEPTH BELOW OUTLET = 46"** 

## **INLET AND OUTLET BAFFLES:**

POLYETHELENE w/STAINLESS STEEL CONNECTORS

#### **INLET BAFFLE:**

15" (8" ABOVE LIQUID LEVEL, 7" BELOW LIQUID LEVEL) 16.25%

## **OUTLET BAFFLE:**

25 1/4" (8" ABOVE LIQUID LEVEL, 17 1/4" BELOW LIQUID LEVEL) 40%

# **LIQUID CAPACITY:**

1150 LIFT = 26.75 GAL PER INCH 1100 LIFT = 25.59 GAL PER INCH 43" LIQUID DEPTH

REGISTERED IN MINNESOTA FOR SEVEN FEET OF COVER ON TOP OF THE TANK.

# **MODEL: DARWIN** 1150/1100

SEPTIC TANK/HOLDING TANK 2748 GALLONS TANK WEIGHT 16,385 LBS Precast
Systems
Inc.

PO Box 56, Darwin MN 55324 320-693-8440 888-693-8440