



signature"
collection



Scandium[™] shown

■ The Radium, Scandium and Elite CVF catalytic vent-free fireplaces from the Dave Lennox Signature Collection reflect the ultimate in innovation and efficiency. Less than eight inches deep, they're ideal for contemporary living spaces, high-rises, lofts or any space where venting cannot be installed, and the slim and modern design makes installation as easy as hanging a picture on a wall. Patented* catalytic technology cleans the hot air as it leaves the combustion chamber, and because these fireplaces boast a 99.99% fuel-efficiency rate, nearly all the heat produced is distributed directly into the living space. These sleek offerings create a unique fire presentation that is sure to amaze and mesmerize.



STANDARD FEATURES

99.99% fuel efficiency lowers fuel costs

Vent-free configuration allows installation almost anywhere a gas connection is available

With less than eight inches in depth and no special framing requirements, unit installation is about as easy as hanging a picture on a wall

Patented catalytic technology cleans hot air as it leaves the combustion chamber

Adjustable flame height and heat intensity

Radium meets BTU and exhaust temperature requirements allowing installation in bedrooms*

Burns natural gas or propane

20-year limited warranty

*Check local codes



Elite™ CVF shown



SCANDIUM™ Front View Side View

PRODUCTS YOU CAN COUNT ON

Lennox is committed to providing you with high-quality products. A qualified dealer can help you find the right product to give you years of comfort and enjoyment.

ELITE™ CVF Front View Side View

PERFORMANCE INFORMATION

Percent of Allowable Per ANSI Z21.11.2 Carbon Monoxide (CO) 25 50 75 100 Nitrogen Dioxide (NO₂)

Test results by independent laboratories confirm that Radium™ and Scandium[™] catalytic vent-free gas fireplaces meet or exceed current and applicable nationally recognized standards and recommendations for indoor air quality and are among the cleanest-burning unvented products when measuring allowable levels of combustion byproducts such as carbon monoxide and nitrogen dioxide.

SPECIFICATIONS					
MODEL	Max. BTU	Min. BTU	FIREPLACE		
			WIDTH	HEIGHT	DEPTH
Radium™	NG 8,870 LP 7,500	5,110 5,110	35-3/8"	27-1/4"	7-1/2"
Scandium™	NG 11,950 LP 10,235	6,820 6,820	41-1/2"	21"	7"
Elite™	NG 6,825 LP 5,800	3,412 3,412	23-13/16"	27-5/32"	6-1/4"



© Lennox Industries Inc. 2008

Visit us at www.lennox.com, or contact us at 1-800-9-LENNOX.

IMPORTANT NOTES:

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale—consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.



