

HUSQVARNA 125B NEW!

Efficient hand held blower that combines high blowing power with user friendliness. Perfect for home owners. Well balanced and easy to manouevre thanks to in-lined air out let.





In lined outlet
The fan housing is designed so that the air stream is in lined with the handle. This makes the machine very easy to manoeuvre.



Auto return stop switch Stop switch automatically resets to the ON position for trouble-free starting.



Cruise control Fan speed can be set for easier handling.



Adjustable tube length The blowing tube length is adjustable for best performance.



Intuitive controls
The controls are well
gathered and easy to
access.



Fuel pumpFuel pump designed for easy starting.

Technical data Engine specification

Cylinder displacement	28 cm³ / 1.7 cu.inch
Cylinder bore	35 mm / 1.4 inch
Cylinder stroke	28.7 mm / 1.1 inch
Power output	0.8 kW
Maximum power speed	8000 rpm
Fuel tank volume	0.5 lit / 16.91 fl oz
Fuel consumption	575 g/kWh
Spark plug	Champion RCJ6Y
Article data	
Air flow in housing	13.31 m³/min / 470 cfm
Air flow in pipe	12.03 m³/min / 425 cfm
Air speed	76 m/s / 170 mph
Air speed (round nozzle)	58.12 m/s / 130 mph

Air speed (flat nozzle)	76 m/s / 170 mph
Vibration & noise data	
Equivalent vibration level (ahv, eq) handle	11.1 m/s²
Sound pressure level at operators ear	92 dB(A)
Sound power level, guaranteed (LWA)	107 dB(A)
Sound pressure (15m)	70 dB(A)
Equipment	
OEM Harness	
OEM Nozzle type	Round+ Flat
Overall dimensions	
Weight	4.26 kg / 9.4 lbs
Logistical Data	
Weight incl. packaging	6 kg / 13.23 lbs
Packaging size, LxWxH	419x216x419 mm / 16.5x8.5x16.5 inch
Pallet quantity	45
Products per 20ft container	720 pcs
Products per 40ft HC container	1620 pcs

Accessories



952 71 19-18 Gutter kit

Kit for cleaning gutters on houses. Total tube length 3 meters.