



HUSQVARNA 135

New lightweight and efficient homeowner saw ideal for those looking for a chainsaw that is exceptionally easy to start and manoeuvre. Featuring X-Torq® engine for lower fuel consumption and reduced emission levels. Equipped with fuel pump and Auto return stop switch for easier starting.



X-Torq®
Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



Air Injection
Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Quick-release air filter
Facilitates cleaning and replacement of the air filter.



Ergonomic rear handle
Increased comfort with soft inlay, ergonomic trigger and asymmetrical handle.



Felling marks
Distinct felling marks for better felling precision.



Combined choke/stop control
Combined choke/stop control allow for easier starting and reduce the risk of engine flooding.

Additional features

Side-mounted chain tensioner
Side-mounted chain tensioner makes chain adjustment quick and easy.

LowVib®
Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

Inertia chain brake
Effective inertia-activated chain brake.

Snap-lock cylinder cover
Snap-lock cylinder cover saves time when changing spark plugs and cleaning.

Fuel pump
Fuel pump designed for easy starting.

Technical data

Engine specification

Cylinder displacement	40.9 cm ³ / 2.5 cu.inch
Cylinder bore	41 mm / 1.61 inch
Cylinder stroke	31 mm / 1.22 inch

Power output	1.4 kW
Maximum power speed	9000 rpm
Fuel tank volume	0.37 lit / 12.51 fl oz
Fuel consumption	652 g/kWh
Ignition module air gap	0.3 mm / 0.01 "
Idling speed	2900 rpm
Spark plug	Champion RCJ7Y, Husqvarna HQT-1, NGK BPMR7A
Electrode gap	0.5 mm / 0.02 "
Torque, max.	2 Nm/6300 rpm
Lubricants	
Oil tank volume	0.25 lit / 0.53 US pint
Oil pump type	Automatic
Vibration & noise data	
Equivalent vibration level (ahv, eq) front / rear handle	3.9/3.8 m/s ²
Sound pressure level at operators ear	102 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Cutting equipment	
Chain pitch	3/8" LP
Recommended bar length, min-max	35-40 cm / 14"-16"
Chain speed at max power	17.1 m/s / 56.1 fts
Chain speed at 133% of maximum engine power speed	30.5 m/s / 100.07 fts
Chain gauge	0.05 "
Sprocket type	Spur 6
Bar mount	Small
Overall dimensions	
Weight (excl. cutting equipment)	4.4 kg / 9.7 lbs

Standard equipment



501 95 92-52 - 3/8" MINI Laminated Small bar mount

The gentle curve and small nose radius reduce the risk of kickback and facilitate good cutting control. Bars are epoxy coated to protect against scratches and corrosion.

Accessories




501 95 92-52 3/8" MINI Laminated Small bar mount

The gentle curve and small nose radius reduce the



501 95 92-56 3/8" MINI Laminated Small bar mount

The gentle curve and small nose radius reduce the



576 83 07-52 3/8" MINI TechLite Small bar mount

Our new lighter TechLite™ bar with superb rigidity is the first of its kind on the market. Compared to our regular bars, the TechLite™ bar is up to 20% lighter and has almost 25% better rigidity. The superior rigidity has been



576 93 65-52 Saw chain H37 3/8" MINI Pitch 1,3 mm

risk of kickback and facilitate good cutting control. Bars are epoxy coated to protect against scratches and corrosion.

risk of kickback and facilitate good cutting control. Bars are epoxy coated to protect against scratches and corrosion.

achived by using bonding materials over the entire surface as supposed to previous techniques. The bar is also less susceptible to bending and returns to its original shape when subjected to high loads. Gives you less strain, increased efficiency and gain a higher productivity without compromising on the quality of the cutting equipment or user safety.



576 93 65-52
Saw chain H37 3/8"
MINI Pitch 1,3 mm

576 93 65-56
Saw chain H37 3/8"
MINI Pitch 1,3 mm
