



HUSQVARNA 226HD75S

Husqvarna 226HD75S is an exceptionally well-balanced and rugged double cutting edge hedge trimmer with X-Torq® engine. The robust design leads to long product life during tough use.



Long life gear components
The gear components have been developed for long life under tough conditions.



Adjustable rear handle
The rear handle is adjustable to facilitate cutting the sides and top of hedges.



Sharp teeth
Sharp and robust cutting teeth for high productivity and long product life.



Fuel pump
Fuel pump designed for easy starting.



X-Torq® engine
The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



LowVib®
Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

Additional features

Stand alone starter

The stand alone starter makes it easy to change starter cord if needed.

Technical data

Engine specification

Cylinder displacement	23.6 cm ³ / 1.44 cu.inch
Cylinder bore	34 mm / 1.34 inch
Cylinder stroke	26 mm / 1.06 inch
Power output	0.85 kW
Maximum power speed	8500 rpm
Fuel tank volume	0.5 lit / 16.91 fl oz
Fuel consumption	412 g/kWh

Engine specification

Power output	0.85 kW
Fuel consumption	412 g/kWh ()

Emission data EPA

HC, g/kWh	41.9 g/kWh
CO, g/kWh	226.7 g/kWh
NOx, g/kWh	0.69 g/kWh

Noise data

Sound power level, guaranteed (LWA)	102 dB(A)
-------------------------------------	-----------

Ignition module air gap	0.35 mm / 0.01 "
Idling speed	3000 rpm
Spark plug	NGK CMR7H-10
Electrode gap	0.95 mm / 0.04 "
Vibration & noise data	
Equivalent vibration level (ahv, eq) front / rear handle	3.6/5.4 m/s ²
Sound pressure level at operators ear	91 dB(A)
Sound power level, guaranteed (LWA)	102 dB(A)
Transmission data	
Gear ratio	5.11:1
Equipment	
Knife Length	75 cm / 29.53 inch
Teeth opening	28 mm / 1.1 "
Recommended maximum twig diameter	10 mm / 0.39 "
Cutting speed	4100 cut/min
Overall dimensions	
Weight	6 kg / 13.2 lbs
Logistical Data	
Weight incl. packaging	9 kg / 19.84 lbs
Packaging size, LxWxH	1255x290x220 mm / 49.41x11.42x8.66 inch
Products per 20ft container	330 pcs
Products per 40ft container	680 pcs
Products per 40ft HC container	780 pcs

Sound pressure at operators ear	91 dB(A)
Vibration data	
Equivalent vibration level (ahv, eq), front and rear handle	3.6/5.4 m/s ²
Uncertainty - Equivalent vibration level	1 m/s ²
Metals	
Plastics	
Rubber	
Other	
Total product weight	6 kg / 13.23 lbs

Accessories



610 00 01-30

XP® Professional Performance 2-Cycle Oil

Our best formulation to date is the "XP® Professional Performance" 2-cycle lubricant. It is a synthetic blend designed for tough, professional usage. * Handles high loads at tough professional usage *Excellent lubricating properties *Lowers engine operating temperature * Less coating on the piston and in crankcase * Extends the engine's life * Provides longer service intervals * Low to medium smoke emission * Includes fuel stabilizer



610 00 01-31

XP® Professional Performance 2-Cycle Oil

Our best formulation to date is the "XP® Professional Performance" 2-cycle lubricant. It is a synthetic blend designed for tough, professional usage. * Handles high loads at tough professional usage *Excellent lubricating properties *Lowers engine operating temperature * Less coating on the piston and in crankcase * Extends the engine's life * Provides longer service intervals * Low to medium smoke emission * Includes fuel stabilizer