

Industry-fastest, laser fax machine with duplex ADF is ideal for robust, everyday use

**i-SENSYS**  
FAX-L410

you can



## Robust, fast Super G3 laser fax machine, with large memory and duplex ADF.

This robust, compact Super G3 laser fax machine, with its large LCD display, fast performance and automatic duplex ADF, is ideal for everyday use within any business.

### Key features

- Industry-fastest Super G3 fax modem (33.6kbps) – 3 seconds per page\* transmission
- Robust, space-saving design with large LCD display
- Ultra High Quality 256 grayscale imaging for clearer detail on faxes
- Large 512-page\* transmit and receive fax memory
- 39 one-touch and 200 coded speed dials
- 50-sheet Duplex ADF for automatic double-sided copying and faxing
- Fast laser print and copy speed of 25ppm
- No waiting with Quick First-Print from sleep mode
- High energy efficiency
- Handset as standard

\* Based on ITU-T Standard Chart No. 1

### What's in the box

Main unit, handset, handset cradle, handset clamp, cartridge 728 starter, power cord, telephone line cable, destination labels, starter guide and warranty card – with user software and manual CDs.

### Dimensions (W x D x H)

472mm x 445mm x 358mm

### Supported OS

**Windows** 7 / XP / Vista

**Mac OS** Version 10.4.9 and up  
(Web distribution only)

**Linux** (Web distribution only)



PRINT



COPY



FAX



SCAN

**Canon**

# Specifications:



<b>FAX UNIT TYPE</b>	Type Standalone facsimile & Laser printer Compatibility Group 3 Applicable line PSTN Modem speed 33.6kbps (Super G3) Print technology Laser beam printing Scanner type Duplex Sheet fed
<b>FAX SCANNING FEATURES</b>	Automatic document feeder 50 sheets (ADF) Document size Width - 216mm (Max), 140mm (Min) Length - 356mm (Max), 127mm (Min) Effective scanning width 214mm Scanning speed Approx. 2.5 sec / page Approx. 20 pages / minute Fax resolution Up to 200 x 400 dpi Image processing system UHQ (Ultra High Quality) Halftone 256 shades of grayscale
<b>FAX PRINTING FEATURES</b>	Printing method Laser Beam Printing Print speed 25 pages per minutes First Print Out Time 5.8 secs Print resolution 600 x 600 dpi Print Quality Up to 1200 x 600 dpi Paper capacity 250 sheets Print cartridge CRG728 All in One cartridge Print cartridge yield Approx. 2100 pages <sup>1 2</sup> Page collated print (on reception) Yes Paper output tray capacity 100 sheets Media Types Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope Media Sizes Cassette: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL Min. 76.2 x 148mm to Max. 216 x 356mm ADF: A4, B5, A5, B6, LTR, LGL, STMT Min. 127 x 140mm to Max. 356 x 216mm Printing width 206mm Toner save mode Yes Auto image reduction on reception Yes (75 to 100% in 1% increments)
<b>TRANSMISSION AND RECEPTION FEATURES</b>	Transmission speed 3 seconds per page with 33.6kbps modem <sup>3</sup> Compression method MH, MR, MMR Memory transmission Yes Fax memory 512 pages <sup>3</sup> Memory backup Unlimited Memory reception Yes Dual access Yes Error correction mode(ECM) Yes Delayed transmission Yes (250 locations) Sequential broadcast Max. 249 destinations Reception Yes Sub-address transmission Yes Error re-transmission Yes Fax transfer Yes
<b>SECURITY AND MANAGEMENT FEATURES</b>	Password user restriction Yes Forced memory reception Yes System management password Yes Reports Activity Management Report (TX/RX), Activity Result Report Transmission header Yes Reception footer Yes

<b>TELEPHONY FEATURES</b>	One-touch dials 39 Coded dials 200 Group dials Max. 238 dials / Max. 238 destinations Program dial Yes Redial Yes (automatic and manual) Dial search Yes FAX/TEL auto switch Yes Answering machine Hook-up Yes Remote reception Yes On Hook key Yes Telephone handset Yes Type Standard
<b>COPIER FEATURES</b>	Copy resolution TEXT/PHOTO mode, TEXT mode, PHOTO mode: 600 dpi x 600 dpi Copy speed (Mono) 25 pages per minutes Multiple copy Up to 99 copies Zoom 25% - 400% in 1% increments First copy output time (FCOT) Less than 9.0 seconds
<b>DISPLAY</b>	Type LCD Size 5 lines Languages 23 languages: (English / Spanish / French / Italian / Hungarian / Dutch / Norwegian / Polish / Greek / Estonian / Croatian / Bulgarian / Portuguese / Slovene / Slovak / Finnish / Swedish / Turkish / Russian / Czech / Danish / German / Romanian) Energy saver key Yes
<b>PRINTER FEATURES</b>	Interface USB 2.0 Hi-Speed PDL UFR II-LT Memory 128MB Printer Windows 7 / XP / Vista / Mac OS X 10.4.9 and up <sup>4</sup> / Linux <sup>4</sup> Supplied Drivers Printer Driver, Fax Driver, Address Book Tool
<b>GENERAL FEATURES</b>	Duty Cycle Max 10,000 pages per month Warm-Up time Approx. 13.5 seconds or less from power on Recovery time Approx. 2.0 seconds Dimensions (W x D x H) 472 x 445 x 358mm Installation space (with trays handset) 472 x 704 x 606mm Weight Approx. 13.9kg Power consumption Maximum: 1320W, Active: 560W, Standby: 4.5W Sleep: 1.4W, Typical Electricity Consumption (TEC): 0.6kWh/w Acoustic Noise Levels Sound Power: Active: 6.5B, Standby: 4.3B or less Sound Pressure: Active: 50dB, Standby: Inaudible Operating Environment Temperature: 50 to 86°F (10 to 30°C) Humidity: 20% to 80% RH (no condensation) Power Source 220 - 240V (±10%), 50/60Hz (±2Hz)
Standard disclaimers. All specifications subject to change without notice 1) Based on ISO/IEC 19752 2) Ships with 1000 pages starter cartridge 3) Based on ITU-T Standard Chart No. 1 4) Web distribution only	



Canon Electronics Inc  
canon.com

Canon Europe  
canon-europe.com

European Edition 0000  
© Canon Europa N.V.,  
2012 (0000)