

## Safety Data Sheet

Carbon & Alloy Steel

#### **SECTION 1: Identification**

#### 1.1 Product identifier

Product name Carbon & Alloy Steel

#### 1.2 Other means of identification

Not available

#### 1.3 Recommended use of the chemical and restrictions on use

Carbon & Alloy Steel Raw Materials & Components

#### 1.4 Supplier's details

Name Reliable Source, Inc.
Address 11109 Jasmine St
Fontana, CA 92337

USA

 Telephone
 909-357-1211

 Fax
 909-357-1311

 email
 info@rsmetals.us

#### 1.5 Emergency phone number(s)

909-357-1211 (business hours)

## **SECTION 2: Hazard identification**

#### **General hazard statement**

The product as delivered does not present a health hazard. However, if user activities generate dust, fumes or mists during processing and handling (melting, welding, sawing, brazing, grinding and machining), it may become hazardous.

#### 2.1 Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Carcinogenicity, Cat. 2
- Sensitization, respiratory, Cat. 1
- Sensitization, skin, Cat. 1
- Specific target organ toxicity (repeated exposure), Cat. 1
- Toxic to reproduction, Cat. 1A

- Toxic to reproduction, effects on or via lactation

#### 2.2 GHS label elements, including precautionary statements

#### **Pictogram**



Signal word Danger

Hazard statement(s)

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 Suspected of causing cancer

H360 May damage fertility or the unborn child May cause harm to breast-fed children H362 H372

Causes damage to organs through prolonged or repeated exposure

Precautionary statement(s)

P201 Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. P202

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P263 Avoid contact during pregnancy/while nursing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace. P272 P280 Wear protective gloves/protective clothing/eye protection/face protection.

In case of inadequate ventilation wear respiratory protection. P284

IF SWALLOWED: Call a POISON CENTER /doctor if you feel unwell P301+P312

IF ON SKIN: Wash with plenty of water P302+P352

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention. P333+P313

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor

P363 Wash contaminated clothing before reuse.

#### Other hazards which do not result in classification

No data available

## **SECTION 3: Composition/information on ingredients**

#### 3.1 **Substances**

Not applicable.

#### **Mixtures** 3.2

#### Components

Component		Concentration
Iron (CAS no.: 7439-89-6)		75 - 100 % (weight)
CLASSIFICATIONS: No data available.		
Tungsten (CAS no.: 7440-33-7)		5 - 10 % (weight)
CLASSIFICATIONS: No data available.		
Chromium compounds (as Cr (III)) (CAS no.: 7440-4	7-3)	5 - 10 % (weight)

CLASSIFICATIONS: Sensitization, skin, Cat. 1; Sensitization, respiratory, Cat. 1; Serious eye damage/eye irritation, Cat. 2; Hazardous to the aquatic environment, long-term (chronic), Cat. 4. NICKEL (CAS no.: 7440-02-0; EC no.: 231-111-4) 5 - 10 % (weight) CLASSIFICATIONS: Carcinogenicity, Cat. 2; Specific target organ toxicity (repeated exposure), Cat. 1; Sensitization, skin, Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 3. Zinc (CAS no.: 7440-66-6; EC no.: 231-175-3) 5 - 10 % (weight) CLASSIFICATIONS: Hazardous to the aquatic environment, short-term (acute), Cat. 1; Hazardous to the aquatic environment, long-term (chronic), Cat. 1. Silicon (CAS no.: 7440-21-3) 1 - 5 % (weight) CLASSIFICATIONS: No data available. Manganese (CAS no.: 7439-96-5) 1 - 5 % (weight) CLASSIFICATIONS: No data available. Carbon (CAS no.: 7440-44-0) 1 - 5 % (weight) CLASSIFICATIONS: No data available. LEAD (CAS no.: 7439-92-1; EC no.: 231-100-4) 0.1 - 1 % (weight) CLASSIFICATIONS: Toxic to reproduction, Cat. 1A; Lact.

### **SECTION 4: First-aid measures**

#### 4.1 Description of necessary first-aid measures

General advice Consult a physician. Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled If breathed in, move person into fresh air. If not breathing, give artificial

respiration. Consult a physician.

In case of skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower

for at least 15 minutes. Call a poison center or doctor if irritation develops or

persists. Wash contaminated clothing before reuse.

In case of eye contact Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical attention/advice.

If swallowed Rinse mouth. If vomiting occurs naturally, have victim lean forward to reduce

the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Call a poison center or doctor.

#### 4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2) and/or in section 11

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

No data available.

## **SECTION 5: Fire-fighting measures**

### 5.1 Suitable extinguishing media

Use alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Specific hazards arising from the chemical

Combustion products may contain metal oxides.

#### 5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

### **SECTION 6: Accidental release measures**

Reliable Source, Inc.

www.reliablesourcemetals.com

Version: 1, Revision: 0, Date of issue: February 28, 2019, p. 3 of 11

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid actions that cause dust to become airborne. Do not breathe dust or mist. Avoid contact with skin. Wear appropriate personal protective equipment as described in Section 8.

#### 6.2 Environmental precautions

Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

#### Reference to other sections

For disposal see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Avoid dust, mist or fume formation. Ensure adequate ventilation. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes and clothing. Avoid ingestion and inhalation. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Normal temperatures and pressures do not affect the material. Keep in a dry and well-ventilated place.

#### Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

US OSHA Permissible Exposure Limits, Annotated Table Z-1, www.osha.gov:

	OSHA PEL (C) Ceiling	Cal/OSHA PEL 8-hour TWA (ST) STEL (C) Ceiling	NIOSH REL Up to 10-hour TWA (ST) STEL (C) Ceiling	ACGIH® TLV® 8-hour TWA (ST) STEL (C) Ceiling
Chromium (III) compounds (CAS no.: 7440-47-3)	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>	0.003 mg/m³-(IHL), water soluble
Chromium (VI) compounds	(C) 1 mg/10m <sup>3</sup> Chromic acid and chromates	0.005 mg/m³ as Cr (C) 0.1 mg/m³	Ca 0.0002 mg/m³ (8-hr- TWA)	0.0002 mg/m³(IHL) (ST) 0.0005 mg/m³(IHL), water soluble
Lead inorganic (as Pb) (CAS no.: 7439-92-1) see 1910.1025		0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>
Silicon (CAS no.: 7440-21-3)				
Total dust	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	
Respirable fraction	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	

Nickel, metal and insoluble compounds (as Ni) (CAS no.: 7440-02-0)	1 mg/m³	metal 0.5 mg/m <sup>3</sup> insoluble 0.1 mg/m <sup>3</sup>	Ca 0.015 mg/m <sup>3</sup>	elemental: 1.5 mg/m³ (IHL); insoluble inorganic compounds: 0.2 mg/m³ (IHL)
Nickel, soluble compounds (as Ni) (CAS no.: 7440-02- 0)	1 mg/m³	0.05 mg/m <sup>3</sup>	Ca 0.015 mg/m <sup>3</sup>	soluble inorganic compounds: 0.1 mg/m³ (IHL)
Manganese compounds and fume (CAS no.: 7439-96-5)	(C) 5 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>	1 mg/m <sup>3</sup> (ST) 3 mg/m <sup>3</sup>	0.02 mg/m <sup>3</sup> (resp.) 0.1 mg/m <sup>3</sup> (IHL) (for elemental and inorganic compounds)

Abbreviations: C = Ceiling limit; Ca = Potential occupational carcinogens; CAS No. = Chemical Abstract Service Number; IHL = Inhalable; ppm = parts per million; STEL = Short Term Exposure Limit; Thor. = Thoracic fraction; TLV® = Threshold Limit Value; TWA – Time weighted average

#### 8.2 Appropriate engineering controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

#### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### **Pictograms**





#### Eye/face protection

When engaged in activities where ingredients could contact the eye, wear safety glasses with side shields or goggles. In extremely dusty environments and unpredictable environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Wear face shield during welding or burning. Eye protection equipment must be tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU)

#### Skin protection

Wear protective gloves suitable for the material handled. Consult manufacturer specifications for further information.

#### **Body protection**

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Avoid actions that cause dust exposure to occur. Use local or general ventilation to control exposures below applicable exposure limits. NIOSH or MSHA approved particulate filter respirators should be used in the context of respiratory protection program meeting the requirements of the OSHA respiratory protection standard [29 CFR 1910.134] to control exposures when ventilation or other controls are inadequate or discomfort or irritation is experienced. Respirator and/or filter cartridge selection should be based on American National Standards Institute (ANSI) Standards Z88.2 Practices for Respiratory Protection.

#### Thermal hazards

No data available.

#### **Environmental exposure controls**

Do not let product enter drains.

### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)

Metal Solid

No odor

Odor threshold No data available. Ha No data available. Melting point/freezing point No data available. Initial boiling point and boiling range No data available. Flash point No data available. Evaporation rate No data available. Flammability (solid, gas) No data available. Upper/lower flammability limits No data available. Upper/lower explosive limits No data available.

Vapor pressure
Vapor density
Relative density
Specific gravity
No data available.
No data available.
No data available.
No data available.
7.20 - 7.86

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Insoluble in water

No data available.

Explosive properties

Oxidizing properties

No data available.

No data available.

No data available.

### Other safety information

No data available.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2 Chemical stability

Stable under normal storage conditions.

#### 10.3 Possibility of hazardous reactions

No data available.

#### 10.4 Conditions to avoid

No data available

#### 10.5 Incompatible materials

Strong acids

### 10.6 Hazardous decomposition products

No data available.

### **SECTION 11: Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Components:

IRON (CAS no.: 7439-89-6)

LD50 Òral - Rat Result: 30000 mg/kg

Nickel (CAS no.: 7440-02-0):

LD50 Oral - Rat Result: 9000 mg/kg

Manganese (CAS no.: 7439-96-5):

LD50 Oral - Rat Result: 9000 mg/kg

Carbon (CAS no.: 7440-44-0) LD50 Intravenous – Mouse

Result: 440 mg/kg

#### Skin corrosion/irritation

Based on available data, classification data are not met

#### Serious eye damage/irritation

Based on available data, classification data are not met

#### Respiratory or skin sensitization

May cause an allergic skin reaction. May cause allergy or asthma symptoms of breathing difficulties if inhaled.

#### Germ cell mutagenicity

Based on available data, classification data are not met

#### Carcinogenicity

Suspected of causing cancer.

Components:

Nickel (CAS no.: 7440-02-0):

IARC: 2B - Possibly carcinogenic to humans

NTP: Reasonably anticipated to be Human Carcinogen

#### Reproductive toxicity

May damage fertility or the unborn child

#### STOT-single exposure

Based on available data, classification data are not met

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure

#### **Aspiration hazard**

Based on available data, classification data are not met

#### Additional information

Reliable Source, Inc.

www.reliablesourcemetals.com Version: 1, Revision: 0, Date of issue: February 28, 2019, p. 7 of 11

No data available.

## **SECTION 12: Ecological information**

#### **Toxicity**

No data available on product

Components:

Manganese (CAS no.: 7439-96-5): LC50 - Daphnia magna – 48h

Result: 29 mg/L

Nickel (CAS no.: 7440-02-0): EC50 - Daphnia magna – 48h

Result: 1 mg/L

LEAD (CAS no.: 7439-92-1): LC50 - Cyprinus carpio – 96h

Result: 0.44 mg/L

#### Persistence and degradability

No data available on product

#### **Bioaccumulative potential**

No data available on product

#### Mobility in soil

No data available.

#### Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### Other adverse effects

No data available.

## **SECTION 13: Disposal considerations**

#### Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

#### Disposal of contaminated packaging

Dispose of as unused product.

## **SECTION 14: Transport information**

#### DOT (US)

Not dangerous goods

#### **IMDG**

Not dangerous goods

#### **IATA**

Not dangerous goods

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations specific for the product in question

#### California Prop. 65 Components

WARNING! This product can expose you to chemicals including Nickel and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name: Nickel (Metallic)

CAS number: 7440-02-0 10/01/1989 – Cancer

Chemical name: Nickel compounds

CAS number: 7440-02-0 05/07/2004 – Cancer

Chemical name: Lead and Lead Compounds

CAS number: 7439-92-1 10/01/1992 – Cancer

02/27/1987 - Developmental Toxicity

02/27/1987 - Female Reproductive Toxicity 02/27/1987 - Male Reproductive Toxicity

#### Massachusetts Right To Know Components

Tungsten (CAS no.: 7440-33-7)

Chromium (CAS no.: 7440-47-3)

Zinc (CAS no.: 7440-66-6)

Manganese (CAS no.: 7439-96-5)

Nickel (CAS no.: 7440-02-0)

LEAD (CAS no.: 7439-92-1)

Silicon (CAS no.: 7440-21-3)

#### **New Jersey Right To Know Components**

Tungsten (CAS no.: 7440-33-7)

Chromium (CAS no.: 7440-47-3)

Zinc (CAS no.: 7440-66-6)

Manganese (CAS no.: 7439-96-5)

Nickel (CAS no.: 7440-02-0)

LEAD (CAS no.: 7439-92-1)

Silicon (CAS no.: 7440-21-3)

#### Pennsylvania Right To Know Components

Tungsten (CAS no.: 7440-33-7)

Chromium (CAS no.: 7440-47-3)

Zinc (CAS no.: 7440-66-6)

Manganese (CAS no.: 7439-96-5)

Nickel (CAS no.: 7440-02-0)

LEAD (CAS no.: 7439-92-1)

Silicon (CAS no.: 7440-21-3)

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

Chromium (CAS no.: 7440-47-3)

Zinc (fume or dust) (CAS no.: 7440-66-6)

Manganese (CAS no.: 7439-96-5)

Nickel (CAS no.: 7440-02-0)

LEAD (CAS no.: 7439-92-1)

#### **HMIS Rating**

Carbon & Alloy Steel	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

#### **NFPA Rating**



#### **SECTION 16: Other information**

#### 16.1 Further information/disclaimer

Date of issue: February 28, 2019.

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. All materials may present unknown hazards and should be used with caution. In no event shall we be held liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if we have been advised of the possibility of such damages.

