

CENTRAL HYDRAULICS INC.

•Daytona Beach •Cocoa •Leesburg •Ocala •Tampa 1-800-264-9571

Easy Couple Hose



Boston Easy Couple

BOSTON
Push-on Hose
Low Working Pressure

Applications:

- Pneumatic tools on production line; convey air, water, oils, etc.; transfer lubricated air to valves and cylinders; low pressure hydraulics
- Black hose cover only has been accepted by MSHA (2G-13C) for underground use in lube oil lines, pneumatic, and low pressure hydraulics

Tube: Vinyl Nitrile (RMA Class A)

Reinforcement: Fiber, 1 Braid

Cover: Neoprene MSHA approved (B K), Vinyl Nitrile (BU,GY,RD,YW,GN)

Color: Black(BK), Gray(GY), Blue(BU), Red(RD), Green(GN), & Yellow(YW)

Temperature Range: -40°F to +200°F

Type of Branding: Ink Print

Working Pressure: 250 PSI

Type of Coupling: Barbed inserts or Push on Couplings (clamps not required)

*NOT FOR GASOLINE

Type of Coupling:

- Neoprene cover
- Vinyl nitrile cover
- Nitrile tube (RMA Class A)
- Continuous permanent brand
- Six colors
- Light weight & flexible
- Easily Coupled
- Braid reinforcement

Advantage:

- Abrasion, oil, and weather resistant
- Good oil restance
- Easy identification
- Color coded air systems
- Easy to handle
- Use push-on couplings: no need for clamps
- Better coupling retention for impluse applications

Markets:

- Assembly/Manufacturers
- Mining
- Construction Industry
- Plastic Molding

Uses:

- Diesel Fuel, Water, Oils (not recommended for gasoline).

Part #	Nominal I.D. (in)	Braid	Nominal O.D. (in)	Approx. lbs./100ft	Max PSI	Min Bend Radius (in)	Standard Reel Length
EC4	1/4"	1	1/2"	8	250	3	500
EC6	3/8"	1	21/32"	13	250	3	500
EC8	1/2"	1	3/4"	15	250	5	500
EC10	5/8"	1	15/16"	20	250	6	250
EC12	3/4"	1	1-1/16"	26	250	7	250

Fax: 386-257-5728 Tele. 1-800-264-9571 sales@centralhydraulics.com www.centralhydraulics.com