

Section 1 - Identification of The Material and Supplier

E.D. Oates Pty Ltd
Trading as Research Products
13-21 Maygar Boulevard
Broadmeadows, Vic, 3047

Phone: 1300 669 686 (business hours)
Fax: (03) 9359 9509
Email: customerservice@oates.com.au
Website: www.oateslaboratories.com.au

Chemical nature: Water based preparation.

Trade Name: **TANNERS CHOICE PROTECTOR**

Product Use: Leather rejuvenator/protector. For professional use only.

Creation Date: **August, 2013**

This version issued: **August, 2013** and is valid for 5 years from this date.

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. F, Flammable. Hazardous according to the criteria of SWA.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R10, R66, R36/37. Flammable. Repeated exposure may cause skin dryness or cracking. Irritating to eyes and respiratory system.

Safety Phrases: S9, S16, S23, S38, S45, S62, S24/25, S36/37. Keep container in a well ventilated place. Keep away from sources of ignition - No smoking. Do not breathe vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment. In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately (show this MSDS where possible). If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

SUSMP Classification: None allocated.

ADG Classification: Class 3: Flammable liquids.

UN Number: 1263, PAINT



GHS Signal word: DANGER

HAZARD STATEMENT:

H226: Flammable liquid and vapour.

AUH066: Repeated exposure may cause skin dryness or cracking.

H315: Causes skin irritation.

H320: Causes eye irritation.

H335: May cause respiratory irritation.

PREVENTION

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing fumes, mists, vapours or spray.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P312: Call a POISON CENTRE or doctor if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P391: Collect spillage.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

STORAGE

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Emergency Overview

Physical Description & Colour: Thick white liquid.

Odour: Characteristic odour.

Major Health Hazards: irritating to eyes and respiratory system, repeated exposure may cause skin dryness or cracking.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Diisobutyl ketone	108-83-8	30-60	145	not set
Nitrocellulose	9004-70-0	10-30	not set	not set
Liquid hydrocarbon	secret	10-30	790	not set
Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Gently blot away excess liquid. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool packages involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances. This product is likely to decompose only after heating to dryness, followed by further strong heating. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 50°C
Upper Flammability Limit: 6.7%
Lower Flammability Limit: 1.2%
Autoignition temperature: No data.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Flammability Class:

Flammable

Section 6 - Accidental Release Measures

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Diisobutyl ketone	145	not set
Liquid hydrocarbon	790	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Thick white liquid.
Odour:	Characteristic odour.
Boiling Point:	Approximately 110°C at 100kPa.
Freezing/Melting Point:	Below 0°C.
Volatiles:	Approx 80%
Vapour Pressure:	2.37 kPa at 20°C (water vapour pressure).
Vapour Density:	As for water.
Specific Gravity:	0.895
Water Solubility:	Dispersible.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	As for water.
Coeff Oil/water Distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition.

Incompatibilities: strong acids, oxidising agents, halogens.

Fire Decomposition: This product is likely to decompose only after heating to dryness, followed by further strong heating. Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Diisobutyl Ketone	Conc>=10%: Xi; R37

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 14 - Transport Information

ADG Code: 1263, PAINT

Hazchem Code: •3Y

Special Provisions: 163, 223

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packaging Group: III

Packaging Method: P001, IBC03, LP01

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredient: Liquid hydrocarbon, is mentioned in the SUSMP.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Emergency Contact: Phone 13 11 26 (Australia wide)

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

Please read all labels carefully before using product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This MSDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, June, 2013.

<http://www.kilford.com.au/> Phone (02)9251 4532

End of Safety Data Sheet

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)