

NU-FLAME STEEL TOPCOAT

Page: 1

Compilation date: 19/01/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NU-FLAME STEEL TOPCOAT

Product code: HPC 104

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Consumer applications, Professional applications

1.3. Details of the supplier of the safety data sheet

Company name: Hydron Protective Coatings Ltd

Unit 7, Phoenix Road

Wednesfield
Wolverhampton
WV11 3PX

United Kingdom

Tel: +44(0)1902 450 950

Email: enquiries@hydronpc.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)1902 450 950

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

Hazard pictograms: GHS02: Flame



Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P370+378: In case of fire: Use carbon dioxide to extinguish.

P233: Keep container tightly closed.

[cont...]

NU-FLAME STEEL TOPCOAT

P240: Ground container and receiving equipment.

P501: Dispose of contents/container to.

P403+235: Store in a well-ventilated place. Keep cool.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

2.3. Other hazards

Other hazards: Flammable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: NU-FLAME STEEL TOPCOAT

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Consult a doctor. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing

becomes bubbly, have the casualty sit and provide oxygen if available.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable.

[cont...]

Page: 2

NU-FLAME STEEL TOPCOAT

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained

breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Remove all incompatible materials as outlined in section 10 of SDS. Turn leaking

containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and

explosion-proof equipment. Dilute with water and mop up if water-soluble.

Alternatively, or if water-insoluble, absorb with an inert dry material and place in an

appr

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Avoid incompatible materials and conditions - see

section 10 of SDS. Keep away from sources of ignition. Keep away from direct sunlight.

Avoid contact with water or humidity.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

NU-FLAME STEEL TOPCOAT

Page: 4

8.2. Exposure controls

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator.

Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer,

chec

Eye protection: Safety glasses. **Skin protection:** Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

Odour: Hydrocarbon (slight)

Evaporation rate: Not applicable.

Oxidising: Not applicable.

Solubility in water: Insoluble in cold water

Viscosity: 60 - 100 s (ISO 6mm)

Boiling point/range°C: 145 Melting point/range°C: No data available.

Flammability limits %: lower: 0.61

Flash point°C: Closed cup: 41°C Vapour pressure: Highest known value:

upper: 6.21

Relative density: 1.17 pH: No data available.

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids. Alkalis.

NU-FLAME STEEL TOPCOAT

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: Decomposition products may include the following materials: carbon monoxide,

carbon dioxide, smoke, oxides of nitrogen.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>6	g/kg
VAPOURS	RAT	4H LC50	8500	mg/kg

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
BLUEGILL (Lepomis macrochirus)	4H LC50	2200	μg/l
FISH	96H LC50	843000	μg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

Persistence (P-):

Persistence result: not P-

Bioaccumulation (B-):

Bioconcentration factor (BCF): 159

Bioaccumulation result: not B-

NU-FLAME STEEL TOPCOAT

Page: 6

Toxicity (T-):

Toxicity result: not T-

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No known significant effects or critical hazards.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with

the requirements of environmental protection and waste disposal legislation.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

(LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY; KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM),

HYDROTREATED LIGHT; 2-BUTANONE OXIME)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |

14.5. Environmental hazards

Environmentally hazardous: No **Marine pollutant:** No

14.6. Special precautions for user

Tunnel code: D/E
Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

NU-FLAME STEEL TOPCOAT

Page: 7

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.