

TECHNICAL DATA SHEET

HPC 106 / 107 NU-FLAME FR UNDERCOAT / GLOSS

DESCRIPTION:

Nu-Flame FR Undercoat and FR Gloss are oil based flame retardant paints for new and previously painted surfaces where a gloss finish is required.

ADVANTAGES:

When Nu-Flame FR Undercoat and FR Gloss are used together. They provide a washable weather resistant finish for interior and exterior use.

Tested to BS 476 part 7 and passes Class 1 surface spread of flame

USES:

For use on door, skirting and other timber finishes.
 To complement the Nu-Flame wall finishes.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or spray. Should not be applied at temperatures below 5°C, Or when relative humidity exceeds 85%.

EQUIPMENT CARE:

All equipment should be cleaned with white spirit.

STORAGE:

Store away from direct sunlight and sources of heat.
 Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

	HPC 106 Nu-Flame FR Undercoat	HPC 107 Nu-Flame FR Gloss
COLOUR	Any RAL / BS4800 Colour	Any RAL / BS4800 Colour
PACK SIZE	SP 5 Litres	SP 5 Litres
COVERAGE	14 m ² /litre	14 m ² /litre
DRYING TIME	4 Hours 16 Hours	4 Hours 12 Hours