

## Safety Data Sheet

**Material Name: Iron-Grip® 601****Product #: 304135- 1 gal  
304137- 11oz**

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name**

Iron-Grip® 601

**Synonyms**

Sealant

**Chemical Family**

Water based mastic

**Product Use**

Duct sealant

**Restrictions on Use**

For industrial use only.

**Manufacturer Information**

Carlisle HVAC Products  
900 Hensley Lane  
Wylie, TX 75098  
www.carlislehvac.com

**Medical Emergency:****CHEMTREC (USA): (800) 424-9300**

MSDS Assistance – 972-442-6545

Technical Assistance – 888-229-2199

Customer Service – 888-229-0199

---

### Section 2 - HAZARDS IDENTIFICATION

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 1 ( central nervous system, eyes, body, systemic toxicity )

Specific Target Organ Toxicity - Repeated Exposure - Category 1 ( eyes,central nervous system )

**GHS Label Elements****Symbol(s)****Signal Word**

Danger

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Hazard Statement(s)

May damage fertility or the unborn child

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure

### Precautionary Statement(s)

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Do not eat, drink or smoke when using this product

#### Response

If exposed: Call a POISON CENTER or doctor/physician

Get medical advice/attention if you feel unwell

Specific treatment (see label)

#### Storage

Store locked up

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

#### Statement of Unknown Toxicity

88.189% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### Other Hazards

No additional information available.

---

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

CAS	Component Name	Percent
Trade Secret	De-foaming agent	0.1-1
Trade Secret	Nonylphenol polyethylene glycol ether	0.1-1
Mixture	Polymer, ethyl acrylate and methacrylic acid	0.1-1
Mixture	Acrylic polymer	0.1-1
141-43-5	Ethanolamine	0.1-1
Mixture	Polycarboxylate salt	0.1-1
107-21-1	Ethylene glycol	0.1-1
Mixture	Fuller's earth	1-5

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

14808-60-7	Silica, crystalline	0.1-1
1317-65-3	Limestone	15-40
Trade Secret	Clay compound	1-5
67-56-1	Methanol	1-5
Mixture	4,4-Dimethyloxazolidine	0.1-1
Mixture	1,2-Propylene glycol	0.1-1

---

### Section 4 - FIRST AID MEASURES

---

#### Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

#### Skin

Wash exposed skin with soap and water. Remove contaminated clothing and wash it before reuse. If skin irritation occurs, get medical advice/attention.

#### Eyes

Flush eyes with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### Ingestion

Do NOT induce vomiting. If swallowed, get medical attention.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

#### Most Important Symptoms/Effects

##### Acute

Causes damage to central nervous system, body, eyes, systemic toxicity.

##### Delayed

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

#### Note to Physicians

Contains. ethylene glycol, methanol

---

### Section 5 - FIRE FIGHTING MEASURES

---

#### Extinguishing Media

##### Suitable Extinguishing Media

Use dry chemical, carbon dioxide, alcohol-resistant foam or water spray.

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Unsuitable Extinguishing Media

None reported.

### Special Hazards Arising from the Chemical

Slight fire hazard. Sealed containers may rupture or explode if exposed to heat.

### Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen, hydrocarbons

### Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure. Do not inhale any material or combustion by-products.

### Fire Fighting Measures

Remove product from area of fire. Stay upwind and keep out of low areas.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

### Environmental Precautions

Avoid release to the environment.

---

## Section 7 - HANDLING AND STORAGE

---

### Precautions for Safe Handling

This product contains crystalline silica, which is a known carcinogen: Do not grind or sand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

### Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Store in a well-ventilated place. Store above 0 C. Store below 45 C. When not in use, keep containers tightly closed. Do not cut, puncture, or weld on or near this container.

### Incompatible Materials

Strong acids, strong oxidizing agents

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Component Exposure Limits

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

<b>Ethanolamine</b>	141-43-5	
ACGIH:	3 ppm TWA	6 ppm STEL
NIOSH:	3 ppm TWA; 8 mg/m3 TWA	6 ppm STEL; 15 mg/m3 STEL
	30 ppm IDLH	
Europe:	1 ppm TWA; 2.5 mg/m3 TWA	3 ppm STEL; 7.6 mg/m3 STEL
	Possibility of significant uptake through the skin	
OSHA (US):	3 ppm TWA; 6 mg/m3 TWA	
Mexico:	3 ppm TWA LMPE-PPT; 8 mg/m3 TWA LMPE-PPT	
	6 ppm STEL [LMPE-CT]; 15 mg/m3 STEL [LMPE-CT]	
<b>Ethylene glycol</b>	107-21-1	
ACGIH:	100 mg/m3 Ceiling aerosol only	
Europe:	20 ppm TWA; 52 mg/m3 TWA	40 ppm STEL; 104 mg/m3 STEL
	Possibility of significant uptake through the skin	
Mexico:	100 mg/m3 Ceiling aerosol	
<b>Silica, crystalline</b>	14808-60-7	
ACGIH:	0.025 mg/m3 TWA respirable fraction	
NIOSH:	0.05 mg/m3 TWA respirable dust	50 mg/m3 IDLH respirable dust
OSHA (US):	((30)/(%SiO <sub>2</sub> + 2) mg/m3 TWA) total dust; ((250)/(%SiO <sub>2</sub> + 5) mppcf TWA) respirable fraction; ((10)/(%SiO <sub>2</sub> + 2) mg/m3 TWA) respirable fraction	
Mexico:	0.1 mg/m3 TWA LMPE-PPT respirable fraction	
<b>Limestone</b>	1317-65-3	
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust	
OSHA (US):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction	
Mexico:	10 mg/m3 TWA LMPE-PPT	20 mg/m3 STEL [LMPE-CT]
<b>Methanol</b>	67-56-1	

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

ACGIH:	200 ppm TWA	250 ppm STEL
	Skin - potential significant contribution to overall exposure by the cutaneous route	
NIOSH:	200 ppm TWA; 260 mg/m3 TWA	250 ppm STEL; 325 mg/m3 STEL
	Potential for dermal absorption	
	6000 ppm IDLH	
Europe:	200 ppm TWA; 260 mg/m3 TWA	
	Possibility of significant uptake through the skin	
OSHA (US):	200 ppm TWA; 260 mg/m3 TWA	
Mexico:	200 ppm TWA LMPE-PPT; 260 mg/m3 TWA LMPE-PPT	
	250 ppm STEL [LMPE-CT]; 310 mg/m3 STEL [LMPE-CT]	
	Skin - potential for cutaneous absorption	

### Biological limit value

There are no biological limit values for any of this product's components.

### Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### Skin Protection

Wear appropriate work clothing.

#### Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

#### Glove Recommendations

Wear protective gloves. Recommended material: Hycron(R), neoprene, nitrile.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	thick gray paste	<b>Physical State</b>	liquid
<b>Odor</b>	Slight, ammonia	<b>Color</b>	gray
<b>Odor Threshold</b>	Not available	<b>pH</b>	8.4 - 9.5
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	212 °F
<b>Freezing point</b>	Not available	<b>Evaporation Rate</b>	30 - 40 % volatile
<b>Boiling Point Range</b>	Not available	<b>Flammability (solid, gas)</b>	Not available

## Safety Data Sheet

Material Name: Iron-Grip® 601

Product #: 304135- 1 gal  
304137- 11oz

<b>Autoignition</b>	Not available	<b>Flash Point</b>	Not available
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition</b>	Not available
<b>Upper Explosive Limit</b>	Not available	<b>Vapor Pressure</b>	17 mmHg (@ 20 °C)
<b>Vapor Density (air=1)</b>	>1	<b>Specific Gravity (water=1)</b>	Not available
<b>Water Solubility</b>	soluble	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	300 Kcps (@ 77 °F)	<b>Solubility (Other)</b>	Not available
<b>Density</b>	1.32 (relative)	<b>VOC</b>	49 g/L (SCAQMD calculation method)

### Other Information

No additional information available.

---

## Section 10 - STABILITY AND REACTIVITY

---

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable under normal conditions of use.

### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

### Incompatible Materials

Strong acids, strong oxidizing agents

### Hazardous decomposition products

Oxides of carbon, oxides of nitrogen, hydrocarbons

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### Information on Likely Routes of Exposure

#### Inhalation

May cause adverse effects on the central nervous system.

#### Skin Contact

May cause mild skin irritation.

#### Eye Contact

May cause mild eye irritation.

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Ingestion

Methanol can produce blindness with onset of symptoms being delayed for 18-24 hours.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Ethylene-vinyl acetate copolymer (Trade Secret)

Oral LD50 Rat >2000 mg/kg

Epoxidized soybean oil (Trade Secret)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >20 mL/kg

De-foaming agent (Trade Secret)

Oral LD50 >2000 mg/kg

Nonylphenol polyethylene glycol ether (Trade Secret)

Oral LD50 Rat 2780 mg/kg

Chlorinated paraffins (Trade Secret)

Oral LD50 Rat >4000 mg/kg

Polymer, ethyl acrylate and methacrylic acid (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

Acrylic polymer (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

Ethanolamine (141-43-5)

Oral LD50 Rat 1515 mg/kg

Dermal LD50 Rabbit 2504 mg/kg

Inhalation LC50 Rat >1.3 mg/L vapor 6 hr

Polycarboxylate salt (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Ethylene glycol (107-21-1)

Oral LD50 Rat 4700 mg/kg

Dermal LD50 Rat 10600 mg/kg

Inhalation LC50 Rat >200 mg/m<sup>3</sup> vapor 4 hr

Silica, crystalline (14808-60-7)

Oral LD50 Rat 500 mg/kg

Limestone (1317-65-3)

Oral LD50 Rat 6450 mg/kg

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

**Methanol (67-56-1)**

Oral LD50 Rat 6200 mg/kg

Inhalation LC50 Rat 22500 ppm 8 h

**4,4-Dimethyloxazolidine (Mixture)**

Oral LD50 Rat 1037 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Inhalation LC50 Rat 1.1 mg/L 4 hr

**1,2-Propylene glycol (Mixture)**

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

**Immediate Effects**

Causes damage to central nervous system, body, eyes, systemic toxicity.

**Delayed Effects**

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

**Irritation/Corrosivity Data**

May cause mild skin irritation. May cause mild eye irritation.

**Respiratory Sensitization**

No data available.

**Dermal Sensitization**

No data available.

**Component Carcinogenicity**

<b>Chlorinated paraffins</b>	Trade Secret
IARC:	Monograph 48 [1990] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present
<b>Ethylene glycol</b>	107-21-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
<b>Silica, crystalline</b>	14808-60-7
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

OSHA:	Present (respirable size)
-------	---------------------------

### Germ Cell Mutagenicity

No data available.

### Reproductive Toxicity

May damage fertility or the unborn child.

### Specific Target Organ Toxicity - Single Exposure

Central nervous system, body, systemic toxicity, eyes

### Specific Target Organ Toxicity - Repeated Exposure

Central nervous system, eyes

### Aspiration hazard

No data available.

### Medical Conditions Aggravated by Exposure

No data available.

### Additional Data

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

---

## Section 12 - ECOLOGICAL INFORMATION

---

### Ecotoxicity

Avoid release to the environment.

### Component Analysis - Aquatic Toxicity

<b>Ethylene-vinyl acetate copolymer</b>	Trade Secret
Fish:	LC50 96 hr Cyprinus carpio >1000 mg/kg
<b>Epoxidized soybean oil</b>	Trade Secret
Fish:	LC50 48 hr freshwater fish 900 mg/L
Algae:	EC50 72 h Desmodesmus subspicatus 8 mg/L IUCLID
<b>De-foaming agent</b>	Trade Secret
Fish:	LC50 hr fish >100 mg/L
<b>Chlorinated paraffins</b>	Trade Secret
Fish:	LC50 96 h Lepomis macrochirus >300 mg/L [static]; LC50 96 h Oncorhynchus mykiss >0.0109 mg/L [flow-through];

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

	LC50 96 h Oncorhynchus mykiss 94.5 - 271 mg/L [static]; LC50 96 h Lepomis macrochirus >0.1 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]
Invertebrate:	EC50 48 hr Daphnia magna 0.0059 mg/L
<b>Polymer, ethyl acrylate and methacrylic acid</b>	Mixture
Fish:	LC50 96 hr Pimephales promelas >1000 mg/L
<b>Ethanolamine</b>	141-43-5
Fish:	LC50 96 h Pimephales promelas 227 mg/L [flow-through]; LC50 96 h Brachydanio rerio 3684 mg/L [static]; LC50 96 h Lepomis macrochirus 300 - 1000 mg/L [static]; LC50 96 h Oncorhynchus mykiss 114 - 196 mg/L [static]; LC50 96 h Oncorhynchus mykiss >200 mg/L [flow-through]
Algae:	EC50 72 h Desmodesmus subspicatus 15 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 65 mg/L IUCLID
<b>Ethylene glycol</b>	107-21-1
Fish:	LC50 96 h Oncorhynchus mykiss 41000 mg/L; LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L [static]; LC50 96 h Lepomis macrochirus 27540 mg/L [static]; LC50 96 h Oncorhynchus mykiss 40761 mg/L [static]; LC50 96 h Pimephales promelas 40000 - 60000 mg/L [static]; LC50 96 h Poecilia reticulata 16000 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 46300 mg/L IUCLID
<b>Limestone</b>	1317-65-3
Fish:	LC50 hr fish >200 mg/L
<b>Methanol</b>	67-56-1
Fish:	LC50 96 h Pimephales promelas 28200 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static];

## Safety Data Sheet

**Material Name: Iron-Grip® 601****Product #: 304135- 1 gal  
304137- 11oz**

	LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static]; LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through]
<b>1,2-Propylene glycol</b>	Mixture
Fish:	LC50 96 h Oncorhynchus mykiss 51600 mg/L [static]; LC50 96 h Oncorhynchus mykiss 41 - 47 mL/L [static]; LC50 96 h Pimephales promelas 51400 mg/L [static]; LC50 96 h Pimephales promelas 710 mg/L
Algae:	EC50 96 h Pseudokirchneriella subcapitata 19000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L [static] EPA

**Persistence and Degradability**

No information available for the product.

**Bioaccumulative Potential**

No information available for the product.

**Mobility**

No information available for the product.

**Other Toxicity**

No additional information available.

---

**Section 13 - DISPOSAL CONSIDERATIONS**

---

**Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

---

**Section 14 - TRANSPORT INFORMATION**

---

**US DOT Information:**

UN/NA #: Not regulated

**IATA Information:**

UN#: Not regulated

**IMDG Information:**

UN#: Not regulated

**TDG Information:**

UN#: Not regulated

## Safety Data Sheet

Material Name: Iron-Grip® 601

Product #: 304135- 1 gal  
304137- 11oz

### Section 15 - REGULATORY INFORMATION

#### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Ethylene glycol	107-21-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ
Methanol	67-56-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ

#### SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactivity: No

#### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Chlorinated paraffins	Trade Secret	No	Yes	No	No	No
Ethanolamine	141-43-5	Yes	Yes	Yes	Yes	Yes
Ethylene glycol	107-21-1	Yes	Yes	Yes	Yes	Yes
Silica, crystalline	14808-60-7	No	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Methanol	67-56-1	Yes	Yes	Yes	Yes	Yes
1,2-Propylene glycol	Mixture	No	No	Yes	Yes	Yes

#### The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Silica, crystalline	14808-60-7
Carc:	carcinogen , initial date 10/1/88 (airborne particles of respirable size)
Methanol	67-56-1
Repro/Dev. Tox	Developmental toxicity , initial date 3/16/12

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Ethanolamine	141-43-5
	1 %
Ethylene glycol	107-21-1
	1 %
Silica, crystalline	14808-60-7
	1 %
Methanol	67-56-1
	1 %
1,2-Propylene glycol	Mixture
	1 %

### Component Analysis - Inventory

Ethylene-vinyl acetate copolymer (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	ELN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Epoxidized soybean oil (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Nonylphenol polyethylene glycol ether (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Chlorinated paraffins (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Polymer, ethyl acrylate and methacrylic acid (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Ethanolamine (141-43-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Ethylene glycol (107-21-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Fuller's earth (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

### Silica, crystalline (14808-60-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Methanol (67-56-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### 4,4-Dimethyloxazolidine (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

### 1,2-Propylene glycol (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

## Section 16 - OTHER INFORMATION

### HMIS Rating

Health: 1\* Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

### NFPA Ratings

Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

Revision Date: June 5, 2018

Revision Note: General Update

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

## Safety Data Sheet

**Material Name: Iron-Grip® 601**

**Product #: 304135- 1 gal  
304137- 11oz**

### Other Information

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.