


POWER ANGLE SNOW PLOUGH BLADE MODEL SL20

WORK POSITIONS



TECHNICAL SPECIFICATIONS

- AUTOMATIC, FULL-TIP, SHOCKPROOF DEVICE WITH LOW TEMPERATURE RESISTANT, URETHANE RUBBER ELASTOMETERS (PATENTED);
- ADJUSTABLE SHOCKPROOF VALVE;
- SWIVEL CYLINDERS FOR HIGH PRESSURES;
- LARGE, INTERCHANGEABLE, ANTI-WEAR AND TEAR STEEL SCRAPER BLADE EDGES;
- QUICK-HITCH PLATE;
- ADJUSTABLE SUPPORT FEET;
- HIGH PRESSURE, HYDRAULIC HOSES WITH QUICK-LOCK CONNECTIONS, CONNECTED TO THE CENTRAL PART OF THE FRAME;
- FRAME DESIGNED TO EXCLUDE ANY NEGATIVE REACTION FROM HARD-PACKED SNOW BETWEEN MOVING PARTS AND TO ENSURE SAFE CONDITIONS AND A LONG WORKING LIFE EVEN AT HIGH SPEEDS;
- SEALED ELECTRICAL SYSTEM WITH LED LIGHTS;
- MARKER POLES SUPPORT;
- CUSTOMISED MEASUREMENTS;
- WIDE RANGE OF ACCESSORIES.

RUSTPROOF TREATMENTS

- SAND-BLASTING;
- RUSTPROOF PRIMER;
- POLYURETHANE PAINT TOPCOAT.

TECHNICAL DATA

- **LENGTH SCRAPER BLADE EDGE**
Maximum 2500 mm. - Minimum 2000 mm.
- **OVERALL DIMENSIONS (when tilted)**
Maximum 2000 mm - Minimum 1660 mm.
- **SL20 PIANA:** Height 730 mm – Weight without couplings 270 Kg.
- **SL20 MONTAGNA:** Side height 900 mm.
Central height 730 mm.
Weight without couplings 310 kg

