




# WATER TRANSFER

## SOLIDS HANDLING PUMPS



### N SERIES

DISCHARGE SIZE RANGE	3" TO 30"
MAX SOLIDS HANDLING SIZE	10.2"
MAX FLOW	38,000 GPM
MAX HEAD	500'

**IMPELLER CHOICES:** choose from the Delta style impeller for heavy sludge, two and three port enclosed impellers for large solids, and three or four bladed, semi-open impeller with cutting action for the worst slurries/solids.

### MATERIALS OF CONSTRUCTION

- Ductile or cast iron pump casings
- Some models available in CD4MCu
- Ductile, cast iron, or CD4MCu impellers
- Stressproof or heat-treated steel shafts (stainless on CD4MCu models)
- 420HT wear rings and shaft sleeve available

### FEATURES

- Cycloseal® grit removal system
- High-efficiency design
- Run-Dry™ and Redi-Prime® Options
- Excellent NPSHr
- Ruggedness and durability
- Two-year warranty

## CONSTRUCTION PUMPS



### DURAPRIME SERIES

DISCHARGE SIZE	3" TO 6"
MAX SOLIDS HANDLING SIZE	3"
MAX FLOW	3050 GPM
MAX HEAD	205'

Robust **DURAPRIME** construction pumps are ideal for rental and construction applications. The Duraprime series feature a rebuild-able pump design, robust construction, efficient operation and competitive pricing.

### MATERIALS OF CONSTRUCTION

- Ductile iron casings
- 17-4PH stainless steel shafts
- 303 Shaft sleeves
- Ductile Iron impellers

### FEATURES

- Cycloseal® grit removal system
- High-efficiency design; up to 82%
- Run-Dry™, Venturi-Prime, Redi-Prime®, and bare pump options
- Easy servicing and upkeep of pumps
- Long life and low maintenance costs
- Two-year warranty