



PROTECT YOUR HOME & FAMILY AND

“LOCK IT UP”

WITH OUR ADVANCED PET DOOR SECURITY COVER

INSTALLING YOUR NEW WATCHDOG SECURITY PET DOOR COVER

WE ALWAYS RECOMMEND INSTALLING YOUR WATCHDOG SECURITY PET DOOR COVER ON THE OUTSIDE FOR MAXIMUM SECURITY, HOWEVER IT CAN BE INSTALLED ON THE INSIDE AS LONG IT IS SECURELY FASTENED.

TOOLS NEEDED (NOT INCLUDED IN BOX)



LEVEL, PENCIL, HEX BIT WRENCH FLAT HEAD SCREWDRIVER & “LOCK TITE” (FOR DOOR ENTRY DOOR INSTALLATION) & APPROPRIATE DRILL BIT & DRILL.

CHOOSE TYPE OF INSTALLATION METHOD

1) INSTALLATION ON TO AN ENTRY DOOR:

- USE PROVIDED TAMPER RESISTANT SCREWS & TEE NUT
- ALSO RECOMMENDED TO THREAD THE BOLT WITH “LOCK-TITE” (NOT INCLUDED – CAN BE FOUND AT YOUR LOCAL HARDWARE STORE) TO PROVIDE ADDITIONAL SECURITY FROM BOLT AND

TEE NUT FROM TURNING (USE A 3/16 HEX NUT WRENCH – NOT INCLUDED)

- AT TIMES THE BOLT MAY BE LONGER THAN YOU NEED TO SECURITY THE DOOR FRAME, IT SO, YOU CAN SHORTEN THE BOLT BY CUTTING IT TO THE DESIRED LENGTH. ANOTHER OPTION WOULD BE TO INTALL WASHERS BEHIND THE BOLT OR TEE NUT TO SHORTEN THE LENGTH AS WELL, BUT MAY NOT LOOK ASTHETICALLY PLEASING.

2) INSTALLATION ON TO A BLOCK WALL:

- USE PROVIDED TAMPER RESISTANT SCREWS & ANCHORS.
- YOU WILL ALSO NEED A 3/8" MASONARY DRILL BIT AND FLAT HEAD SCREWDRIVER OR BIT (NOT INCLUDED).

3) INSTALLATION ON TO A WOOD CLAD:

- USE PROVIDED TAMPER RESISTANT SCREWS.
- YOU WILL ALSO NEED A 3/8" MASONARY DRILL BIT AND FLAT HEAD SCREWDRIVER OR BIT (NOT INCLUDED).
- IT IS BEST TO PILOT THE SCREWS WITH A 3/32" WOOD OR METAL DRILL BIT (NOT INCLUDED).

4) INSTALLATION ON TO A STUCCO CLAD SURFACE:

- USE PROVIDED TAMPER RESISTANT SCREWS & ANCHORS
 - YOU WILL ALSO NEED A 3/8" MASONARY DRILL BIT AND FLAT HEAD SCREWDRIVER OR BIT (NOT INCLUDED).
-

INSTALLATION OF YOUR NEW WATCHDOG SECURITY PET DOOR COVER

FOR THE BEST RESULTS, THE WATCHDOG SECURITY PET DOOR COVER MUST FIT FLUSH TO THE WALL OVER THE EXISTING PET DOOR FRAME.

STEPS:

- 1) REMOVE THE DOOR FROM THE FRAME. YOU WILL FIND IT TO BE EASIER TO INSTALL THE DOOR FRAME. CENTER THE SECURITY DOOR TO YOUR EXISTING PET DOOR AND MARK THE HOLE OUTLETS WITH A PENCIL.
- 2) WITH A LEVEL CHECK TO SEE IF YOU'RE EXISTING PET DOOR IS LEVEL IF IT IS YOU CAN USE IT TO LEVEL YOUR WATCHDOG SECURITY PET DOOR. IF YOUR EXISTING DOOR IS NOT LEVEL IT MAY NOT BE SQUARE, YOU MAY NEED TO ADJUST IT SO THAT THE DOOR OPENINGS LINE UP TO EACH OTHER.



3) REMOVE THE DOOR AND DRILL THE CORRECT SIZE HOLE WHERE MARKED. THE SIZE OF THE HOLE WILL CHANGE BASED ON APPLICATION OF FASTENERS.



4) INSTALL THE TAMPER RESISTANT SCREWS OR BOLTS. (DO NOT TIGHTEN YET, YOU MUST ALIGN AND DRILL THE REMAINING THREE HOLES).



5) LEVEL THE DOOR AND REPEAT STEPS TO MARK, DRILL & TEMPORARILY INSTALL UPPER CORNERS WITH TAMPER RESISTANT SCREWS. NOW MARK BOTH BOTTOM HOLES, REMOVE DOOR, AND DRILL THE BOTTOM TWO HOLES. YOU ARE NOW READY TO INSTALL THE FRAME. FIRMLY TIGHTEN THE SCREW HARDWARE TO COMPLETE THE INSTALLATION.





CONGRATULATIONS ON INSTALLING YOUR WATCHDOG SECURITY PET DOOR COVER

“LOCK IT UP”



RETURN POLICY - Before returning a product you must contact Watchdog Security Pet Doors for a return authorization. Contact us at 800-242-5093. A copy of your invoice must be included with all returns.

30 Day Warranty If for any reason you are not satisfied with the performance of any equipment within the 30-day warranty, you may return it for a full refund. All 30 day warranty returns must be in “as-new” condition with the original packaging (also in “as-new” condition). All instruction manuals, accessories, parts, etc. which came with the original shipment must be returned. Prior to returning items, please call Watchdog Security Pet Doors at 800-242-5093 in order to receive shipping instructions and a RMA number. Refunds will be issued after the equipment is received, inspected and verified to be in good working condition. Note: if the products are worn to the point they can’t be resold “as-new” products the 30 day warranty is void. **Shipping costs are non-refundable. Some products may require a re-stocking fee.**

Manufacturer Equipment Warranty - This warranty covers any failure of the equipment due to defective material or workmanship for 30 days. This warranty is provided by the equipment manufacturer and is void if the equipment has been used for purposes other than its intended purpose, abused, or damaged due to improper handling or installation.



Lock Instructions



Feature:

- To alter the code
- Can set 1000 the code
- Easy to fix and simple operation
- Positioning the switch of close and open button, extra security.
- No key
- Outdoor and indoor are suitable
- Provide One-Way Screws

To alter the code:

1. From the factory the code is set to 000
2. To change the code , turn the adjustive SW1 “○” to “△” ,
3. While at the same time changing the code sa desired.
4. Turn back the adjustive SW1 to the original location to finish the setting.
5. If you do not remember the password. Need to be viewed from behind.
Use the flashlight to view the number,
the red number for you to set the password number.