



LEVERAGE WRENCHES



► Proto® leverage wrenches have been specifically engineered for optimum safety. The unique, versatile design allows wrenches to be used with or without handles.

FEATURES

- Provide safe alternative to striking wrenches in confined spaces and on applications that prohibit sparking.
- Ideal for Oil and Gas Industries.
- Offset box wrench head offers access to recessed fasteners and keeps hands clear of obstructions.
- Ergonomic design allows wrenches to be used conventionally without the handle.
- The handle can be attached to provide increased leverage for final tightening.
- Bar Stop on the wrench shaft helps to align locking button with handle hole.
- Comprehensive selection of pull wrenches covers a wide range of the most popular sizes.
- Made in the USA.

PLEASE NOTE:

24" Handle works with sizes: 1-1/16" - 1-5/8"

36" Handle works with sizes: 1-11/16" - 3-1/8"

24" HANDLE

PRODUCT #	OVERALL LENGTH	WEIGHT (LBS)
J26HAN24	24"	2.60

24" WRENCHES

PRODUCT #	SIZE	OUTSIDE HEAD WIDTH	HEAD THICKNESS	OVERALL LENGTH	WEIGHT (LBS)
J2617PW	1-1/16"	1-11/16"	5/8"	10-37/64"	1.80
J2618PW	1-1/8"	1-15/16"	3/4"	10-11/16"	2.10
J2619PW	1-3/16"	1-15/16"	3/4"	10-11/16"	2.10
J2620PW	1-1/4"	1-15/16"	3/4"	10-11/16"	2.10
J2621PW	1-5/16"	2-3/16"	7/8"	10-13/16"	2.30
J2622PW	1-3/8"	2-3/16"	7/8"	10-13/16"	2.13
J2623PW	1-7/16"	2-3/16"	7/8"	10-13/16"	2.30
J2624PW	1-1/2"	2-7/16"	1"	10-15/16"	2.40
J2626PW	1-5/8"	2-7/16"	1"	10-15/16"	2.44

J26HAN36

J26HAN24

Detent Pin

Bar Stop

J2617PW

J2617PW & J26HAN24

36" HANDLE

PRODUCT #	OVERALL LENGTH	WEIGHT (LBS)
J26HAN36	36"	8.00

36" WRENCHES

PRODUCT #	SIZE	OUTSIDE HEAD WIDTH	HEAD THICKNESS	OVERALL LENGTH	WEIGHT (LBS)
J2627PW	1-11/16"	2-11/16"	1-1/8"	13-9/32"	4.17
J2628PW	1-3/4"	2-11/16"	1-1/8"	13-9/32"	4.17
J2629PW	1-13/16"	2-11/16"	1-1/8"	13-3/8"	4.27
J2630PW	1-7/8"	2-15/16"	1-1/4"	13-3/8"	4.27
J2631PW	1-15/16"	2-15/16"	1-1/4"	13-1/2"	4.80
J2632PW	2"	2-15/16"	1-1/4"	13-1/2"	4.80
J2634PW	2-1/8"	3-3/16"	1-5/16"	13-11/16"	5.25
J2635PW	2-3/16"	3-3/16"	1-5/16"	13-11/16"	5.25
J2636PW	2-1/4"	3-7/16"	1-7/16"	13-11/16"	5.25
J2637PW	2-5/16"	3-7/16"	1-7/16"	13-49/64"	5.55
J2638PW	2-3/8"	3-7/16"	1-7/16"	13-49/64"	5.54
J2640PW	2-1/2"	3-15/16"	1-5/8"	13-57/64"	6.25
J2641PW	2-9/16"	3-15/16"	1-5/8"	13-57/64"	6.25
J2642PW	2-5/8"	3-15/16"	1-5/8"	13-57/64"	6.30
J2644PW	2-3/4"	3-15/16"	1-5/8"	14-19/64"	7.12
J2646PW	2-7/8"	4-7/16"	1-3/4"	14-5/32"	7.75
J2647PW	2-15/16"	4-7/16"	1-3/4"	14-5/32"	7.75
J2648PW	3"	4-7/16"	1-3/4"	14-5/32"	7.80
J2650PW	3-1/8"	4-7/16"	1-3/4"	14-19/64"	9.13



WARNING: WORK SAFELY WITH TOOLS. WEAR SAFETY GOGGLES.

©2014 Stanley Black & Decker, Inc. • 2195 East View Parkway, Suite 103, Conyers, GA 30013

1.800.800.TOOL • Fax: 1.770.648.9108 • protoindustrial.com