

Handley

INDUSTRIES

Lo-Sheen Urethane TIMBER & CORK FINISH

Description

For protecting and beautifying interior timber and cork floors. Handley Urethane is a one can polyurethane which cures by absorbing moisture out of the atmosphere to form a tough resilient coating which has excellent abrasion and chemical resistance.

Urethane Features

- One can – no mixing required
- Flexible coating
- Resilient, lasts for years
- Non slip surface
- Can be applied with a brush or roller
- Hard wearing, scratch resistant
- Heat and chemical resistant
- Available in gloss, satin or lo-sheen
- Excellent coverage
- Low maintenance

Coverage

8 – 10 sq mtrs/ltr approximately.

Caring For Your Urethane Floor

As complete curing of a Urethane floor takes a full 7 days, care must be exercised during this time. Avoid dragging furniture etc. over the surface. Use protective mats in traffic areas. To extend the life of the floor, mats should be used in doorways in order to remove dirt and grit from feet. Protective pads should be used on the legs of furniture. The floor should be swept frequently and washed with 3 litres of hot water and 1/4 cup of Methylated Spirits.

Application

Please refer to directions on the can label. Handley Industries recommend a minimum of three coats applied liberally with either a brush or roller. Clean equipment immediately after use with Handley Brush Cleaner.

...2/...

HANDLEY INDUSTRIES LTD

77 Hillside Road, Glenfield, Auckland, New Zealand.

P.O. Box 36-025, Northcote. Telephone 0-9-444 4558. Fax 0-9-444 2761

Manufacturers and distributors to the flooring industry