

Handley

INDUSTRIES

Ultrathane NON YELLOWING TIMBER & CORK FINISH

Description

Ultrathane is an aliphatic one can moisture curing polyurethane. It is resistant to yellowing and has UV light absorbers incorporated to assist in protecting substrates from the effects of sunlight. These features make Ultrathane ideal for use on light coloured wood floors and in conjunction with Handley Colour Blockout to avoid colour distortion of the coating after exposure to UV light. Floors coated with standard aromatic polyurethanes will very quickly discolour as a result of exposure to UV light. Ultrathane will remain crystal clear thus helping to retain the original natural timber or cork colour and avoiding unsightly furniture and mat outlines on your floor.

Ultrathane Features

- Non Yellowing
- One can – no mixing required
- Flexible coating
- Resilient, lasts for years
- Non slip surface
- Can be applied with a brush or roller
- Hard wearing, scratch resistant
- Heat and chemical resistant
- Excellent coverage
- Keeps Surface Appearance Light
- Low maintenance

Coverage

6 – 8 sq mtrs/ltr approximately.

Caring For Your Ultrathane Floor

As complete curing of an Ultrathane floor takes a full 7 days, care must be exercised during this time. Avoid dragging furniture etc. over the surface. Use protective mats in traffic areas. To extend the life of the floor, mats should be used in doorways in order to remove dirt and grit from feet. Protective pads should be used on the legs of furniture. The floor should be swept frequently and washed with 3 litres of hot water and 1/4 cup of Methylated Spirits.

...2/...

HANDLEY INDUSTRIES LTD

77 Hillside Road, Glenfield, Auckland, New Zealand.

P.O. Box 36-025, Northcote. Telephone 0-9-444 4558. Fax 0-9-444 2761

Manufacturers and distributors to the flooring industry