1/2 HP AC CHAIN DRIVE WI-FI GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS.

SEGURE

SECURITY+ 2.0° SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MyQ TECHNOLOGY ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee.

**Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV® with tvOSTM 10.0 or later or an iPad® with iOS-10.0 or later set up as a home hub.

PRODUCT GUIDE 8365W-267 1/2 HP AC CHAIN DRIVE WI-FI GARAGE DOOR OPENER

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®

Turns on garage door opener lights from inside the garage.



(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ Light Accessories each.



WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



POWERFUL ADD-ONS:

MyQ HOME BRIDGE

Adds Apple® HomeKit™ compatibility and Sirio voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.**



Warks with Apple HomeKit

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



REMOTE LIGHT SWITCH

Replaces an existing wall switch to enable home lighting control with a garage remote or smartphone.



DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.





GARAGE DOOR OPENER

MASTERFUL ENGINEERING.

MOTOR



- -1/2 Horsepower AC
- -1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- -120V AC
- -60 Hz Voltage
- -2.7A Current Rating
- -III Listed
- -4' Power Cord (3-Prong)

MECHANICS



- Steel Chassis, T-Rail and Trolley
- Full Chain Drive Mechanism (16:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and **Environmental Conditions**
- Electronic Limits for Easy Setup
- AC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

711 Per second to move upward

SPEED

7 11

Per second to move downward

STANDARD SPECS.

RADIO CONTROLS

Operating Range: ~2001

Operating Temperature: -35°F to 150°F

SECURITY+ 2.0®

(2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)

- -Remote Controls: 310, 315 and 390 MHz Tri-Band*
- Keyless Entry: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding
- *Tri-band on Security+ 2.0 coding only.

ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

MvQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LIGHTING





- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delay
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)







CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8365W)
- Multi-Function Control Panel (882LMW)
- -(2) 3-Button Remote Controls (893LM)
- Wireless Keyless Entry (877LM)
- -The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop

- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices

*WARNING: to reduce the risk of injury to persons-ONLY enable Timer-to-Close and MyQ remote operation features when opener is installed on a sectional door.

ALARM COM is a registered service mark of Alarm com-

Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc. Clare Controls is a registered trademark of Clare Controls, Inc.

Google, Google Home, Google Assistant and other related marks and logos are trademarks of Google Inc. Nest is a trademark of Nest Labs, Inc.

XFINITY Home and the XFINITY Home design logo are trademarks or service marks of Comcast Corporation UL and the UL logo are trademarks of UL LLC @ 2018 All Rights Reserved.

Wi-Fi® is a registered trademark of Wi-Fi Alliance HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation LMGDENPG8365267 3/18

ELECTRIC GARAGE DOOR SALES, INC.

1128 Pennsylvania Ave. Monaca. PA 15061 (724)774-3200 - PAO42047



