

Duct connection Low & Middle Static Pressure Type

- > Compact Design
- > Quiet Operation
- > Freedom of Layout

			1 PK	1.5 PK	2 PK	2.5 PK	3 PK	3 PK	3.5 PK
Model	Indoor		FDBNQ09MV14	FDBNQ13MV14	FDBNQ18MV14	FDBNQ21MV14	FDMNQ26MV14	FDMNQ26MV14	FDMNQ30MV14
	Outdoor		RNQ09MV14	RNQ13MV14	RNQ18MV14	RNQ21MV14	RNQ26MV14	RNQ26MY14	RNQ30MY14
Catu daya			V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz					Y: 380-415V, 3Ø, 50Hz	
Kapasitas	Btu/h		9.200	13.000	17.700	21.000	26.000	26.000	30.000
	kW		2.7	3.8	5.2	6.2	7.6	7.6	8.8
Daya Listrik	KW		0.86	1.28	2.06	2.38	2.62	2.62	3.03
COP	W/W		3.14	2.97	2.52	2.60	2.90	2.9	2.9
Indoor	Dimensi (HxWxD)	mm	260x900x580			260x1,300x580	305x1,350x680	305x1,550x680	
	Berat Mesin	kg	25			32	43		52
Outdoor	Dimensi (HxWxD)	mm	550x765x285		595x845x300		735x825x300		990x940x320
	Berat Mesin	kg	35	36	40	49	56		74
Ukuran Pipa	Cair	inch	1/4				3/8		
	Gas	inch	3/8	1/2		5/8	5/8		
Maksimal Pipa	Panjang	m	30				30		50
	Tinggi	m	10		15		20		30

			4 PK	5 PK	6 PK
Model	Indoor		FDMNQ36MV14	FDMNQ42MV14	FDMNQ48MV14
	Outdoor		RNQ36MY14	RNQ42MY14	RNQ48MY14
Catu daya			Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h		36.000	42.000	48.000
	kW		10.6	12.3	14.1
Daya Listrik	KW		3.53	4.49	5.56
COP	W/W		3.00	2.74	2.54
Indoor	Dimensi (HxWxD)	mm	305x1,550x680		
	Berat Mesin	kg	52		
Outdoor	Dimensi (HxWxD)	mm	1,345x900x320		
	Berat Mesin	kg	103	107	111
Ukuran Pipa	Cair	inch	3/8		
	Gas	inch	5/8		
Maksimal Pipa	Panjang	m	50		
	Tinggi	m	30		