

Floor Standing

- > Auto Swing Mode
- > Powerful Operation
- > Easy Maintenance
- > Two temperature sensors

		3 PK	3 PK	4 PK	5 PK	6 PK
Model	Indoor	FVRN71BXV14	FVRN71BXV14	FVRN100BXV14	FVRN125BXV14	FVRN140BXV14
	Outdoor	RR71CXV1A4	RR71CXY1A4	RR100DXY1A4	RR125DXY1A4	RR140DXY1A4
Catu daya		V: 220-240V, 1 ϕ , 50Hz / 220-230V, 1 ϕ , 60Hz			Y: 380-415V, 3 ϕ , 50Hz	
Kapasitas	Btu/h	29,000	28,000	36,000	42,000	55,000
	kW	8.49	8.21	10.6	12.31	16.12
Daya Listrik	KW	2.90	2.84	4	4.1	5.49
COP	W/W	2.93	2.89	2.97	3.00	2.94
Indoor	Dimensi (HxWxD)	mm 1,850x600x270		1,850x600x350	1,850x600x350	
	Berat Mesin	kg 42		45	48	51
Outdoor	Dimensi (HxWxD)	mm 753x 855x328		852x1,030x400	852x1,030x400	
	Berat Mesin	kg 57		95	95	105
Ukuran Pipa	Cair	inch 3/8			3/8	
	Gas	inch 5/8			5/8	3/4
Maksimal Pipa	Panjang	m 45			50	45
	Tinggi	m 25			30	25