

# Spesifikasi Multi-S 2 Connection

## Unit Indoor

Model name	CTKC15RVM4			CTKC20RVM4		
Catu Daya	1 phase, 220-240 V, 50 Hz / 1 phase, 220-230 V, 60 Hz					
Warna panel depan	Putih (N9.5)					
Rentang hembusan udara (Hz)	H/M/L/SL	m <sup>3</sup> /min		10.5 / 8.9 / 6.5 / 3.5		
Tingkat tekanan suara	H/L/SL	dB (A)		38/25/22		
Kecepatan kipas	5 langkah, senyap dan otomatis					
kontrol temperatur	Kontrol Mikroprosesor					
Dimensi	T x L x P	mm		285 x 770 x 223		
Berat mesin			kg			
			8			
Persambungan pipa	Liquid	Inch		1/4		
	Gas			3/8		
Insulasi panas	Untuk cair dan gas					

## Unit Outdoor

Nama Model	2MKC20VVM4			2MKC30QVM4		
Catu Daya	1 phase, 220-240 V, 50 Hz			1 phase, 220-240 V, 50 Hz / 1 phase, 220-230 V, 60 Hz		
Kapasitas maksimal koneksi Indoor unit	kW			3.0		
Warna unit	Putih Gading					
Tipe Kompresor	Tipe Hermetically sealed swing					
Tipe Refrigeran	R-32					
Tingkat tekanan suara	H/L	dB (A)		48/44		
Dimensi	H x W x D	mm		418 x 695 x 244		
Berat mesin			kg			
			22			
Panjang pipa maksimum			m		25 (total)	
					20 (Untuk setiap ruangan)	
Persambungan pipa	Liquid	Inch		1/4		
	Gas			3/8 x2		
Isian Refrigeran tambahan			g/m		20 (Jika lebih dari 20m)	
Perbedaan tinggi maksimum			m		15	

## 2 Koneksi 2MKC20VVM4 **NEW**

Unit Outdoor	Kombinasi unit indoor	Kapasitas rata-rata pada tiap unit (kW)		Total kapasitas (kW) Rated (Min. - Max.)	Total konsumsi daya (kW) Rated (Min. - Max.)	Total current (A) Rated (Min. - Max.)
		Room A	Room B			
2MKC20VVM4	15	1.5		1.5 (0,87-2,00)	0.40 (0,19-0,64)	2.5 (1,2-3,1)
	20	2		2 (0,87-2,40)	0.62 (0,19-0,76)	3.9 (1,2-3,6)
	15+15	1.0	1.00	2 (0,90-3,00)	0.55 (0,19-1,06)	3.5 (1,2-5,1)
	15+20	0.86	1.14	2 (0,90-3,00)	0.55 (0,19-1,06)	3.5 (1,2-5,1)

Note: Tidak bisa dikoneksikan hanya dengan 1 unit indoor

## 2 Koneksi 2MKC30QVM4

Unit Outdoor	Kombinasi unit indoor	Kapasitas rata-rata pada tiap unit (kW)		Total kapasitas (kW) Rated (Min. - Max.)	Total konsumsi daya (kW) Rated (Min. - Max.)	Total current (A) Rated (Min. - Max.)
		Room A	Room B			
2MKC30QVM4	15	1.5		1.5 (0,89-2,50)	0.35 (0,20-0,66)	1.7 (1,1-3,3)
	20	2		2 (0,89-3,00)	0.5 (0,20-0,85)	2.4 (1,1-4,0)
	15+15	1.5	1.5	3 (0,90-3,50)	0.69 (0,19-0,93)	3.3 (1,1-4,4)
	15+20	1.29	1.71	3 (0,90-3,81)	0.69 (0,19-1,03)	3.3 (1,1-4,7)

Note: Tidak bisa dikoneksikan hanya dengan 1 unit indoor