P.O. Box 640 1800 Springhead Ch. Rd. Willacoochee, Ga. 31650 912-534-6071 800-948-7870 912-534-6254(fax)

LM 150 lb Woven Stabilization Fabric

L&M 150# Woven Stabilization is a polypropylene fabric designed for ground cover. This engineered geo-textile is stabilized to resist degradation due to ultraviolet exposure. It is resistant to commonly encountered soil chemicals, mildew and insects, and is non-biodegradable. We wish to advise that **L&M 150# Woven Stabilization** meets the following minimum average roll values:

Property	Test	Minimum
	Method	Average
		Roll Value
		(English)
Weight		3 oz/sq.yd
Grab Tensile	ASTM-D-4632	150 lb(w)
		120 lb(f)
Grab	ASTM-D-4632	20%(w)
Elongation		15%(f)
Mullen Burst	ASTM-D-3786	300 psi
Puncture	ASTM-D-4833	84 lb
UV Resistance	ASTM-D-4355	70 % at 2500 hr
Permittivity	ASTM-D-4491	0.05 sec
Flow Rate	ASTM-D-4491	34 gal/min/ft ²

L&M Supply Co., Inc. provides the woven fabric indicated above. The values listed are a result of testing conducted by an independent testing laboratory. These test results are no more than one year old when presented to the authorizing agent.