



PYRAMID

Surface Mounted Over Mirror



Housing

Matte natural anodized, aluminum extrusion profile and stainless steel mounting accessories with plastic ceiling cup.

Optics

Opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L70B50 \geq 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Color

Matte natural anodized
White (RAL9016)

Type	Order Code	CCT (K)	lm	CRI	W	V/Hz	L1 (mm)	Weight (kg)
SP 0600 AYN	SPAYN.600.15.30	3000	1100	Ra>80	15	220-240 / 50-60	620	0,9
	SPAYN.600.15.40	4000	1150					
SP 0900 AYN	SPAYN.900.22.30	3000	1500	Ra>80	22		900	1,2
	SPAYN.900.22.40	4000	1750					
SP 1200 AYN	SPAYN.1200.28.30	3000	2050	Ra>80	28	220-240 / 50-60	1180	1,5
	SPAYN.1200.28.40	4000	2300					
SP 1500 AYN	SPAYN.1500.36.30	3000	2600	Ra>80	36		1460	1,7
	SPAYN.1500.36.40	4000	3100					

