

Discover the Duralite difference.


DURALITE

Series 400

Aluminum Replacement Window







Features:

- 2" Heavy duty frame with .050 wall thickness. (6063-T5 alloy)
- .062" wall thickness on sill.
- Sill has both a finned weatherstrip and a bulb vinyl creating a double seal.
- Sash jambs have continuous vinyl insert for smooth operation and a finned weatherstrip for minimum air infiltration.
- Interlocking center rails with finned weatherstrip for extra security and minimum air infiltration.
- Rigid vinyl glazing beads.
- · Will accept either a half or full screen.

Options:

- · Colors . . . : Mill finish, white, or bronze.
- Glass . . . : Clear or gray tinted in stock. (Specialty glass also available upon request)
- Lites : Multi-lites available upon request.
- Screen . . . : Standard fiberglass wire or "Sunscreen."
- Flanges . . . : Replacement (No flanges).
- Windows can be mulled together to accommodate larger openings.

Test Results:

A window 44" x 72" was tested at an independent laboratory and has proven to meet or exceed ANSI/AAMA specifications for air infiltration, water penetration, and structural integrity.

Replaces wood or aluminum windows, also some jalouses and casements.

Our performance pledge:

Every Duralite product is backed by our pledge of quality performance in material, workmanship and service after the sale.

Your satisfaction is our only measure of success.