



ALLIGATOR® SPIRAL LACE Fastener System

Low-Profile, Non-Metallic Splice

For applications where a mechanical belt fastener is desired for ease of belt installation or quicker belt cleaning, but for one reason or another a metallic fastener cannot be used, consider Alligator® Spiral Lace. Alligator Spiral Lace is a low-profile splice that is fabricated into the belt through a variety of splicing techniques. Depending on the installation method it can operate over pulley diameters as small as 13/32" (10 mm). It is available in white or blue polyester for applications demanding FDA-compliant materials, black polyester for general applications, or PEEK for high temperature applications.



Spiral Lace Applications

Alligator Spiral Lace is a non-metallic splice that is ideal for applications with metal detectors, food or pharmaceutical processing, x-ray equipment, or for applications with delicate product that is easily scratched that require non-marking/non-scratching splices.




Advantages of a Hinged Splice

Alligator® Spiral Lace, like other Flexco mechanical splices, is constructed of two fastened belt ends that are joined by a hinge pin. This hinged splice makes installation on the conveyor structure simple as the belt can be fed into proper location, the belt ends meshed together, and the connecting pin inserted. For belts requiring frequent removal, such as regular sanitation for food applications, the hinged splice can save hours of downtime with each cleaning.

www.flexco.com



Leader Pins Simplify Pin Insertion



Connecting pin installation can be difficult, given both the small diameter of the pin and the flexibility of the material. To ease and speed this process we offer Leader Pins, which attach a smaller diameter, rigid lead pin to the larger diameter, flexible connecting pin. The lead pin is easily fed through the splice, allowing the actual connecting pin to be pulled through. The use of Leader Pins often reduces pin insertion time by more than 75%.

ALLIGATOR® SPIRAL LACE Fastener System

Alligator® Spiral Lace Selection Chart

Fastener Size	Belt Thickness		Minimum Pulley/ Nose Bar		Maximum Operating Tension		Max. Operating Temperature		Approximate Pin Diameter	
	in.	mm	in.	mm	P.I.W.	kN/M	°F	°C	in.	mm
ASL50	1/16	1.6	13/32	10	50	8.7	320	160	.31	.8
ASL60/ASL160	1/2	2.4	1/2	13	50	8.7	320	160	.035	.9
ASL90/ASL190	19/32	3.2	5/8	15	50	8.7	320	160	.047	1.2
ASL80H	1/4	6.4	5/8	15	50	8.7	320	160	.047	1.2

Ordering Information - Alligator® Spiral Lace

Length		Ordering Number	Item Code	Length		Ordering Number	Item Code
Feet	Meters			Feet	Meters		
White - Single Web				Black - Single Web			
10	3	ASL50/3	19460				
10	3	ASL60/3	19461	10	3	ASLB60/3	19486
33	10	ASL60/10	19462				
100	30	ASL60/30	19463	100	30	ASLB60/30	05463
10	3	ASL90/3	19466	10	3	ASLB90/3	19485
33	10	ASL90/10	19467				
100	30	ASL90/30	19468	100	30	ASLB90/30	19491
10	3	ASL160/3	19483				
10	3	ASL190/3	19484				
White - Double Web				Black - Double Web			
10	3	ASL60D/3	19476				
33	10	ASL60D/10	19477				
100	30	ASL60D/30	19478				
10	3	ASL90D/3	19479	10	3	ASLB90D/3	19489
33	10	ASL90D/10	19480	33	10	ASLB90D/10	19480
100	30	ASL90D/30	19481	100	30	ASLB90D/30	19494
10	3	ASL100D/3	19488				
Tan - Double Web - High Heat				Blue – Single Web			
10	3	ASL80H/3	19470	10	3	ASLBLUE50/3	04416
				10	3	ASLBLUE60/3	04417
				10	3	ASLBLUE90/3	04418

Leader Pins (Note: Custom Lengths Available)

05200	POLY035X15FT-W/3FT	(15-foot pin with 3-foot leader)
05201	POLY047X15FT-W/3FT	(15-foot pin with 3-foot leader)

Replacement Hinge Pins - Coils

Feet	Meters	Ordering Number	Item Code
100	30	ASLHP60	19473
100	30	ASLHP90	19474
100	30	ASLHP80	19475

Authorized Distributor:



2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA
Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2008 Flexible Steel Lacing Company. Alligator® is a registered trademark. 08-13. For Reorder: X1278

