

GT600 Series

Commercial Grade Panels

The GT600 series of control panels host extensive features and are the ideal choice for commercial and institutional installations up to 136 zones. Hybrid wireless 868MHz capabilities allow additional flexibility with a complete range of wireless accessories. The GT600 series are G-Tag compliant providing a unique solution for meeting DD243 requirements.



GT601

- EN Grade 3, Grade 2 or BS settings selectable upon power up
- Up to 136 zones, 7 areas, 99 users and 752 event log
- Up to 60 ID zones with two ID+ expanders
- Metal casing
- Unique DD243 solution with G-Tag
- Complete remote diagnostics via GT remote software
- Hybrid wireless up to 16 wireless zones
- Up to 7 LCD keypads - 32 characters for simple operation and descriptions
- Plug-on STU board
- Code grouping enables several control areas
- Resettable fuses and improved monitoring for higher reliability

GT600

- EN Grade 2 or BS settings selectable upon power up
- Up to 40 zones, 3 areas, 31 users and 500 event log
- Up to 30 ID zones with ID+ expander
- Polycarbonate casing
- Other features as GT601



G-Tag

G-Tag is a unique, simple and inexpensive solution for setting/unsetting the panel with a proximity tag, meeting DD243 requirements. Together with Micro Maglock and Z bracket it complies with DD243 requirements for single room applications.

Specifications

| | GT601 | GT600 |
|-------------------------|--------------------------------|-------------------------------|
| Security Grade | EN Grade 3 or Grade 2 or BS | EN Grade 2 or BS |
| End Station housing | Metal | Polycarbonate |
| Programmable Zones | 136 | 40 |
| Zone type options | 14 | 14 |
| Onboard zones | 8 | 8 |
| Wired zone expanders | 16 x 8 zones | 4 x 8 zones |
| Wireless zone expanders | 2 X 8 zones (up to 16 zones) | 2 X 8 zones (up to 16 zones) |
| ID expansion | 2 X ID cards = 60 ID zones | 1 X ID card = 30 ID zones |
| Areas | 7 | 3 |
| Part sets | 2 on all areas | 2 on all areas |
| Number of keypads | 7 | 7 |
| Keypad Type | LCD | LCD |
| Prox compatible | Yes | Yes |
| Keypad zones | 2 per keypad | 2 per keypad |
| PA separate on keypad | Yes | Yes |
| Alert keys on keypad | 1&3 7&9 | 1&3 7&9 |
| Speaker output | Yes | Yes |
| Programmable bell ring | Yes | Yes |
| Digi compatible | Built-in | Built-in |
| Digi formats | FF/SIA/Contact ID | FF/SIA/Contact ID |
| Vocom | Built-in | Built-in |
| Resettable fuses | Aux/Bell/Keypad/Comms/Battery | Aux/Bell/Keypad/Comms/Battery |
| Keyswitch option | Via Zone | Via Zone |
| PSU | 2 Amp | 1.2 amp |
| Strobe confirmation | Yes | Yes |
| Upload download | Yes | Yes |
| Wiring formats | 2 Wire/4 Wire/EOL | 2 Wire/4 Wire/EOL |
| Onboard Outputs | 2 | 2 |
| Additional output cards | 4 cards x 4 outputs each | 4 cards x 4 outputs each |
| STU compatible | Via STU adaptor | Via STU adaptor |
| User codes | 99 | 31 |
| Event Log | 752 | 500 |
| Modem Log | 128 | 64 |
| Max Loop Resistance | 2K (without EOL) | 2K (without EOL) |
| Battery Sizes | 1.2Ah/2.0Ah/3.0Ah/7.0Ah/17.0Ah | 1.2Ah/3.0Ah/7.0Ah |
| Quiescent current | 150mA @ 12v dc | 150mA @ 12v dc |
| Dimensions | H420 x W380 x D96mm | H235 x W270 x D65mm |

Specifications are subject to change without prior notice

Wireless Accessories

- Wireless PIR & PIR Pet with look down zones
- Wireless outdoor motion detector
- Wireless outdoor barrier beams
- Door/Window Contacts
- Shock with Contact detectors
- Glass-break detector
- Smoke detector
- Flood detector
- Gas detector
- CO detector
- Wristband panic transmitter
- 2 and 4 button keyfobs

Remote Servicing

- Upload/Download compatibility allows installation engineer full remote management
- Engineer can remotely check all components of the External Sounders to guarantee continued operation
- Full system can be tested by the master user for complete peace of mind

Ordering Information

| P/N | Description |
|----------|------------------------------|
| 01600P | GT600 polycarbonate panel |
| 01601PCB | GT601 PCB only |
| RP128B26 | GT601 / ProSYS metal housing |

Please contact us for additional ordering information and kit options

PD6662, EN50131-1 Grade 2 or 3, DD243 Compliant



Creating Security Solutions.
With Care.

riscogroup.co.uk

RISCO Group UK, Tel: 0161 655 5500, Fax: 0161 655 5501, Email: sales@riscogroup.co.uk