



AKUSTIKDUG 125

Type	Weight (g/m <sup>2</sup> )							Thickness (mm)	Trapez tear strength (N)		Breaking strength (N)		Elongation at break (%)	
		Light beige	Sand	Brown	Grey	Anthracite	Black	EN ISO 9073-2	EN ISO 9073-4	EN ISO 9073-18	EN ISO 9073-18	MD	OD	
125WL BH-1	125	3255	3210	3154	3062		3105	1.0	MD 140	OD 100	MD 240	OD 300	MD 45	OD 45

WL: Thermally bonded on both sides.

BH-1: One side with textile-like surface, other thermally bonded.

<b>Roll width tolerance:</b>	+/- 1 cm
<b>Cut sheets width tolerance:</b>	+/- 1 cm
<b>Widths:</b>	According to agreement
<b>Standard roll length:</b>	100 lin. mts
<b>Standard fastening on tubes:</b>	Staples

<b>Standard packaging:</b>	HDPE plastic
<b>Fibre composition:</b>	Polypropylene or blends of polypropylene and polyester
<b>Special colours/products:</b>	By special agreement upon orders of min. 30,000 m <sup>2</sup>
<b>Embossed pattern:</b>	Exclusive embossed pattern is available on BH-1 surfaces for types of min. 125 g/m <sup>2</sup>
<b>Cut sheets:</b>	Fibertex can be delivered in rectangular cut sheets in agreed dimensions
<b>Certificates:</b>	Oekotex Standard 100, ISO 9001, ISO 14001
<b>Material safety data sheet (MSDS):</b>	Available on request