

SUV/4WD/ Light Commercial







SUV/4WD/Light Commercial

Exide has developed a range of SUV, 4WD and light commercial batteries that suits every application and any customer budget. The range has been designed to provide genuine suitability for Australasia's harsh conditions when it comes to starting the large urban SUV, dual-purpose use for the tough rugged 4WD or strong cranking and durable hard working for light commercial fleets.

Technology Design

Exide Batteries has a commitment to "Power the Future" through the delivery of Enhanced performance, Extreme product life and Ultimate value to its customers.

Modern motor vehicles demand a significant increase in electrical supply, compared to previous generations of passenger vehicle technology. Along with the growing desire of consumers to explore the rugged and remote areas of the region the emphasis on product reliability is paramount. With this in mind Exide has developed batteries that provide a totally balanced performance philosophy. As part of the approach the cold cranking amps (CCA), reserved capacity (RC) and amp hours (AH) ratings have all been considered equally important to meet modern motor vehicle requirements and provide total battery performance.

The addition of Ap9 technology to the Exide range of products helps support the mechanical properties of rolled expanded grids, whereas the traditional silver additive has proven to have no impact. In extreme conditions, grid corrosion is limited by the addition of Ap9 and by a low calcium content. Additionally, when batteries endure long term storage and overcharging at high temperatures, battery life is increased with the addition of Ap9 no matter what the technology. Ap9 improves the battery recharge ability after

a discharge.

Exide's Extreme range, has been further enhanced with a new technology additive we call 2xT. The 2xT additive is combined with other active material components to achieve the necessary formulation to improve durability and reliability. 2xT technology in the Extreme range, will deliver longer life, hence the backing of an extended warranty. This is the top consideration of consumers when purchasing a battery.

This comprehensive range provides the owner with choice of technology of a maintainable version, sealed maintenance free or AGM, with a variety of budget levels and quality and warranty options. So when you need your workhorse on the road, trust Exide.



Economy Range

Feature

- Maintainable product technology
- Reliable starting power
- Up to 18 month warranty available
- Integrated carry handle

Benefit

- Allows for DIY maintenance
- Reliability in product performance
- Provides peace of mind
- Allows for easy installation and handling



Endurance Range


Feature

The choice of two technologies


- 1. Maintainable product technology
- 2. Sealed maintenance free product technology
- Meets original equipment specifications
- Ap9 Additive
- Total balanced performance
- Up to 30 month warranty available
- Integrated carry handle

Benefit

- · Choice for the consumer
- Genuine match for the vehicle technology
- Safe and no maintenance required
- Provides high performance in your vehicle
- Provides longer battery life
- Durability under all conditions
- Provides increased value and peace of mind
- Allows for easy installation and handling







Extreme Range

Feature


The choice of three technologies

- 1. Maintainable product technology
- 2. Sealed maintenance free product technology
- 3. AGM Sealed maintenance free
- Glass Matt Separators
- Exceeds original equipment specifications
- Ap9 Additive
- 2XT additive
- Total balanced performance
- Up to 42 month warranty available
- Integrated carry handle

Benefit

- · Choice for the consumer
- Allows for DIY maintenance
- No maintenance required
- For your specialised and premium applications
- Enhanced vibration resistance
- Designed to outperform original equipment
- Provides longer battery life
- Increased performance and life expectancy
- Extreme durability under all conditions
- · Provides increased value and peace of mind
- Allows for easy installation and handling





SUV/4WD/Light Commercial

						/42/				_			
Product Code	New Bar Code	Volts	Technology	Length	Width	Height	CCA	RC	АН	Vent	Ledge	Post	Assembly
EXTREME - TIER 3													
XN50ZZLMF	9313122901201	12	SMF Cal/Cal	259	173	223	720	150	85	TS	SL	SAE	C (+R)
XN50ZZMF	9313122901218	12	SMF Cal/Cal	259	173	223	720	150	85	TS	SL	SAE	D (+L)
XN70ZZLMF	9313122901225	12	SMF Cal/Cal	305	173	224	810	185	95	TS	SL	SAE	C (+R)
XN70ZZMF	9313122901232	12	SMF Cal/Cal	305	173	224	810	185	95	TS	SL	SAE	D (+L)
X66HAGM	9313122900990	12	AGM Starting	276	175	189	760	130	70	TS	NL	SAE	C (+R)
XN50AGM	9313122901287	12	AGM Starting	260	174	222	700	160	92	TS	NL	Stud Thread	D (+L)
XN70AGM	9313122901294	12	AGM Starting	304	173	225	765	200	110	TS	NL	Stud Thread	D (+L)
XN50EX	9313122901249	12	Hybrid Maint	259	173	223	620	150	80	СР	NL	SAE	D (+L)
XN50EXL	9313122901256	12	Hybrid Maint	259	173	223	620	150	80	СР	NL	SAE	C (+R)
XN70EX	9313122901263	12	Hybrid Maint	305	173	224	720	180	95	СР	NL	SAE	D (+L)
XN70EXL	9313122901270	12	Hybrid Maint	305	173	224	720	180	95	СР	NL	SAE	C (+R)
ENDURANCE - TIER 2													
N50ZZ	9313122901164	12	Cal/Cal Maint	259	173	223	620	140	70	СР	NL	SAE	D (+L)
N50ZZL	9313122901171	12	Cal/Cal Maint	259	173	223	620	140	70	СР	NL	SAE	C (+R)
N70ZZ	9313122901188	12	Cal/Cal Maint	305	173	224	680	160	75	CP	NL	SAE	D (+L)
N70ZZL	9313122901195	12	Cal/Cal Maint	305	173	224	680	160	75	СР	NL	SAE	C (+R)
N50ZZLMF	9313122901829	12	SMF Cal/Cal	259	173	223	620	140	70	TS	SL	SAE	C (+R)
N50ZZMF	9313122901836	12	SMF Cal/Cal	259	173	223	620	140	70	TS	SL	SAE	D (+L)
N70ZZLMF	9313122901843	12	SMF Cal/Cal	305	173	224	750	170	90	TS	SL	SAE	C (+R)
N70ZZMF	9313122901850	12	SMF Cal/Cal	305	173	224	750	170	90	TS	SL	SAE	D (+L)
ECONOMY - TIER 1											525		
LMN50ZZ	9313122901126	12	Cal/Cal Maint	259	173	223	450	95	50	СР	NL	SAE	D (+L)
LM50ZZL	9313122901133	12	Cal/Cal Maint	259	173	223	450	95	50	СР	NL	SAE	C (+R)
LMN70ZZ	9313122901140	12	Cal/Cal Maint	305	173	224	590	110	55	СР	NL	SAE	D (+L)
LMN70ZZL	9313122901157	12	Cal/Cal Maint	305	173	224	590	110	55	СР	NL	SAE	C (+R)
				40	-0	-0-	0.	0	(O)	95	90	-0-0	HOH

For more information contact: