



Bobcat®

Bobcat 418 Compact Excavator

The NEW 418 ZTS (Zero Tail Swing) excavator is ultra-compact, powerful and comfortable for operating with confidence in restricted space.



SPECIFICATIONS

Tail Swing Type	Zero Tail Swing
Weight	1176 kg
Dig Depth	1820 mm
Reach (at ground level)	3093 mm
Dump Height Clearance	1817 mm
Width Retracted / Expanded	710 - 1100 mm
Cab Height	2209 mm
Performance	
Arm Breakout Force	5550 N
Bucket Breakout Force	8294 N
Rated Lift Capacity	
Travel Speed Low Range	2.1 km/hr
Travel Speed High Range	3.1 km/hr
Engine	
Horsepower	7.4 kW (9.9 hp)
Engine Type	Diesel
Fuel Tank Capacity	16 L
Hydraulics	
Hydraulic Pump	Gear
Machine Options	
Retractable Undercarriage	Std
In-Cab Pattern Selector	Std
Features for Attachments	
Auxillary Hydraulics	Std
Auxillary Hydraulic Flow	20 L/min
Auxillary Hydraulic Pressure	190 bar (2.756 psi)



Bobcat®

Bobcat 323 Compact Excavator

A proven compact excavator with big features and performance for working in tight spaces.



SPECIFICATIONS

Weight	1658 kg
Dig Depth	2300 mm
Reach (at ground level)	3912 mm
Dump Height Clearance	2547 mm
Width Retracted / Expanded	980-1360 mm
Cab Height	2202 mm
Performance	
Arm Breakout Force	8879 N
Bucket Breakout Force	16685 N
Rated Lift Capacity	290 kg
Travel Speed Low Range	2.3 km/hr
Travel Speed High Range	3.8 km/hr
Engine	
Model	Kubota D722-E2B
Engine Type	Diesel
Fuel Tank Capacity	27.5
Hydraulics	
Hydraulic Pump	Piston
Load Sensing Pump	Std
Machine Options	
Cab With Heat	Opt
Retractable Undercarriage	Std
In-Cab Pattern Selector	Std
Steel Tracks	Opt
Features for Attachments	
Auxillary Hydraulics	Std
Auxillary Hydraulic Flow	30 L/min
Auxillary Hydraulic Pressure	186 bar (2.700 psi)