

Valvola di ritegno a battente PN16

Swing check valve PN16

Clapet anti-retour à simple battant PN16

Válvula de retención oscilante PN16



DESCRIPTION

1. Working temperature: Brass seal ring $\leq 200^{\circ}\text{C}$
Rubber seal ring $\leq 80^{\circ}\text{C}$
2. Flange dimensions: DIN2533
3. Face to face dimensions: DIN 3202 F6
- ☆ 4. If special request, the valve can be with external Lever and counter Weight(L.W.)
- ☆ 5. DN450 & larger size are only ductile iron body & bonnet
- ☆ 6. DN700 & larger size are with 2 discs & doors

MATERIALS LIST

PART	MATERIAL
BODY & BONNET	CAST IRON
SEAT	BRASS
DISC	C.I. W/BRASS or RUBBER RING
HANGER	DUCTILE IRON
HANGER PIN	CARBON STEEL/SS

DIMENSIONS(mm)

DN	L	D	D1	D2	b	f	Z-d	H
40	180	150	110	88	18	3	4-19	114
50	200	165	125	102	20	3	4-19	127
65	240	185	145	122	20	3	4-19	137
80	260	200	160	138	22	3	8-19	150
100	300	220	180	158	22	3	8-19	164
125	350	250	210	184	24	3	8-19	185
150	400	285	240	212	24	3	8-19	205
200	500	340	295	268	26	3	12-28	249
250	600	405	355	320	28	3	12-28	305
300	700	460	410	370	28	4	12-28	333
350	800	520	470	430	30	4	16-28	378
400	900	580	525	490	28	4	16-30	405
450	1000	640	585	550	30	4	20-30	512
500	1100	715	650	610	31.5	4	20-33	525
600	1300	840	770	725	36	5	20-37	608
700	1500	910	840	793	39.5	5	24-37	/
800	1700	1025	950	900	43	5	24-40	/
900	1900	1125	1050	1000	46.5	5	28-40	/
1000	2100	1255	1170	1115	50	5	28-43	/

