

Flange Filettate EN 1092-1 13B PN16

Threaded flanges to EN 1092-1 13B PN16
Brides filetées à EN 1092-1 13B PN16
Bridas roscadas según EN 1092-1 13B PN16



Diametro nominale	Flangia						Collanino	Gradino		Foratura			Peso di una flangia (7,85 Kg/dm3)
	d1	Filetto	k	D	b	h1	d3	d4	f	d2	Vite	Fori	KG
15	21,3	R 1/2"	65	95	16	22	35,0	45,0	2,0	14	M12	4	0,722
20	26,9	R 3/4"	75	105	18	26	45,0	58,0	2,0	14	M12	4	1,040
25	33,7	R 1"	85	115	18	28	52,0	68,0	2,0	14	M12	4	1,250
32	42,4	R 1-1/4"	100	140	18	30	60,0	78,0	2,0	18	M16	4	1,810
40	48,3	R 1-1/2"	110	150	18	32	70,0	88,0	3,0	18	M16	4	2,060
50	60,3	R 2"	125	165	18	28	84,0	102,0	3,0	18	M16	4	2,390
65	76,1	R 2-1/2"	145	185	18	32	104,0	122,0	3,0	18	M16	4	2,970
80	88,9	R 3"	160	200	20	34	118,0	138,0	3,0	18	M16	8	3,780
100	114,3	R 4"	180	220	20	40	140,0	158,0	3,0	18	M16	8	4,380
125	139,7	R 5"	210	250	22	44	168,0	188,0	3,0	18	M16	8	6,070
150	168,3	R 6"	240	285	22	44	195,0	212,0	3,0	22	M20	8	7,240

