

IC Implementation in US

ICDM / Veta WORKSHOP

April 16, 2018
Ohio DOT Computer Lab
1606 W. Broad St., Columbus, OH 43223

Michael M. Arasteh
Pavement and Materials Engineer
FHWA, OTS, Baltimore Resource Center

Importance of Compaction



A BRIEF HISTORY OF IC IN US



TPF-5(128) study

EDC IC Support ?????

IC & Asphalt Density Study

IC Retrofit Study

TPF-5(334) study

IC DEFINITION

Global Positioning System GPS BCM 05 positioning

Onboard Report System

Temperature Sensors Continuous Measurement System

Courtesy of Bomag



DQQ and Radio




Courtesy of Topcon/RDO

Infrared

Sensor

US IC NATIONAL IMPLEMENTATION



FHWA TECH BRIEF

TECHNICAL BRIEF

U.S. Department of Transportation

DEFINITION OF PRE-MAPPING

Pre-mapping is defined as measuring base line stiffness of existing support materials using an IC roller. The IC measurement value (ICMV) system is used to estimate stiffness based on acceleration signals caused by roller drum.

The pre-mapping ICMV and its measurement depths-typically 3 to 5 feet-depend on the roller type, weight, drum dimension vibrate frequency and amplitude, speed, direction of travel, and the stiffness of the mapped

Candidate support materials for pre-mappin include granular full depth reclamation materials or their equivalent. Typically, the I machines used to pre-map existing pavient subsurface structural support are the same those used to construct subsequent layers. I orde to pre-early double jump during premapping, the IC machine settings including speed, vibration frequency, and amplitude.)

With IC, teams can identify soft spots during construction and make corrective actions. If the soft spot was caused by excess moisture in the soft, the materials can be disked and aired out before recompaction. If the soft spot occurred due to insufficient moisture, water can be added to the materials before

INTELLIGENT COMPACTION FOR PRE-MAPPING

TECHNICAL BRIEF

TECHNICAL BRIEF



U.S. Department of Transportation
Federal Highway Administration

A double dram IC roller pre-mapping t Route 4, MN under the TPF-FH

BACKGROUND

Intelligent compaction (IC) is an equipment-based technology to is wibratory rollers are equipped with a high precision global position sensors, an accelerometer-based measurement system, and an or used to improve compaction control for various pavement materisubbase materials, and apphalt materials.

Pre-mapping originated as a research activity on the 2008 FHWA team used So like double-drum IC roller to measure the baseline o materials at low wheaton frequency and amplitude prior to the asp during poining, construction telffic caused the explaid sayer to fall purter team later related they could identify the coff sport in the production your recognizes the value of pre-mapping the data collect fearm identify potential out posts the fore pavement faller.

As of today, several state department of transportation (DOT) IC sp option or requirement. This techbrief intends to provide the best a pre-mapping in order to clarify its advantages and limitations.

WHAT IS VETA?

Veta is a map-based software tool for viewing, and analyzing geospatial data. Currently. Veta can import data from various IC machines and PMTP scanners to perform editing, filtering, spot test correlation, and statistical analysis as a post-processing tool.

One of the salient features of Veta is to view IC and PMTP data as color-coded maps on top of geographical road or aerial maps to facilitate quantitative interpretation.

Key examples are to evaluate consistency of rolling patterns, to identify cold blobs or streaks of temperature segregation, etc. Veta can allow users to select any specific passes to be viewed, including the last pass or final

The FHWA Veta Software was developed with funding from the FHWA. MnDOT, and the TPF-5(334) pooled fund study.

QUALITY ASSURANCE STATEMENT

he Federal Highway Administration (FHVMA) provides light-qualify lindomation to serve downment, industry, and the public in a manner that promotes sublic understanding. Standards and policies are used or serue and manning: the quality, objectivity, utility, and integrity of its information. FHVMA periodically evident quality issues and adjusts its programs and recomment for more continuous quality increases.

COLOR-CODED IC MAPS CONSISTENT VISUAL DATA INTERPRETATION

TECHNICAL BRIEF

SUMMER 2017



screen shot of Veta — a map-based software tool for viewing and analyzing geospatial d

BACKGROUND

Intelligent compaction (IC) and paver-mounted thermal profiler (PMTP) systems have been gaining popularity across the USA in the past 10 years to improve compaction quality and detect temperature sag registion behind pavers. On IC and PMTP systems, color-coded maps from their orboard displays are used extensively for monitoring and visual inspection of collected field data and machine operation.

IC and BMTP systems gather a termendous amount of coregion geospatial data that poors challenges for data management, analysis, and reporting. These issues have become the main hurdes dating implementation. To address the above issues, the Himmeotat Department of Transportation and the FHWA have funded the development of the Veta software tool for IC and PMTP data viewing and analysis. Currently, the Transportation Podel Furd (PTP) study. "IFF-9334 (Internement to the Irefliger Construction Data Management System (Veta) and Implementation is leading the effort for enhancing and maintaining Veta to foolitate the national (PMTP implementation).

This Tech Brief will provide guidelines for IC color-coded maps in order to ensure clear field inspection of IC maps and interpretation of IC results.

TECHNICAL BRIEF



U.S. Department of Transportation Federal Highway Administration

ELEMENTS OF IC SPECIFICATIONS

The common elements of IC specifications include the following:

- 1. IC System Requirements
- 2. Quality Control Plan
- 3. Training
- 4. Field Operation Requirements
- Data Requirements and Submission
- o. Preasures and Payment

QUALITY ASSURANCE STATEMENT

The Federal Highway Administration (PHWA) provides high-quality information to serve Government, industry, and the public in a manner that promotes public understanding. Standards and policies are used to remure and maintime the quality, objectivity, utility, and integrity of its information. FHWA periodically reviews quality tours and adjusts its programs and processes to ensure confinious quality improvement.

SPECIFICATION FOR INTELLIGENT COMPACTION

A REVIEW ON NATIONAL AND STATE SPECIFICATIONS

TECHNICAL BRIEF

SUMMER 2017

TECHNICAL BRIEF



U.S. Department of Transportation Federal Highway Administration

BACKGROUND

Adequate and uniform compaction of road materials, such as solis, aggregate bases, materials is one of the most important regainements in readey construction. It is for high quality of compaction to ensure long-lasting performance. Intelligent Comp modern what along violes equipped with an integrated measurement system, an orbosystem. Global Postioning Systems (Global Poste and regaing and optional feedback coninglementation stage to help improve compaction quality control. The FHVA and instancial Eg globe egoefficiations. An increasing number of state agencies have also do specifications. This Tech Brief will provide a review on those specifications an one conenhancements.



Poster and the second s

WHAT IS ICMV?

Intelligent Compaction Measurement Value (ICMV) is a generic term for accelerometer-based measurement of the compaction of the compaction of the compaction of the compaction of the acceleration signals that represent the rebound force from the compacted materials to the Collection of the acceleration of the compacted materials to the Collection of the

QUALITY ASSURANCE STATEMENT

The Federal Highway Administration (FHWA) provides figle-quality information to serve Government, including and the public in a manner that promotes public understanding Standards and policies are used to ensure and maximize the quality, objectivity, utility, and integriny of its information. FHWA periodically reviews quality issues and adjusts its programs and process to ensure ordination undillustrations and

INTELLIGENT COMPACTION MEASUREMENT VALUES (ICMV)

A ROAD MAP

TECHNICAL BRIEF

SUMMER 2017



BACKGROUND

Intelligent compaction (IC) is an equipment-based technology to improve quality control of propaction. IC vibratory rollers are equipped with a high precision global positioning optem (ICFS): infere of temperature sensors, an accidenmente-based measurement system, and an orboxed color-coded display. IC is used to improve compection control for visious perventer meterials including an appliant materials. The accidence are applicable of the control option of the control option of the control option of the control option option. The control option of the control option option of the control option of the control option option option option option of the control option opt

Intelligent Compaction Measurement Value (CMVI) is a genetic term for an acceleromate-based measurements system instrumented on vibrativey rollers as a key part of IC systems, ICMV are in different forms of members with various levels of correlation to compacted materials's mechanical and physical properties. The purpose of this document is to demystify ICMV by providing a comprehensive description on the mechanisms of ICMV and values levels of solutions as the road map for using ICMV towards compaction monitoring control and

FHWA APPLICATION NOTES

APPLICATION NOTES



U.S. Department of Transportation Federal Highway Administration

BACKGROUND

Because soils compaction is mosture dependent, construction teams find it difficult to ensure adequate compaction using traditional efforts based solely on roll-passes. To improve soils compaction, teams can use the advanced real-time monitoring offered by intelligent compaction (IC). ICtal all the guesswork out of compaction.

with in., teams can identify soft spots during construction and make corrective actions. If the soft spot was caused by excess moisture in the soil, the materials can be disked and aired out before recompaction. If the soft spot occurred due to insufficient moisture, water can be added to the materials before recompaction.

Traditional solis moisture-density tests have several drawbacks they are insensitive to in situ moisture content, they are limited to specific locations within the compacted area, and they provide only partial information about compaction progress. If clakes an innovative approach to measuring stiffness-related values by providing many types of information about the entire compacted area offering 100% coverage.

IC can disastically improve quality control and advance ingifare metation towards modulizabase di compaction acceptance. By highing construction teams achieve consistent and uniform soils embanisment and subbase compaction, implementing IC on a project car produce a superior platfor in for the patwerner layer placed above it. IC improves the entire readways constitution process. benefitting

INTELLIGENT COMPACTION FOR SOIL

APPLICATION NOTES: INTELLIGENT COMPACTION IMPLEMENTATION ON IOWA I-80/US 65 PROJECT

In 2013, Iowa DOT's I-80 and US 65 Interchange mainline and ramp widening project served as an intelligent compaction (IC) testing ground. The 2.5-mile construction project in Polk County near Altoona included more than 400,000 cubic yards (CY) of soil compaction.



IOWA I-80/US 65 PROJECT DESCRIPTION

The grading contractor provided the construction services for a field trial comparing Iowa DOT's Type A Compaction Specification with compaction results from an IC roller. The soils used for the project are glacial till and were placed in 8-inch lifts.

The Type A Compaction Specification requires a minimum of one roller pass per inch depth of each lift with a padfoot for theepsfoot) roller with pad projections of 6 ½ in thes or more. The material must be compacted until the roller is supported entirely on its feet, which is defined as when the tamping feet permetate no more than 3 inches into an 8-inch lift, or 33% of the depth of the layer being placed. The specification requires equality control (IGC) testing every 1,300 CY to evaluate the moisture content and in-place density using a nuclear density gauge (NDCs).

The project included the use of a patific of single drum roller weighing more than 12 tons (1) a Real Time Kinematic (RTK) Global Positioning System (GPS). It data flow protocol which identifies the data to be reported, data format for electronic submission, and daily data submittal, a test stip for calibration and proof are a mapping for quality acceptance. During proofing runs or mapping, the It of other operation needs to be at constant speed and vibration settings frequency and amplitude in the forward direction.

APPLICATION NOTES



U.S. Department of Transportation Federal Highway Administration

BACKGROUND

Intelligent compaction (VI) takes all the generative for off-rolling gatterns. Decimal signals compaction is temperature and time dependent. It commits an architecture that the entire signals must get the control amount of compactions effort. With residency along efforts, there are always some areas of the aphaltment that do not receive total coverage. The amount of these "instead," areas will very depending on roller operations, and will very depending on roller operatures' experience. Viceners, even the most balanted roller operators will seen committee areas of the mark with an inselligent coverage. This creates locations that will have less than optimized marks to control that will have less than optimized marks to control that will have less than optimized marks to control that will have less than optimized marks.

Few derays tests are taken in comparison to the amount of amphilit that is placed. Secare as few areas are tested for density, it makes sense to assert that areas that do not receive total compastion coverage can be and are easily overlooked. There are asserted factors that affect apithal density, such as temperature, exiting subgrade and base course density, rolling patterns and variation insits. To have a quality control tool that can element on or of these factors is very beneficial for a Contractor.

INTELLIGENT COMPACTION FOR ASPHALT PAVING

APPLICATION NOTES: INTELLIGENT COMPACTION IMPLEMENTATION ON SITKA AIRPORT PROJECT

With traditional rolling efforts, some areas of the asphalt mat do not receive total coverage. Contractors can use intelligent compaction (IC) to ensure the entire asphalt mat yets the correct amount of compaction effort.

USE ON THE SITKA AIRPORT PROJECT

Intelligent compaction was required during supfield paining per the specifications for the Sittle Rocky Gutdernez Apport Russway Overlay Project. This project required miling Nichol the existing russway and passing 2 Ni inches on the milled surface. The runsway was closed nightly, and recognised each morning All work had to be completted during the hours of POO pm to POO am.



K was bited as a bid item in the contract. Per the specifications, one K roller was required per pover. The contract required exhelion priving, so two K rollers were used. The standard FHWA K specification was used.

The Contractor, Knik Construction Co., Inc. (Knik). used Wirtgen/HAMM Tandem HD+140 VO IC Rollers. The K rollers were used in the breakdown rolling position. The onboard display was used to monitor pass rounts and temperatures in real time. This was particularly useful for night paving. It was very dark and rolling lines were difficult to see. Both roller operators agreed that had it not been for the real time monitoring of roller position (pass counts) it would have been impossible to guarantee full coverage of the asphalt mat.



FHWA IC WORKSHOPS



FHWA IC EQUIPMENT DEMO



US NATIONAL IC GUIDE SPECS

FHWA Soils/Asphalt IC

Generic - IC Specifications for Soils DOT to modify as applicable to meet State Specifications June 2011

Intelligent Compaction Technology for Soils Applications

DESCRIPTION

This work shall consist of the construction of the rondway fill embaulment utilizing intelligent Compaction (IC) rollers within the limits of the work as described in the plans. IC is defined as a process that uses vibratory rollers equipped with a measurement documentation system that automatically records various critical compaction parameters correlated to agency standard reting protocols in real time during the compaction process. If cutes roller vibration measurements to assess the mechanistic soils properties and to ensure optimum compaction is achieved through continuous monitoring of the operations. Additional information on the IC technology may be found on the website www.meth.gencompaction.com and from the Transportation Research Board - NCHER Peport 165 on Intelligent 501 Compaction Systems.

The Contractor shall supply sufficient numbers of rollers and other associated equipment necessary to complete the compaction requirements for the specific materials. The Contractor will determine the number of IC rollers to use depending on the scope of the project. The IC roller(s) may be utilized during production with other standard compaction equipment and shall be used for the evaluation of the compaction operations.

EQUIPMENT

The IC rollers shall meet the following specific requirements:

- IC rollers shall be self propelled single-drum vibratory rollers equipped with
 accelerometers mounted in or about the drum to measure the interactions between the
 rollers and compacted materials in order to evaluate the applied compaction effort.
 Rollers may be smooth or pad footed drums.
- The output from the roller is designated as the Intelligent Compaction Measurement Value (IC-MV) which represents the stiffness of the materials based on the vibration of the roller drums and the resulting response from the underlying materials.
- 3. The IC rollers shall include an integrated on-board documentation system that is capable of displaying real-time color-coded maps of IC measurement values including the stiffness response values, location of the roller, number of roller passes, machine settings, together with the speed, frequency and amplitude of roller drums. The display unit shall be capable of transferring the data by means of a USB port.
- Roller mounted GPS radio and receiver units shall be mounted on each IC roller. RTK-GPS radio and receivers are required to monitor the location and track the number of nasses of the rollers.

Generic - IC Specifications for HMA DOT to modify as applicable to meet State Specifications

June 2011

Intelligent Compaction Technology for HMA Applications

DESCRIPTION

This work shall consist of the construction of the Hot Mix Asphalt (HMA) utilizing Intelligent Compaction (C) rollers within the limits of the work as described in the plans. It is defined as a process that uses vibratory rollers equipped with a measurement/documentation system that automanically records various excitical compaction parameters correlated to agent standard testing protocols in real time during the compaction process. It cutes roller vibration measurements to assess the mechanistic properties to ensure optimum compaction is achieved through continuous monitoring of the operations. Additional information on the IC technology may be found on the website www.untelligentcompaction com and from the Transportation Research Board. NCHRP Report 676 on intelligent Soil Compaction Systems.

The Contractor shall supply sufficient numbers of rollers and other associated equipment necessary to complete the compaction requirements for the specific materials. The Contractor will determine the number of IC rollers to use depending on the scope of the project. The best location in the paving operations for the IC roller is in the breakdown position and can be used with non-IC rollers.

EQUIPMENT

The IC rollers shall meet the following specific requirements:

- 1. It collers shall be self propelled double-drum vibratory rollers equipped with accelerometers mounted in or about the drum to measure the interactions between the rollers shall also be equipped with non-contact temperature sensors for measuring pavement unface temperature.
- The output from the roller is designated as the Intelligent Compaction Measurement Value (IC-MV) which represents the stiffness of the materials based on the volvation of the roller drums and the resulting response from the underlying materials.
- 3. The IC rollers shall include an integrated on-board documentation system that is capable of displaying real-time color-coded maps of IC measurement values including the stiffness response values, location of the roller, number of roller passes, machine settings, together with the temperature, speed and the frequency and amplitude of roller drums. The display unit shall be capable of transferring the data by means of a USB port.
- Roller mounted GPS radio and receiver units shall be mounted on each IC roller. RTK-GPS radio and receivers are required to monitor the location and track the number of passes of the rollers.

AASHTO PP 81-17 & Data Spec.

Standard Practice for

Intelligent Compaction Technology for Embankment and Asphalt Pavement Applications

AASHTO Designation: PP 81-171

Tech Section: 5c, Quality Assurance and Environmental

Release: Group 1 (April 2017)

Standard Specification for

File Format of Intelligent Construction Data

AASHTO Designation: MP NN-161


AASHO

American Association of State Highway and Transportation Officials 444 North Capitol Street N.W., Suite 249 Washington, D.C. 20001




American Association of State Highway and Transportation Officials 444 North Capitol Street N.W., Suite 249 Washington, D.C. 20001

US DOT IC SPECS




US DOT IC PROJECTS






MNDOT IC IMPLEMENTATION PLAN



(10%)



IICTG — September 26-28, 2018 Minneapolis, MN



Construction
Technologies
Group

www.IITCG.org

CONSTRUCTION INNOVATION NOVA AWARD



TPF STUDY - IC DATA MANAGEMENT



Transportation Pooled Fund Program

TPF-5(334)

Home | About TPF | How to Participate | Open Solicitations | Search | Forms | Success Stories | Related Links | Email Alerts

Home > Home > Search Solicitations and Studies > Study Detail View Study Detail View

Study Detail View

Enhancement to the Intelligent Construction Data Management System (Veta) and Implementation

General Information

Study Number: TPF-5(334) Status: Cleared by FHWA

Lead Agency: Minnesota Department of Transportation

Contract Start Date: Est. Completion Date:

Partners: x , AK , AL , CA , CT , GA , ME , MN , MO , MS , NY , OR , PA

Contract/Other Number:

Last Updated: Sep 19, 2016

Contract End Date:

Contact Information:

Lead Agency Contact(s):

Debra Fick

deb.fick@state.mn.us Phone: 651-366-3759

FHWA Technical Liaison(s):

Richard Duval

Richard.Duval@dot.gov



IC/TP data




Automatic

Manual USB



Manual






Data Export _{USB}, email, etc.






Spot test data


STANDARD IC SOFTWARE - VETA



STANDARD VETA ANALYSIS




IDENTIFY WEAK AREAS





BENEF





Pre-Mapping Subbase




Asphalt Compaction










BENEFITS

Failed density due to static passes




Passed density with vib passes Aided using IC

Courtesy of Rebecca Embacher, MnDOT




IC IMPROVE ROLLING PATTERNS










30%
Increase in
Compaction
Efforts



Lift 1 without IC

< 3 Passes: 31 %

≥ 3 Passes: 69 %

COV:71%

Lift 2 with IC

< 3 Passes: 10 %

≥ 3 Passes: 90 %

COV: 55%

INTELLIGENTCOMPACTION.COM



IC Support

View helpful info and contact us for support at our IC Technical Support Service Center.

Veta Upgrade

Download the latest version of Veta, the IC data management and analysis software.

Learn IC in a Day

Attend an IC workshop and learn how to use IC to ensure longer pavement lives.

Specifications

View and download asphalt and soils IC specifications.

THE FHWA TSSC WEBSITE



Home / Programs / Construction / Technologies and Innovations / IC / Support

Intelligent Compaction

IC Technical Support Service Center

At the Intelligent Compaction Technical Support Service Center (IC TSSC), you can request support and view the IC knowledge base. The knowledge base contains frequently asked questions (FAQ), documentation, workshop information, and IC project information.

We provide email and phone support through the IC TSSC Monday - Friday from 8:00am to 5:00pm Central Standard Time. We answer voicemail messages within a 24-hour time period with the exception of messages left in the system on Fridays-we'll answer those voicemails the next business day.

Call +1 (512) 659 1231 for support with any IC-related topic, including: general (IC equipment/systems/GPS), specifications, workshops, and Veda data management software.

To contact us about IC or Veda for any reason, please submit an IC support ticket.

More Information

- Highway Construction
- Pavement Technology

Contacts

- Antonio Nieves
- Office of Asset Management, Pavements, and Construction 202-366-4597 E-mail Antonio
- Michael Arasteh
 Resource Center

Resource Center (Baltimore) 410-962-0678 E-mail Michael

FHWA IC SUPPORT

- Technical Support Service Center (TSSC)
- http://www.IntelligentCompaction.com/Support/
- Phone: +1 (512) 659-1231
- Email: ICSupport@TheTranstecGroup.com
- 5 days a week (Monday Friday)
- 8:00am to 5:00pm CST



SHRP2 Pavement Solutions R06C RAPID TECHNOLOGIES TO ENHANCE QUALITY CONTROL OF ASPHALT MIXES ROADWAY WORKSHOP

DESCRIPTION

The Federal Highway Administration (FHWA) and the American Association of State Highway and Transportation Officials (AASHTO) are pleased to offer your state DOT the opportunity to host a half-day workshop to highlight the use of paver mounted thermal profiler technology to improve the uniformity of asphalt concrete mixtures being placed in your state. The agenda for this workshop event will include project team presentations, agency and contractor perspectives highlighting the application, benefits. and lessons learned from several field demonstration projects. This outreach activity will disseminate information about the techniques and methods successfully used by State DOTs to increase the uniformity of asphalt concrete mats to extend the life of asphalt pavements.

TARGET AUDIENCE

The target audience is State Highway personnel, contractors, and others involved in the placement of asphalt concrete mixtures.

OUTCOMES

At the end of the event, workshop participants will be familiar with:

- The SHRP2 R06C research and products, including the paver mounted thermal profiler
- State DOT's construction practices
- The various R06C field demonstration projects built around the U.S.
- Contractor and Agency perspectives on the use of thermal profilers for QA and QC

Participants will also have the opportunity to participate in Q&A sessions with the project team and local officials.



Infrared Scanner: Paver Mounted Thermal Profiler Field Demonstration Project

INFORMATION

For more information about the Workshop and other R06C opportunities, please contact:

FHWA: Steve Cooper
Tel: 443-257-7145
Stephen J. Cooper@dot.gov

AASHTO: Kate Kurgan Tel: 202-624-3635 kkurgan@aashto.org

ARA: Harold Von Quintus R06C Subject Matter Expert Tel: 512-218-5088 hvonquintus@ara.com

ARA: Joe Reiter R06C Project Team Tel: 217-356-4500 jreiter@ara.com



er О Ω \boldsymbol{arpi} മ d oun e ğ

Preliminary Agenda

Objectives of the ROGC – Paver Mounted Thermal Profiler Workshop are to: (1) discuss the value added by using Thermal Profiler technology (what it is, why should you care, how this affects your bottom line, how do you get there), and (2) present a summary of the results from the field demonstration projects. The workshop is targeted both to contractor and agency personnel.

Time	Topic/Presentation	Speaker
8:00	Registration	
8:30	Call to Order	Host Agency
8:30 to 8:40	Welcome and Introductions	Host Agency, FHWA and AASHTO
8:40 to 9:15	Introduction to Infrared Technology: What is it and Why is it Needed?	ARA
9:15 to 9:45	Equipment and Software Demonstration: Getting Real Time Information for Decision Making	Equipment Supplier and/or ARA
9:45 to 10:30	Field Demonstration Projects: What was Learned? 1. Application and Use 2. Comparison of Differing Paving Operations/Equipment	ARA
10:30 to 11:45	Break	
10:45 to 11:15	Perspectives of the IR Scanner as a QA Tool: 1. Reducing Risks 2. Trouble Shooting Tool 3. Training	ARA
11:15 to 11:45	Implementation: 1. Lead Agency Strategies/Specifications 2. QC Plan and Paving Operation Management 3. Comments from Contractor and Agency Personnel	Contractor/Agency and/or ARA
11:45 to 12:10	Products from Study: 1. Primer for Paver Mounted Thermal Profiler 2. Case Study Reports from Demonstration Projects 3. Updated Specification: Improving the Mat. 4. Lessons Learned	ARA
12:10 to 12:30	Questions/Answers and Closing Comments and Wrap-up	Host Agency, FHWA, and ARA
12:30 to 1:00	Ground Penetrating Radar Presentation and Demonstration (Optional)	GSSI

- 1. Return on Investment
- 2. Train-the-trainer
- 3. Field Demo
- 4. Retrofit Optimization
- 5. Field data (Error recognition, solution protocol, and corrective action)
- 6. VETA implementation
- 7. Forensic Investigation

- Even though there are 29 States have implemented IC at different paces and levels, most DOTs still faced many obstacles when starting, or during the process of incorporating IC in to their specifications.
- The main obstacle is lack of understating of technology, technical support and training for IC, PMTP, and Veta.
- Veta is an <u>essential software tool</u> for managing IC data as required in the national standard AASHTO PP81, and several state DOT specifications.

- Examples of DOTs who have started implementation and in need of training are AL, AZ, CT, IL, KY, ME, MO, MS, ND, NY, OH, OK, TN.
- Example of DOTs who started the implementation of IC/PMTP, but have been stagnated are NM, PA, TX, VT.
- Caltrans, as a national leader, is challenged with the IC certification/qualification process and further implementation of the technology due to lack of training and technical support.

 The "GOAL" Under the leadership of FHWA, to implement IC similar to programs such as International Roughness Index (IRI) for smoother roads.

Ongoing Research

- NCHRP 24-45 "Evaluating Mechanical Properties of Earth Material During Intelligent Compaction."
- Goal To develop procedure(s) that measure mechanical properties of earth materials to facilitate adoption of IC technologies for field acceptance.
- OH, MI, MN, and IL Field Projects
- This project anticipated to be completed by end of year 2019.

Future Research

"Evaluation of high levels of Intelligent Compaction
Measurement Values (ICMV)" as per Road Map described
in the FHWA ICMV Tech Brief.

 GOAL - To create a research product that will elevate the usage of IC with <u>higher quality of measurements</u> and lay the foundation for future IC certification, and the overall technology.

Future Research

 "Evaluation of Reference/Standard Intelligent Compaction Rollers."

 GOAL - To identify and qualify reference and standard IC rollers capable of directional vibration for the use in future IC certification programs.

AASHTO IC related specifications

- AASHTO PP81-17: Standard Practice for Intelligent Compaction Technology for Embankment and Asphalt Pavement Applications.
- AASHTO MPNN-18: Standard Specification for File
 Format of Intelligent Construction Data. It is a draft
 standard as a companion standard to PP81-17 to provide
 a standard for data exchange and storage.
- AASHTO TCCC Courses

Future AASHTO Activities

• "Development and Implementation of IC Certification Programs and associated AASHTO specifications."

IC equipment/system Certification

IC setup,

IC operators,

IC data management/analysis/report with Veta.

 "Train-the-Trainers Program." An intensive program to equip DOT engineers with IC knowledge and hands-on experience in order for them to train their staff and contractors.



Thank you!

Michael Arasteh

Technical Committee member of IICT

PAVEMENT AND MATERIALS TEAM, FHWA Michael.Arasteh@dot.gov