









Agenda

- Benefits
- Sylvan Avenue
- Willard Street
- Maintenance
- Suggestions
- Future









Benefits of Permeable Pavement

- Improved storm water management
- Reduced downstream impacts
- Improved storm water quality
- Winter Conditions
- Noise









Agenda

- Benefits
- Sylvan Avenue
- Willard Street
- Maintenance
- Suggestions
- Future









Sylvan Ave - Background

Goals...

- Improve storm water management
 - Infiltration or detention
 - Cleaning of stormwater
- Test case for permeable asphalt streets










Sylvan Ave - Background

Sylvan Ave Issues...

- Flat road
- Narrow road
- Narrow ROW
- Ponding











Sylvan Ave - Design

- Initial soil borings
- Deeper soil borings
- To infiltrate or not to infiltrate?


Sample No./Type	Recovery (in.)	Depth	Description of Material
	. 1	0_	Ground Surface Elevation =
			Note I
		1	Note 2
SS-1	18	2	
		3—	SILTY FINE TO MEDIUM SAND FILL - trace clay and gravel - loose - moist - brown - (SM)
SS-2	18	4	
		6-	Note 1: 2.0" Bituminous Concrete Pavement
		7—	Note 2: 6.0" SILTY FINE TO COARSE SAND AND GRAVEL FILL - moist - brown - (SM-GM Fill)



















Sylvan Ave - Design

- 1. Filter Layer
 - Free draining sand
 - 6" Underdrain
 - Impermeable liner
- 2. Reservoir
 - 100 yr design storm
 - 18-24" thickness (35-40% voids)
 - Open graded stone crushed









Sylvan Ave - Design

- 3. Pavement section & details
 - Permeable HMA
 - 3" thick
 - 50 gyratory mix design
 - 75-85% density; 15-25% porosity
 - AC 5.0-6.5%
 - Polymer Binder
 - Standard curb & gutter vs. spill-out









Subgradeprep












Membrane & underdrains












Aggregate











Curb & gutter and sidewalk












Paving





























PermeabilityTest("buckettest")











Agenda

- Benefits
- Sylvan Avenue
- □ Willard Street
- Maintenance
- Suggestions
- Future









Willard St. - Background

- 1. Different Challenges
 - Soils
 - Cross Slope
 - Traffic Volumes

- 2. Different Opportunities
 - Full Infiltration
 - Spill-Out Curbs









Willard St. - Design

- 1. Stone Reservoir
 - Used different aggregate
 - Minimum 30% voids
 - Grid, but no liner


- 2. HMA mix
 - 4" thickness

















Willard St. - Construction











Willard St. - Construction











Agenda

- Benefits
- Sylvan Avenue
- Willard Street
- Maintenance
- Suggestions
- Future









Maintenance - General

Vacuum Road - twice per year (Fall and Spring)

Clogged Areas - Power wash (< 200 psi) with detergent, and vacuumed.



Planter Areas - Well maintained and confined.









Maintenance - General

Exposed Ground - Seed and mulch

Surface Sealing or Resurfacing - Not permitted

Patching (< 50 square feet) - Standard patch

Patching (> 50 square feet) – Permeable pavement

Stock Piling Materials - Not permitted









Maintenance - Winter

Plowing – Plow every 2"+ storm with a slightly raised blade

Salt – Minimal salt permitted

Sand – Not permitted









Maintenance - Residents

Leaves/Yard Waste – Bag or compost. Not in street

Contaminants – Prevent from leaving property

No Dumping - materials or liquids on road

Planter Areas - well maintained and confined

Exposed Ground – Seed and mulch at a minimum







Agenda

- Background
- Design
- Construction
- Maintenance
- Suggestions
- Future









Suggestions

- Design by a licensed engineer
- Deep soil borings
- Careful site selection
- Full-time inspection
- Material selection
- Clear maintenance program









Agenda

- Background
- Design
- Construction
- Maintenance
- Suggestions
- □ Future









Future

- Future of permeable pavement in Ann Arbor?
 - Test case results
 - Possible future projects
 - Another option for stormwater infiltration










Future











Questions?









nhutchinson@a2gov.org 734-794-6000 x43633